chanhvinh.com

Standex Electronics

PARTNER | SOLVE | DELIVER

Series Datasheet

standexelectronics.com

LI Series Reed Relays

- **Features: Small Size High Voltage Relay, High Dielectric Strength, High Insulation Resistance**
- **Applications: Cable & In-Circuit, Battery Mngt., High Voltage Test Equipment, Electric Vehicles & Others**
- **Markets: Solar, Test & Measurement, Automotive & Others**



Part Description: LI00-1A85

Nominal Voltage	Contact Quantity & Contact Form	Switch Model
05, 12, 24	1A	85

Customer Options Contact Data (@ 20°C)	Switch Model 85 (A-Dry)	Unit
Contact Material	Rhodium	
Rated Power (max.) Any DC combination of V&A not to exceed max. rated power	100	W
Switching Voltage (max.) DC or peak AC	1000	V
Switching Current (max.) DC or peak AC	1.0	A
Carry Current (max.) DC or peak AC	2.5	A
Contact Resistance (max.) @ 0.5V & 10mA, Measured with 40% Pull-In Overdrive	150	mOhm
Breakdown Voltage (min.) (upon request)* According to EN60255-27	3 - 4.5*	kVDC
Operating Time (max.) Including Bounce, Measured w/40% Pull-In Overdrive	1.1	ms
Release Time (max.) Measured without Coil Suppression	0.1	ms
Insulation Resistance (min./typ.) Rh<45%, 100V Test Voltage	10^{10} /10^{12}	Ohm
Capacitance (typ.) @ 10kHz across open Switch	0.5	pF

REACH COMPLIANT RoHS COMPLIANT

USA: +1 866.782.6339 | info@standexelectronics.com EMEA: +49 (0)7733 9253 200 | salesemea@standexelectronics.com APAC: +86 21/37606000 | salesasia@standexmeder.com

chanhvinh.com

Standex Electronics

PARTNER | SOLVE | DELIVER

LI Series Reed Relays


Coil Data (at 20°C)		Coil Voltage (VDC)		Coil Resistance (Ohm)	Pull-In Voltage (VDC)	Drop-Out Voltage (VDC)	Coil Power (mW)	Coil Inductance (mH)
Contact Form	Switch Model	Nominal	Max.	Typical (± 10 %)	Max.	Min.	Nominal	Nominal
1A	85	05		200	3.5	0.75	125	
		12		680	8.4	1.4	211	
		24		2,000	16.8	3.6	288	
The Pull-In, Drop-Out Voltage and Coil Resistance will change at rate of 0.4% per °C								

Relay Data (@ 20°C)		Unit
Dielectric Strength Coil/Contact (min.) According to EN60255-27	100	kVDC
Insulation Resistance Coil/Contact (min/typ) 1/2 sine wave, 6md, 3-axis	$10^{12}/10^{13}$	Ohm
Capacitance Coil/Contact (typ.) @10 kHZ	1.2	pF
Shock Resistance (max.) 1/2 sine wave, 6md, 3-axis	100	g
Vibration Resistance (max.) 10 – 2,000 Hz	20	g
Operating Temperature (max.) Surrounding of the relay's housing	-40 to 100	°C
Storage Temperature (max.) Surrounding of the relay's housing	-40 to 125	°C
Soldering Temperature (max.) 5 sec. max.	260	°C
Washability Aqueous rinse suitable. Proper drying necessary.	Fully Sealed	

Handling & Assembly Instructions


- Switching inductive and/or capacitive loads create voltage and/or current peaks, which may damage the relay. Protective circuits need to be used.
- External magnetic fields needs to be taken into consideration, including a too high packing density. This may influence the relays' electrical characteristics.
- Mechanical shock impacts e.g. dropping the relays may cause immediate or post-installation failure.
- Wave soldering: maximum 260°/5 seconds.
- Reflow soldering: Recommendations given by the soldering paste manufacturer need to be considered as well as the temperature limits of other components/processes.

Dimensions (in mm [inch]) Tolerances acc. to ISO 2768-m




Pin-Out (Top View)

*View from top of component 2.54mm [0.10"] pitch grid



Life Test Data (*Load increase reduces life expectancy of Reed Switches)



Please note: All technical specifications on this series datasheet refer to the standard product range. Modifications in the sense of technical progress are reserved. For general information only. For more specific information, please consult the product datasheet, available upon request.

This series datasheet could contain technical inaccuracies or typographical errors. Changes are periodically made to the information herein. These change will be incorporated in future revisions.

For deviating values, most current specifications and products please contact your nearest sales office.

USA: +1 866.782.6339 | info@standexelectronics.com EMEA: +49 (0)7733 9253 200 | salesemea@standexelectronics.com APAC: +86 21/37606000 | salesasia@standexmeder.com