chanhvinh.com


life.augmented

ESDZX168B-1BF4

Datasheet

Ultra-low capacitance single line ESD protection





Product status link
ESDZX168B-1BF4

Features

- Stand-off voltage : 16 V
- Ultra-low clamping voltage: 32 V at 16 A I_{pp} TLP
- Bidirectional protection
- Ultra-low capacitance: 0.12 pF
- Very high bandwidth: > 40 GHz
- Very low dynamic resistance : 0.8 Ω
- 0201 package
- ECOPACK2 compliant component
- Exceeds IEC 61000-4-2 level 4 standard:
  - ±12 kV (contact discharge)
  - ±30 kV (air discharge)

Application

Where transient over voltage protection in ESD sensitive equipment is required, such as:

- USB4, USB 3.1 Gen 1 and Gen 2
- HDMI 2.1
- Ethernet 1G, 10G
- DisplayPort
- LVDS

Description

The ESDZX168B-1BF4 is a bidirectional single line TVS diode designed to protect the data lines or other I/O ports against ESD transients. Thanks to extra low capacitance, ESDZX168B-1BF4 can protect high-speed differential lines with no impact on signal integrity.

With an extremely low clamping voltage, ESDZX168B-1BF4 is able to protect the most sensitive, submicron technology circuits.

chanhvinh.com

1 Characteristics

Table 1. Absolute maximum ratings (T_{amb} = 25 °C)

Symbol	Parameter		Value	Unit
V_{pp}	Peak pulse voltage	IEC 61000-4-2 contact discharge IEC 61000-4-2 air discharge	±12 ±30	kV
I_{pp}	Peak pulse current (8/20 µs)		2.2	A
T_j	Operating junction temperature range		-55 to +150	°C
T_{stg}	Storage junction temperature range		-65 to +150	
T_L	Maximum lead temperature for soldering during 10 s		260	

Figure 1. Electrical characteristics (definitions)




Table 2. Electrical characteristics (values) (T_{amb} = 25° C)

Symbol	Parameter	Test condition	Min.	Typ.	Max.	Unit
V_{trig}	Trigger voltage		18	23	25	V
V_H	Holding voltage		16			V
V_{RM}	Reverse working voltage				16	V
I_{RM}	Leakage current	V_{RM} = 16 V			50	nA
I_R	Leakage current	V_R = 5 V			10	nA
V_{CL}(1)	Clamping voltage	IEC 61000-4-2, 8 kV contact discharge measured after 30 ns		32		V
V_{CL}(1)	Clamping voltage	8/20 µs waveform, I_{PP} = 2 A			24	V
V_{CL}(1)	TLP measurement (pulse duration 100ns)	I_{PP} = 16 A		32		V
		I_{PP} = 4 A		23		
R_D(1)	Dynamic resistance	TLP - Pulse duration 100 ns - I_{PP} [1 A – 16 A]		0.8		Ω
C_{LINE}	Line capacitance	V_{LINE} = 0 V, F = 1 MHz		0.7		pF
C_{LINE}(1)	Line capacitance	V_{LINE} = 0 V, F = 2.5 GHz		0.11	0.17	pF
		V_{LINE} = 0 V, F = 5 GHz		0.10	0.15	
F_C(1)	-3dB			> 40		GHz

1. *Evaluated by characterization – Not tested in production.*

chanhvinh.com

1.1 Characteristics (curves)

Figure 2. Leakage current versus junction temperature (typical values)




Figure 3. Junction capacitance versus frequency (typical values)




Figure 4. ESD response to IEC 61000-4-2 (+8 kV contact discharge)




Figure 5. ESD response to IEC 61000-4-2 (-8 kV contact discharge)




Figure 6. S21 attenuation measurement result





Figure 7. TLP measurement



chanhvinh.com

2 Package information

To meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions, and product status are available at: www.st.com. ECOPACK is an ST trademark.

2.1 0201 package information

Figure 8. Package outline




Table 3. Package mechanical data

Ref.	Dimensions		
	Millimeters		
	Min.	Typ.	Max.
A	0.180	0.200	0.220
b	0.1475	0.1675	0.1875
D	0.560	0.580	0.600
D1		0.3375	
E	0.260	0.280	0.300
E1	0.185	0.205	0.225
fD		0.0375	
fE		0.0375	

chanhvinh.com

2.2 Packing and marking information

Figure 9. **Marking layout**



The marking « U » can be rotated by a multiple of 90° to differentiate assembly location.

Figure 10. **Package orientation in reel**




Figure 11. **Tape outline**




Table 4. **Tape and reel mechanical data**


Ref.	Dimensions		
	Millimeters		
	Min.	Typ.	Max.
A0	0.31	0.34	0.37
B0	0.61	0.64	0.67
D0	1.40	1.50	1.60
F	3.45	3.50	3.55
K0	0.21	0.24	0.27
P0	3.90	4.00	4.10
P1	1.95	2.00	2.05
P2	1.95	2.00	2.05
W	7.90	8.00	8.30

chanhvinh.com

3 Recommendation on PCB assembly

3.1 Footprint

Figure 12. **Recommended footprint in mm**




Note: Solder mask defined (SMD) recommended.

3.2 Stencil opening design

Stencil opening thickness: 75 µm / 3 mils

Figure 13. **Stencil opening recommendations**



chanhvinh.com

3.3 Solder paste

1. Halide-free flux qualification ROL0 according to ANSI/J-STD-004.
2. “No clean” solder paste is recommended.
3. Offers a high tack force to resist component movement during high speed.
4. Use solder paste with fine particles: powder particle size 20-38 µm.

3.4 Placement


1. Manual positioning is not recommended.
2. It is recommended to use the lead recognition capabilities of the placement system, not the outline centering
3. Standard tolerance of ±0.05 mm is recommended.
4. 1.0 N placement force is recommended. Too much placement force can lead to squeezed out solder paste and cause solder joints to short. Too low placement force can lead to insufficient contact between package and solder paste that could cause open solder joints or badly centered packages.
5. To improve the package placement accuracy, a bottom side optical control should be performed with a high resolution tool.
6. For assembly, a perfect supporting of the PCB (all the more on flexible PCB) is recommended during solder paste printing, pick and place and reflow soldering by using optimized tools.

3.5 PCB design preference

1. To control the solder paste amount, the closed via is recommended instead of open vias.
2. The position of tracks and open vias in the solder area should be well balanced. A symmetrical layout is recommended, to avoid any tilt phenomena caused by asymmetrical solder paste due to solder flow away.

3.6 Reflow profile

Figure 14. ST ECOPACK recommended soldering reflow profile for PCB mounting



Note: Minimize air convection currents in the reflow oven to avoid component movement. Maximum soldering profile corresponds to the latest IPC/JEDEC J-STD-020.

chanhvinh.com

4 Ordering information

Table 5. Ordering information

Order code	Marking	Package	Weight	Base qty.	Delivery mode
ESDZX168B-1BF4	U[1]	ST0201	0.100 mg	17000	Tape and reel

1. *The marking can be rotated by multiples of 90° to differentiate assembly location*

chanhvinh.com

chanhvinh.com

Revision history

Table 6. **Document revision history**

Date	Revision	Changes
21-Sep-2023	1	Initial release.
10-Jul-2024	2	Updated *Table 2*, *Figure 3*, *Figure 4*, *Figure 5*, and *Figure 6*.
16-Sep-2024	3	Updated Product status link on cover page.

chanhvinh.com

chanhvinh.com

IMPORTANT NOTICE – READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgment.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2024 STMicroelectronics – All rights reserved

chanhvinh.com