

chanhvinh.com

L293D
L293DD

PUSH-PULL FOUR CHANNEL DRIVER WITH DIODES

- 600mA OUTPUT CURRENT CAPABILITY PER CHANNEL
- 1.2A PEAK OUTPUT CURRENT (non repetitive) PER CHANNEL
- ENABLE FACILITY
- OVERTEMPERATURE PROTECTION
- LOGICAL "0" INPUT VOLTAGE UP TO 1.5 V (HIGH NOISE IMMUNITY)
- INTERNAL CLAMP DIODES





SO(12+4+4) **Powerdip (12+2+2)**

ORDERING NUMBERS:

L293DD L293D

DESCRIPTION

The Device is a monolithic integrated high voltage, high current four channel driver designed to accept standard DTL or TTL logic levels and drive inductive loads (such as relays solenoides, DC and stepping motors) and switching power transistors.


To simplify use as two bridges each pair of channels is equipped with an enable input. A separate supply input is provided for the logic, allowing operation at a lower voltage and internal clamp diodes are included.

This device is suitable for use in switching applications at frequencies up to 5 kHz.

The L293D is assembled in a 16 lead plastic packaage which has 4 center pins connected together and used for heatsinking

The L293DD is assembled in a 20 lead surface mount which has 8 center pins connected together and used for heatsinking.

BLOCK DIAGRAM




chanhvinh.com


ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
V_S	Supply Voltage	36	V
V_{SS}	Logic Supply Voltage	36	V
V_i	Input Voltage	7	V
V_{en}	Enable Voltage	7	V
I_o	Peak Output Current (100 µs non repetitive)	1.2	A
P_{tot}	Total Power Dissipation at T_{pins} = 90 °C	4	W
T_{stg}, T_j	Storage and Junction Temperature	– 40 to 150	°C

PIN CONNECTIONS (Top view)



SO(12+4+4)



Powerdip(12+2+2)

THERMAL DATA

Symbol	Decription		DIP	SO	Unit
$R_{th\ j\text{-}pins}$	Thermal Resistance Junction-pins	max.	–	14	°C/W
$R_{th\ j\text{-}amb}$	Thermal Resistance junction-ambient	max.	80	50 (*)	°C/W
$R_{th\ j\text{-}case}$	Thermal Resistance Junction-case	max.	14	–	

(*) With 6sq. cm on board heatsink.

chanhvinh.com

ELECTRICAL CHARACTERISTICS (for each channel, V_S = 24 V, V_{SS} = 5 V, T_{amb} = 25 °C, unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_S	Supply Voltage (pin 10)		V_{SS}		36	V
V_{SS}	Logic Supply Voltage (pin 20)		4.5		36	V
I_S	Total Quiescent Supply Current (pin 10)	V_i = L ; I_O = 0 ; V_{en} = H		2	6	mA
		V_i = H ; I_O = 0 ; V_{en} = H		16	24	mA
		V_{en} = L			4	mA
I_{SS}	Total Quiescent Logic Supply Current (pin 20)	V_i = L ; I_O = 0 ; V_{en} = H		44	60	mA
		V_i = H ; I_O = 0 ; V_{en} = H		16	22	mA
		V_{en} = L		16	24	mA
V_{IL}	Input Low Voltage (pin 2, 9, 12, 19)		– 0.3		1.5	V
V_{IH}	Input High Voltage (pin 2, 9, 12, 19)	$V_{SS} \leq 7$ V	2.3		V_{SS}	V
		$V_{SS} > 7$ V	2.3		7	V
I_{IL}	Low Voltage Input Current (pin 2, 9, 12, 19)	V_{IL} = 1.5 V			– 10	µA
I_{IH}	High Voltage Input Current (pin 2, 9, 12, 19)	2.3 V ≤ V_{IH} ≤ V_{SS} – 0.6 V		30	100	µA
$V_{en\ L}$	Enable Low Voltage (pin 1, 11)		– 0.3		1.5	V
$V_{en\ H}$	Enable High Voltage (pin 1, 11)	$V_{SS} \leq 7$ V	2.3		V_{SS}	V
		$V_{SS} > 7$ V	2.3		7	V
$I_{en\ L}$	Low Voltage Enable Current (pin 1, 11)	$V_{en\ L}$ = 1.5 V		– 30	– 100	µA
$I_{en\ H}$	High Voltage Enable Current (pin 1, 11)	2.3 V ≤ $V_{en\ H}$ ≤ V_{SS} – 0.6 V			± 10	µA
$V_{CE(sat)H}$	Source Output Saturation Voltage (pins 3, 8, 13, 18)	I_O = – 0.6 A		1.4	1.8	V
$V_{CE(sat)L}$	Sink Output Saturation Voltage (pins 3, 8, 13, 18)	I_O = + 0.6 A		1.2	1.8	V
V_F	Clamp Diode Forward Voltage	I_O = 600nA		1.3		V
t_r	Rise Time (*)	0.1 to 0.9 V_O		250		ns
t_f	Fall Time (*)	0.9 to 0.1 V_O		250		ns
t_{on}	Turn-on Delay (*)	0.5 V_i to 0.5 V_O		750		ns
t_{off}	Turn-off Delay (*)	0.5 V_i to 0.5 V_O		200		ns

(*) See fig. 1.

chanhvinh.com

TRUTH TABLE (one channel)

Input	Enable (*)	Output
H	H	H
L	H	L
H	L	Z
L	L	Z

Z = High output impedance
(*) Relative to the considered channel

Figure 1: Switching Times






Figure 2: Junction to ambient thermal resistance vs. area on board heatsink (SO12+4+4 package)




chanhvinh.com

DIM.	mm			inch		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
a1	0.51			0.020		
B	0.85		1.40	0.033		0.055
b		0.50			0.020	
b1	0.38		0.50	0.015		0.020
D			20.0			0.787
E		8.80			0.346	
e		2.54			0.100	
e3		17.78			0.700	
F			7.10			0.280
I			5.10			0.201
L		3.30			0.130	
Z			1.27			0.050

OUTLINE AND MECHANICAL DATA




Powerdip 16




chanhvinh.com

DIM.	mm			inch		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
A	2.35		2.65	0.093		0.104
A1	0.1		0.3	0.004		0.012
B	0.33		0.51	0.013		0.020
C	0.23		0.32	0.009		0.013
D	12.6		13	0.496		0.512
E	7.4		7.6	0.291		0.299
e		1.27			0.050	
H	10		10.65	0.394		0.419
h	0.25		0.75	0.010		0.030
L	0.4		1.27	0.016		0.050
K	0° (min.)8° (max.)					

OUTLINE AND MECHANICAL DATA



SO20



SO20MEC

chanhvinh.com

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specification mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 2003 STMicroelectronics – Printed in Italy – All Rights Reserved

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States.

http://www.st.com