
chanhvinh.com

life.augmented

LD56020

Datasheet

Low input voltage, 200 mA ultra-low noise LDO



Flip-Chip4



SOT23-5L

Maturity status link
LD56020

Features

- Input voltage from 1.1 V to 5.5 V
- Ultra-low dropout voltage (190 mV max. at 200 mA load)
- Low ground current (18 µA typ. at no load)
- Output voltage tolerance: ± 2 % overtemperature, ± 1% at 25 °C
- 200 mA guaranteed output current
- Ultra-low output noise: 8.8 μV_{RMS} (10 Hz to 100 kHz)
- 50 mV output voltage steps (available on request) from 0.6 V to 4.0 V
- Logic-controlled electronic shutdown
- Thermal shutdown
- Output active discharge function
- Packages: Flip-chip4 0.65 x 0.65 mm² and SOT23-5L

Applications

- Smartphones/tablets
- Image sensors
- VCO and RF modules

Description

The LD56020 is a high accuracy voltage regulator which provides 0.2 A of current. It is available in CSP 0.65 x 0.65 mm² package, SOT23-5L, allowing the maximum space saving.


The device is stabilized with a small ceramic capacitor on input and output. The ultra-low drop, low quiescent current and short-circuit current foldback make the LD56020 suitable for low power battery-operated applications.

An enable logic control function puts the LD56020 in shutdown mode allowing a total current consumption lower than 0.1 µA. Thermal protection is also included.

chanhvinh.com

1 Diagram


Figure 1. **Block diagram**



chanhvinh.com

2 Pin configuration

Figure 2. **Pin connection**



SOT23-5L
(top view)

Flip-chip 4
(marking view)


Table 1. **Pin description**

Symbol	SOT23-5L	Flip-Chip 4	Description
V_{IN}	1	A1	LDO Supply voltage
V_{OUT}	5	A2	LDO Output voltage
GND	2	B2	Ground
EN	3	B1	Enable input: set V_{EN} = high to turn on the device; V_{EN} = low to turn off the device. This pin is internally pulled down via a 1 MΩ resistor
NC	4	-	Not internally connected: can be connected to GND
Exposed pad	-	-	Must be connected to GND.

chanhvinh.com

3 Typical application diagram

Figure 3. **Application diagram**



chanhvinh.com

4 Maximum ratings

Table 2. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{IN}	Input supply voltage	- 0.3 to 7	V
V_{OUT}	Output voltage	- 0.3 to 7	V
I_{OUT}	Output current	Internally limited	A
EN	Enable pin voltage	- 0.3 to V_{IN} + 0.3	V
PD	Power dissipation	Internally limited	W
ESD	Charge device model	± 1000	V
	Human body model	± 2000	
T_{J-OP}	Operating junction temperature	- 40 to 125	°C
T_{J-MAX}	Maximum junction temperature	150	°C
T_{STG}	Storage temperature	- 55 to 150	°C

Table 3. Thermal data

Symbol	Parameter	Flip-Chip4	SOT23-5L	Unit
R_{thja}	Thermal resistance, junction-to-ambient	210	200	°C/W

chanhvinh.com

5 Electrical characteristics

V_{IN} = $V_{OUT(NOM)}$ + 0.3 V; I_{OUT} = 1 mA; C_{IN} = 1 µF, C_{OUT} = 1 µF; V_{EN} = 1 V; typical values are at T_J = 25 °C; min/max values are at -40 °C ≤ T_J ≤ 85 °C, unless otherwise specified.

Table 4. Electrical characteristics

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
V_{IN}	Operating input voltage		1.1		5.5	V
V_{OUT}	Output voltage accuracy	$V_{OUT(NOM)}$ + 0.3 V ≤ V_{IN} ≤ 5.5 V; V_{OUT} ≥ 1.5 V	-2.0		+2.0	%
		$V_{OUT(NOM)}$ + 0.3 V ≤ V_{IN} ≤ 5.5 V; V_{OUT} ≤ 1.5 V	-30		+30	mV
V_{OUT}	Output voltage range	50 mV steps	0.6		4.0	V
ΔV_{OUT-IN}	V_{IN} Static regulation	$V_{OUT(NOM)}$ + 0.3 V ≤ V_{IN} ≤ 5.0 V, I_{OUT} = 1 mA		0.01	0.1	%/V
ΔV_{OUT}	Static load regulation for CSP	I_{OUT} = 1 mA to 200 mA		1.5	5	mV
	Static load regulation for SOT 23-5L	I_{OUT} = 1 mA to 200 mA		15	20	
V_{DROP}	Dropout voltage	I_{OUT} = 0.05 A; V_{OUT} = 1.05 V V_{OUT} = 97% of $V_{OUT(NOM)}$		40	90	mV
V_{DROP}	Dropout voltage for CSP	I_{OUT} = 0.10 A; V_{OUT} = 1.05 V V_{OUT} = 97% of $V_{OUT(NOM)}$		70	130	mV
		I_{OUT} = 0.11 A; V_{OUT} = 1.2 V V_{OUT} = 97% of $V_{OUT(NOM)}$		60	140	
		I_{OUT} = 0.2 A; V_{OUT} = 1.2 V V_{OUT} = 97% of $V_{OUT(NOM)}$		110	190	
	Dropout voltage for SOT 23-5L	I_{OUT} = 0.10 A; V_{OUT} = 1.05 V V_{OUT} = 97% of $V_{OUT(NOM)}$		80	100	mV
		I_{OUT} = 0.11 A; V_{OUT} = 1.2 V V_{OUT} = 97% of $V_{OUT(NOM)}$		70	150	
		I_{OUT} = 0.2 A; V_{OUT} = 1.2 V V_{OUT} = 97% of $V_{OUT(NOM)}$		120	200	
eN	Output noise voltage	$V_{OUT(NOM)}$ = 1.0 V; V_{IN} = 1.5 V 10 Hz to 100 kHz, I_{OUT} = 1 mA		8.8		μV_{RMS}
SVR_{IN}	V_{IN} Supply voltage rejection	V_{IN} = $V_{OUT(NOM)}$ + 0.3 V ± V_{RIPPLE} V_{RIPPLE} = 0.2 V_{pp}, Freq = 100 Hz, I_{OUT} = 20 mA		90		dB
		V_{IN} = $V_{OUT(NOM)}$ + 0.3 V ± V_{RIPPLE} V_{RIPPLE} = 0.2 V_{pp} Freq = 1 kHz, I_{OUT} = 20 mA		95		
		V_{IN} = $V_{OUT(NOM)}$ + 0.3 V ± V_{RIPPLE} V_{RIPPLE} = 0.2 V_{pp} Freq = 10 kHz, I_{OUT} = 20 mA		85		
		V_{IN} = $V_{OUT(NOM)}$ + 0.3 V ± V_{RIPPLE} V_{RIPPLE} = 0.2 V_{pp} Freq = 100 kHz, I_{OUT} = 20 mA		55		
I_Q	Quiescent curerent	I_{OUT} = 0 mA		20	25	µA
I_{Q_OFF}	Standby Current	V_{EN} = GND		0.01	1	µA

chanhvinh.com

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_{LIM}	Output current limit	V_{OUT} = 0.9 x $V_{OUT(NOM)}$	250	300		mA
I_{SC}	Short-circuit current	V_{OUT} = 0 (foldback protection)		100	TBD	mA
V_{EN}	Enable input logic low				0.2	V
	Enable input logic high		0.7			
I_{EN}	Enable pin input current	V_{EN} = 1.1 V (internal pull-down)		0.2	0.5	µA
T_{ON}	Turn-on time	$V_{OUT(NOM)}$ = 1.0 V		150		µs
T_{SHDN}	Thermal shutdown			160		°C
	Hysteresis			20		

Table 5. Recommended Input and output capacitors

Symbol	Parameter	Test Conditions	Min.	Typ.	Max	Unit
C_{IN}	Input capacitance	Stability	0.7	1		µF
C_{OUT}	Output capacitance		0.7	1	10	
ESR	Output/Input capacitance		5		500	mΩ

chanhvinh.com

6 Typical performance characteristics

The following plots are referred to LD56020 in the typical application circuit and, unless otherwise noted, at T_A = 25 °C

Figure 4. Output voltage vs. temperature (V_{IN} = 1.4 V)




Figure 5. Output voltage vs. V_{IN}




Figure 6. Line regulation vs. temperature




Figure 7. Load regulation vs. temperature




Figure 8. Dropout voltage vs. temperature, (I_{OUT} = 50 mA)





Figure 9. Dropout voltage vs. temperature, (I_{OUT} = 200 mA)



chanhvinh.com

Figure 10. Dropout voltage vs. output current




Figure 11. I_{LIM} vs. temperature




Figure 12. I_{short} vs. temperature




Figure 13. Quiescent current vs. temperature




Figure 14. Quiescent current vs. temperature I_{OUT} = 200 mA





Figure 15. Quiescent current vs. input voltage



chanhvinh.com

Figure 16. Enable current vs. temperature





Figure 17. Turn-on time



Vin = Vout(nom) + 0.3 V, Ven from 0 to Vin, tr=tf=1µs, C_{IN} = C_{OUT} = 1µF, Iout = 0 mA

Figure 18. Turn-on time I_{OUT} = 0 mA



Vin = Ven = from 0 to 1.3 V tr = 1 µs, C_{IN} = C_{OUT} = 1µF Iout = 0 mA

Figure 19. Turn-on time I_{OUT} = 200 mA




Vin = Ven = from 0 to 5.5 V tr = 1 µs, C_{IN} = C_{OUT} = 1µF Iout = 200 mA

Figure 20. Line regulation transient



V_{EN}=1V Vin=Vout(nom)+0.3V to 5.5V, tr=tf=5µs Iout=1mA C_{IN} = C_{OUT} = 1µF


Figure 21. Line regulation transient (I_{OUT} = 1 µA)



V_{EN}=1V Vin=Vout(nom)+0.3V to 5.5V, tr=tf=5µs Iout=1mA C_{IN} = C_{OUT} = 1µF


chanhvinh.com

Figure 22. Load transient



V_{EN}=1 V, Vin=3.3 V, Iout=1 mA to 200 mA, tr=tf= 5 µs C_{IN}=C_{OUT}=1 µF

Figure 23. Stability plane



V_{EN}=1V Vin=from Vout(nom)+0.3V to 5.5V Iout=from 1mA to 200mA,C_{IN} =1µF


chanhvinh.com

7 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: www.st.com. ECOPACK is an ST trademark.

7.1 SOT23-5L package information

Figure 24. SOT23-5L package outline




chanhvinh.com

Table 6. **SOT23-5L mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A			1.25
A1	0.04		0.10
A2	1.00	1.10	1.20
A3	0.60	0.65	0.70
b	0.33		0.41
b1	0.32	0.35	0.38
c	0.15		0.19
c1	0.14	0.15	0.16
D	2.82	2.92	3.02
E	2.60	2.80	3.00
E1	1.50	1.60	1.70
e	0.95 CS		
e1	1.90 BSC		
L	0.30		0.60
Θ	0		8°


Figure 25. **SOT23-5L recommended footprint**



chanhvinh.com

7.2 Flip-chip 4 package information

Figure 26. **Flip-chip 4 package mechanical outline**




8387748 option F

chanhvinh.com

Table 7. **Flip-chip 4 mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A	0.375	0.410	0.445
A1	0.145	0.160	0.175
A2	0.230	0.250	0.270
b	0.189	0.210	0.231
D	0.660	0.690	0.72
D1		0.350	
E	0.660	0.690	0.720
E1		0.350	
SD		0.175	
SE		0.175	
f		0.170	
ccc		0.075	

Figure 27. **Flip-chip 4 package footprint**




chanhvinh.com

7.3 Flip-chip 4 packing information

Table 8. Reel mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A			180
C	12.8	13	13.2
D	20.2		
N	60		
T			14.4

Figure 28. Reel



Note: Drawing not in scale

chanhvinh.com

Figure 29. **Tape drawing**






Figure 30. **Reel orientation**



MARKING VIEW



chanhvinh.com

8 Ordering information

Table 9. **Order codes**

Order code	Package	Output voltage	Marking	Packing
LD56020M100R	SOT23-5L (1)	1.0 V	TBD	Tape and reel
LD56020M110R		1.1 V	TBD	
LD56020M120R		1.2 V		
LD56020M180R		1.8 V		
LD56020M300R		3.0 V		
LD56020M330R		3.3 V		
LD56020J100R	Flip-Chip4	1.0 V	TBD	Tape and reel
LD56020J110R		1.1 V	TBD	
LD56020J120R		1.2 V		
LD56020J180R		1.8 V		
LD56020J300R (1)		3.0 V		
LD56020J330R (1)		3.3 V		

1. *Available on request.*

chanhvinh.com

Revision history

Table 10. **Document revision history**

Date	Revision	Changes
01-Mar-2022	1	Initial release.

chanhvinh.com

Contents

1 Diagram 2
2 Pin configuration 3
3 Typical application diagram 4
4 Maximum ratings 5
5 Electrical characteristics 6
6 Typical performance characteristics 8
7 Package information 12
7.1 SOT23-5L package information 12
7.2 Flip-chip 4 package information 14
7.3 Flip-chip 4 packing information 16
8 Ordering information 18
Revision history 19

chanhvinh.com

List of tables

Table 1. Pin description . . . 3
Table 2. Absolute maximum ratings . . . 5
Table 3. Thermal data . . . 5
Table 4. Electrical characteristics . . . 6
Table 5. Recommended Input and output capacitors . . . 7
Table 6. SOT23-5L mechanical data . . . 13
Table 7. Flip-chip 4 mechanical data . . . 15
Table 8. Reel mechanical data . . . 16
Table 9. Order codes . . . 18
Table 10. Document revision history . . . 19

chanhvinh.com

List of figures

Figure 1. Block diagram . . . 2
Figure 2. Pin connection . . . 3
Figure 3. Application diagram . . . 4
Figure 4. Output voltage vs. temperature (V_{IN} = 1.4 V) . . . 8
Figure 5. Output voltage vs. V_{IN} . . . 8
Figure 6. Line regulation vs. temperature . . . 8
Figure 7. Load regulation vs. temperature . . . 8
Figure 8. Dropout voltage vs. temperature, (I_{OUT} = 50 mA) . . . 8
Figure 9. Dropout voltage vs. temperature, (I_{OUT} = 200 mA) . . . 8
Figure 10. Dropout voltage vs. output current . . . 9
Figure 11. I_{LIM} vs. temperature . . . 9
Figure 12. I_{short} vs. temperature . . . 9
Figure 13. Quiescent current vs. temperature . . . 9
Figure 14. Quiescent current vs. temperature I_{OUT} = 200 mA . . . 9
Figure 15. Quiescent current vs. input voltage . . . 9
Figure 16. Enable current vs. temperature . . . 10
Figure 17. Turn-on time . . . 10
Figure 18. Turn-on time I_{OUT} = 0 mA . . . 10
Figure 19. Turn-on time I_{OUT} = 200 mA . . . 10
Figure 20. Line regulation transient . . . 10
Figure 21. Line regulation transient (I_{OUT} = 1 µA) . . . 10
Figure 22. Load transient . . . 11
Figure 23. Stability plane . . . 11
Figure 24. SOT23-5L package outline . . . 12
Figure 25. SOT23-5L recommended footprint . . . 13
Figure 26. Flip-chip 4 package mechanical outline . . . 14
Figure 27. Flip-chip 4 package footprint . . . 15
Figure 28. Reel . . . 16
Figure 29. Tape drawing . . . 17
Figure 30. Reel orientation . . . 17

chanhvinh.com

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, please refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2022 STMicroelectronics – All rights reserved