
chanhvinh.com

life.augmented


SCT018H65G3AG

Datasheet

Automotive-grade silicon carbide Power MOSFET 650 V, 20 mΩ typ., 55 A in an H²PAK-7 package



H²PAK-7



STPOWER

Product status link
SCT018H65G3AG

Product summary	
Order code	SCT018H65G3AG
Marking	18H65G3AG
Package	H²PAK-7
Packing	Tape and reel

Features

Order code	V_{DS}	$R_{DS(on)}$ typ.	I_D
SCT018H65G3AG	650 V	20 mΩ	55 A

- AEC-Q101 qualified
- Very low $R_{DS(on)}$ over the entire temperature range
- High speed switching performances
- Very fast and robust intrinsic body diode
- Source sensing pin for increased efficiency

Applications

- Main inverter (electric traction)
- DC/DC converter for EV/HEV
- On board charger (OBC)

Description

This silicon carbide Power MOSFET device has been developed using ST's advanced and innovative 3rd generation SiC MOSFET technology. The device features a very low $R_{DS(on)}$ over the entire temperature range combined with low capacitances and very high switching operations, which improve application performance in frequency, energy efficiency, system size and weight reduction.

chanhvinh.com

1 Electrical ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{DS}	Drain-source voltage	650	V
V_{GS}	Gate-source voltage	-10 to 22	V
	Gate-source voltage (recommended operating values)	-5 to 18	
	Gate-source transient voltage, t_p < 1 µs, t ≤ 10 hours over lifetime	-11 to 25	
I_D(1)	Drain current (continuous) at T_C = 25 °C	55	A
	Drain current (continuous) at T_C = 100 °C	55	
I_{DM}(2)	Drain current (pulsed)	312	A
P_{TOT}	Total power dissipation at T_C = 25 °C	385	W
T_{stg}	Storage temperature range	-55 to 175	°C
T_J	Operating junction temperature range		°C

1. *I_D is limited by package.*
2. *Pulse width is limited by safe operating area.*

Table 2. Thermal data

Symbol	Parameter	Value	Unit
R_{thJC}	Thermal resistance, junction-to-case	0.39	°C/W
R_{thJA}	Thermal resistance, junction-to-ambient	50	°C/W

chanhvinh.com

2 Electrical characteristics

T_C = 25 °C unless otherwise specified.

Table 3. On/off states

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	V_{GS} = 0 V, I_D = 1 mA	650			V
I_{DSS}	Zero gate voltage drain current	V_{GS} = 0 V, V_{DS} = 650 V			10	µA
I_{GSS}	Gate-body leakage current	V_{DS} = 0 V, V_{GS} = -10 to 22 V			±100	nA
$V_{GS(th)}$	Gate threshold voltage	V_{DS} = V_{GS}, I_D = 5 mA	1.8	3.0	4.2	V
$R_{DS(on)}$	Static drain-source on-resistance	V_{GS} = 15 V, I_D = 30 A		24		mΩ
		V_{GS} = 18 V, I_D = 30 A		20	27	
		V_{GS} = 18 V, I_D = 30 A, T_J = 175 °C		28		

Table 4. Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{iss}	Input capacitance	V_{DS} = 400 V, f = 1 MHz, V_{GS} = 0 V	-	2124	-	pF
C_{oss}	Output capacitance		-	184	-	pF
C_{rss}	Reverse transfer capacitance		-	18	-	pF
Q_g	Total gate charge	V_{DD} = 400 V, V_{GS} = -5 to 18 V, I_D = 30 A	-	79.4	-	nC
Q_{gs}	Gate-source charge		-	23.5	-	nC
Q_{gd}	Gate-drain charge		-	20.3	-	nC
R_g	Gate input resistance	f = 1 MHz, I_D = 0 A	-	1.14	-	Ω

Table 5. Switching energy (inductive load)

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
E_{on}	Turn-on switching energy	V_{DD} = 400 V, I_D = 30 A,	-	209	-	µJ
E_{off}	Turn-off switching energy	R_G = 18 Ω, V_{GS} = -5 V to 18 V	-	184	-	µJ

Table 6. Switching times

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	V_{DD} = 400 V, I_D = 30 A, R_G = 18 Ω, V_{GS} = -5 to 18 V	-	25	-	ns
t_r	Rise time		-	28	-	ns
$t_{d(off)}$	Turn-off delay time		-	56	-	ns
t_f	Fall time		-	25	-	ns

chanhvinh.com

Table 7. Reverse SiC diode characteristics

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_{SD}(1)	Continuous diode forward current	T_C = 25 °C	-		55	A
		T_C = 100 °C	-		55	
V_{SD}	Diode forward voltage	I_{SD} = 30 A, V_{GS} = 0 V	-	2.6		V
t_{rr}	Reverse recovery time	I_{SD} = 30 A, di/dt = 1000 A/µs, V_{DD} = 400 V	-	20		ns
Q_{rr}	Reverse recovery charge		-	147		nC
I_{RRM}	Reverse recovery current		-	11.8		A

1. *I_{SD} is limited by package.*

chanhvinh.com

2.1 Electrical characteristics (curves)

Figure 1. Safe operating area




Figure 2. Maximum transient thermal impedance




Figure 3. Typical output characteristics (T_J = 25 °C)




Figure 4. Typical output characteristics (T_J = 175 °C)




Figure 5. Typical transfer characteristics





Figure 6. Total power dissipation



chanhvinh.com

Figure 7. Typical gate charge characteristics




Figure 8. Typical capacitance characteristics




Figure 9. Typical switching energy vs drain current




Figure 10. Typical switching energy vs supply voltage




Figure 11. Typical switching energy vs gate resistance





Figure 12. Normalized breakdown voltage vs temperature



chanhvinh.com

Figure 13. Normalized gate threshold vs temperature




Figure 14. Normalized on-resistance vs temperature




Figure 15. Typical reverse conduction characteristics (T_J = 25 °C)





Figure 16. Typical reverse conduction characteristics (T_J = 175 °C)




chanhvinh.com

3 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: www.st.com. ECOPACK is an ST trademark.

3.1 H²PAK-7 package information

Figure 17. **H²PAK-7 package outline**




DM00249216_6

chanhvinh.com

Table 8. **H²PAK-7 package mechanical data**

Dim.	mm	
	Min.	Max.
A	4.30	4.80
A1	0.03	0.20
C	1.17	1.37
e	2.34	2.74
e1	4.88	5.28
e2	7.42	7.82
E	0.45	0.60
F	0.50	0.70
H	10.00	10.40
H1	7.40	8.00
L	14.75	15.25
L1	1.27	1.40
L2	4.35	4.95
L3	6.85	7.25
M	1.90	2.50
R	0.20	0.60
V	0°	8°

Figure 18. **H²PAK-7 recommended footprint**



footprint_DM00249216_6

Note: Dimensions are in mm.

chanhvinh.com

3.2 Packing information

Figure 19. **Tape outline**





Figure 20. **Reel outline**



chanhvinh.com

Table 9. **Tape and reel mechanical data**

Tape			Reel		
Dim.	mm		Dim.	mm	
	Min.	Max.		Min.	Max.
A0	10.5	10.7	A		330
B0	15.7	15.9	B	1.5	
D	1.5	1.6	C	12.8	13.2
D1	1.59	1.61	D	20.2	
E	1.65	1.85	G	24.4	26.4
F	11.4	11.6	N	100	
K0	4.8	5.0	T		30.4
P0	3.9	4.1			
P1	11.9	12.1	Base quantity		1000
P2	1.9	2.1	Bulk quantity		1000
R	50				
T	0.25	0.35			
W	23.7	24.3			

chanhvinh.com

Revision history

Table 10. **Document revision history**

Date	Revision	Changes
07-Oct-2022	1	First release.
13-May-2024	2	Updated Figure 10. Typical switching energy vs supply voltage. Updated Section 3.1: H²PAK-7 package information.

chanhvinh.com

Contents

1 **Electrical ratings** 2
2 **Electrical characteristics** 3
2.1 Electrical characteristics (curves) 5
3 **Package information** 8
3.1 H²PAK-7 package information 8
3.2 Packing information 10
Revision history 12

chanhvinh.com

IMPORTANT NOTICE – READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgment.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2024 STMicroelectronics – All rights reserved