chanhvinh.com


ST2378E

8-bit dual supply 1.71 to 5.5 V level translator with I/O V_{CC} ± 15 KV ESD protection


Datasheet – production data

Features

- High speed
  - t_{PD} = 15 ns (max.) at T_A = 85 °C
  - V_L = 1.8 V
  - V_{CC} = 5.5 V
- Guaranteed data rate
  - 13 Mbps (1.8 V ≤ V_L ≤ V_{CC} ≤ 5.5 V)
- Low power dissipation
  - I_{TS-VL} = I_{TS-VCC} = 1µA (max.) at T_A = 85 °C
  - I_{QVL} = 100 µA (max.) at T_A = 85 °C
  - I_{QCC} = 10µA (max.) at T_A = 85 °C
- Output impedance
  - $|I_{OHA}|$ = 20 µA (min.) at V_L = 1.8 V; V_{CC} = 5.5 V
  - I_{OLA} = 1.0 µA (min.) at V_L = 1.8 V; V_{CC} = 5.5 V
- Bidirectional level translation
- Totem pole and open drain driving for I^2C communications
- 5 V tolerant on enable pin
- Wide operating voltage range
  - V_L (opr.) = 1.71 V to V_{CC}
  - V_{CC} (opr.) = 1.71 V to 5.5 V
- ESD performance
- HBM > 15 KV ESD protection on I/OV_{CC} lines
- Lead-free Flip-Chip and TSSOP package



Flip-Chip20



TSSOP20

Description

The ST2378E device is an 8-bit, dual supply, bidirectional level translator with ±15 kV ESD protection on I/Os at V_{CC} side. It is designed to interface data transfer between low voltage ASICs/PLDs and higher voltage systems. Externally applied voltage, V_{CC} and V_L, set logic levels at both sides with range specified as 1.71 V ≤ V_L ≤ 5.5 V and V_L ≤ V_{CC} ≤ 5.5 V. For proper operation, V_{CC} should be set higher than V_L.

Utilizing a transmission-gate-based design, this device allows bidirectional asynchronous data transfer, which means each channel is allowed to have either V_{CC} to V_L or V_L to V_{CC} data transfer direction independently and no direction pin is required. The ST2378E device operates at guaranteed data rate of 13 Mbps over the entire specified operating voltage range.

Among the other features there is included the OE pin which allows disable mode operation whereby current consumption is reduced to less than 1 µA.

This is information on a product in full production. www.st.com

chanhvinh.com

Contents

1 **Block diagram** 3

2 **Pin settings** 4

2.1 Pin connection 4

2.2 Pin description 4

3 **Electrical data** 5

3.1 Maximum ratings 5

3.2 Recommended operating conditions 5

4 **Electrical characteristics** 6

5 **Test circuit** 11

6 **Waveforms** 12

7 **Package information** 14

8 **Revision history** 19

chanhvinh.com

1 Block diagram

Figure 1. Block diagram





Figure 2. Functional diagram (1 I/O line)




chanhvinh.com

2 Pin settings

2.1 Pin connection

Figure 3. Pin connection



Flip-Chip20
(bottom view) bump side

TSSOP20 (top view)

2.2 Pin description

Table 1. Pin description

Flip-Chip20 pin N°	TSSOP20 pin N°	Symbol	Name and function
E2, D1, D2, C1, C2, B1, B2, A1	2, 18, 4, 16, 6, 14, 8, 12	I/O_{VL1} to I/O_{VL8}	Data inputs/outputs
E3, D4, D3, C4, C3, B4, B3, A4	19, 3, 17, 5, 15, 7, 13, 9	I/O_{VCC1} to I/O_{VCC8}	Data inputs/outputs
A2	11	OE	Output enable inputs
A3	10	GND	Ground (0 V)
E1	1	V_L	Positive supply voltage
E4	20	V_{CC}	Positive supply voltage

chanhvinh.com

3 Electrical data

3.1 Maximum ratings

Table 2. Absolute maximum rating

Symbol	Parameter	Value	Unit
V_L	Supply voltage	-0.3 to V_{CC}	V
V_{CC}	Supply voltage	-0.3 to +7.0	V
V_{OE}	DC control input voltage	-0.3 to +7.0	V
$V_{I/OVL}$	DC I/O_{VL} input voltage (OE = GND or V_L)	-0.3 to V_L + 0.3	V
$V_{I/OVCC}$	DC I/O_{VCC} input voltage (OE = GND or V_L)	-0.3 to V_{CC} + 0.3	V
I_{IK}	DC input diode current (OE control pin)	–20	mA
I_{IOVL}	DC output current	±25	mA
I_{IOVCC}	DC output current	±25	mA
I_{SCTOUT}	Short-circuit duration I/O_{VL}, I/O_{VCC} driven from 40 mA source	Continuous	mA
I_{CCB}	DC V_{CC} or ground current	±100	mA
P_d	Power dissipation(1)	500	mW
T_{stg}	Storage temperature	-65 to +150	°C
T_L	Lead temperature (10 sec.)	300	°C

1. 500 mW: ≅ 65 °C derated to 300 mW by 10 mW/°C: 65 °C to 85 °C.

3.2 Recommended operating conditions

Table 3. Recommended operating conditions

Symbol	Parameter		Value	Unit
V_L	Supply voltage		1.71 to V_{CC}	V
V_{CC}	Supply voltage		1.71 to 5.5	V
V_I	Input voltage (OE output enable pin, V_L power supply referred)		0 to 5.5	V
$V_{I/OVL}$	I/O_{VL} voltage		0 to V_L	V
$V_{I/OVCC}$	I/O_{VCC} voltage		0 to V_{CC}	V
T_{op}	Operating temperature		-40 to 85	°C
dt/dv	Input rise and fall time (OE control pin)(1)		0 to 10	ns/V
dt/dv	Input rise and fall time(2)	$1.71 < V_L < V_{CC} < 5$ V	0 to 10	ns/V
		$V_{CC} = V_L = 5$ V	0 to 3	ns/V

1. V_{OE} from 10% V_L to 90% V_L.
2. V_{IOVL} from 10%V_L to 90%V_L; V_{IOVCC} from 10% V_{CC} to 90% V_{CC}.

chanhvinh.com

4 Electrical characteristics

Table 4. DC specification

Symbol	Parameter	Test condition(1)			Value					Unit
					T_A = 25 °C			-40 to 85 °C		
		V_L (V)(2)	V_{CC} (V)(2)		Min.	Typ.(3)	Max.	Min.	Max.	
V_{IHL}	High level input voltage (I/O_{VL})	1.8	V_L to 5.5		V_L-0.2			V_L-0.2		V
		2.5	V_L to 5.5		0.75 V_L			0.75 V_L		
		3.3	V_L to 5.5		0.75 V_L			0.75 V_L		
		5.0	V_L to 5.5		0.75 V_L			0.75 V_L		
V_{ILL}	Low level input voltage (I/O_{VL})	1.8	V_L to 5.5				0.15		0.15	V
		2.5	V_L to 5.5				0.30		0.30	
		3.3	V_L to 5.5				0.30		0.30	
		5.0	V_L to 5.5				0.30		0.30	
V_{IHC}	High level input voltage (I/O_{VCC})	1.8	V_L to 5.5		V_L-0.2			V_L-0.2		V
		2.5	V_L to 5.5		0.75 V_{CC}			0.75 V_{CC}		
		3.3	V_L to 5.5		0.75 V_{CC}			0.75 V_{CC}		
		5.0	V_L to 5.5		0.75 V_{CC}			0.75 V_{CC}		
V_{ILC}	Low level input voltage (I/O_{VCC})	1.8	V_L to 5.5				0.15		0.15	V
		2.5	V_L to 5.5				0.30		0.30	
		3.3	V_L to 5.5				0.30		0.30	
		5.0	V_L to 5.5				0.30		0.30	
V_{IH-TS}	High level input voltage (OE)	1.8	V_L to 5.5		V_L-0.2			V_L-0.2		V
		2.5	V_L to 5.5		0.75 V_L			0.75 V_L		
		3.3	V_L to 5.5		0.75 V_L			0.75 V_L		
		5.0	V_L to 5.5		0.75 V_L			0.75 V_L		
V_{IL-TS}	Low level input voltage (OE)	1.8	V_L to 5.5				0.15		0.15	V
		2.5	V_L to 5.5				0.25 V_L		0.25 V_L	
		3.3	V_L to 5.5				0.25 V_L		0.25 V_L	
		5.0	V_L to 5.5				0.25 V_L		0.25 V_L	
V_{OHL}	High level output voltage I/O_{VL}	1.8 to 5.5	V_L to 5.5	I_O = -20 µA $I/O_{VCC} \geq V_{CC}$ -0.2	0.67 V_L			0.67 V_L		V
V_{OLL}	Low level output voltage I/O_{VL}			I_O = 1.0 mA $I/O_{VCC} \leq$ 0.15 V			0.40		0.40	

chanhvinh.com

Table 4. DC specification (continued)

Symbol	Parameter	Test condition(1)			Value					Unit
					T_A = 25 °C			-40 to 85 °C		
		V_L (V)(2)	V_{CC} (V)(2)		Min.	Typ.(3)	Max.	Min.	Max.	
V_{OHC}	High level output voltage I/O_{VCC}	1.8 to 5.5	V_L to 5.5	I_O = -20 µA $I/O_{VL} \geq V_L$ -0.2	0.67 V_{CC}			0.67 V_{CC}		V
V_{OLC}	Low level output voltage I/O_{VCC}			I_O = 1.0 mA $I/O_{VL} \leq$ 0.15 V			0.40		0.40	
I_{TSL}	Control input leakage current (OE)	1.8 to 5.5	V_L to 5.5	V_I = GND or 5.5			1		1	µA
I_{TS-LKG}	High impedance input leakage current (IO_{VL}, I/O_{VCC})	1.8 to 5.5	V_L to 5.5	OE = GND			1		1	µA
I_{QVCC}	Quiescent supply current V_{CC}	1.8 to 5.5	V_L to 5.5	I/O_{VL}, I/O_{VCC} unconnected		0.1	1		10	µA
I_{QVL}	Quiescent supply current V_L	1.8 to 5.5	V_L to 5.5	I/O_{VL}, I/O_{VCC} unconnected		13	20		100	µA
I_{TS-VL}	High impedance mode quiescent supply current V_L	1.8 to 5.5	V_L to 5.5	OE = GND I/O_{VL}= GND to V_L I/O_{VCC} = GND to V_{CC}			1		1	µA

1. For normal operation, ensure $V_L < (V_{CC} + 0.3\ V)$. During power-up, $V_L > (V_{CC} + 0.3\ V)$ will not damage the device.
2. Power supply range: V_L, V_{CC} 1.8 V ± 5%, 2.5 ± 0.2 V, 3.3 ± 0.3 V, 5.0 ± 0.5 V.
3. Typical values are referred to T_A = 25 °C.

chanhvinh.com

Table 5. AC electrical characteristics (totem pole driving)

Symbol	Parameter		Test condition[1]		Value			Unit
			C_L= 15 pF, t_r = t_f ≤6 ns[2] Driver output R_T ≤ 50 Ω		-40 to +85 °C			
			V_L (V)[3]	V_{CC} (V)[3]	Min.	Typ.[4]	Max.	
t_{RVCC}	Rise time I/O_{VCC}[5]		1.8	1.8		11	15	ns
			1.8	2.5		11	15	
			1.8	3.3		10	15	
			1.8	5.0		9	15	
			2.5	3.3		8	15	
t_{FVCC}	Fall time I/O_{VCC}[5]		1.8	1.8		6	15	ns
			1.8	2.5		7	15	
			1.8	3.3		8	15	
			1.8	5.0		10	15	
			2.5	3.3		6	15	
t_{RVL}	Rise time I/O_{VL}[5]		1.8	1.8		12	15	ns
			1.8	2.5		10	15	
			1.8	3.3		9	15	
			1.8	5.0		10	15	
			2.5	3.3		7	15	
t_{FVL}	Fall time I/O_{VL}[5]		1.8	1.8		7	15	ns
			1.8	2.5		6	15	
			1.8	3.3		6	15	
			1.8	5.0		7	15	
			2.5	3.3		4	15	
$t_{IOVL-VCC}$	Propagation delay time[6] I/O_{VL-LH} to I/O_{VCC-LH} I/O_{VL-HL} to I/O_{VCC-HL}	t_{PLH}	1.8	1.8		6	15	ns
			1.8	2.5		7	15	
			1.8	3.3		7	15	
			1.8	5.0		7	15	
			2.5	3.3		4	15	
		t_{PHL}	1.8	1.8		5	15	
			1.8	2.5		5	15	
			1.8	3.3		6	15	
			1.8	5.0		8	15	
			2.5	3.3		4	15	

chanhvinh.com

Table 5. AC electrical characteristics (totem pole driving) (continued)

Symbol	Parameter		Test condition(1)		Value			Unit
			C_L = 15 pF, $t_r = t_f \leq 6$ ns(2) Driver output $R_T \leq 50\ \Omega$		-40 to +85 °C			
			V_L (V)(3)	V_{CC} (V)(3)	Min.	Typ.(4)	Max.	
$t_{IOVCC-VL}$	Propagation delay time(6) I/O_{VCC-LH} to I/O_{VL-LH} I/O_{VCC-HL} to I/O_{VL-HL}	t_{PLH}	1.8	1.8		2	15	ns
			1.8	2.5		2	15	
			1.8	3.3		2	15	
			1.8	5.0		2	15	
			2.5	3.3		2	15	
		t_{PHL}	1.8	1.8		5	15	
			1.8	2.5		5	15	
			1.8	3.3		5	15	
			1.8	5.0		6	15	
			2.5	3.3		4	15	
t_{PZL} t_{PZH} t_{PLZ} t_{PZL}	Output enable and disable time		1.8	1.8		60	80	ns
			1.8	5.0		150	200	
t_{OSLH} t_{OSHL}	Channel to channel skew time(7),(8)		1.8	1.8		0.1	1	ns
			1.8	5.0		0.5	1	
DR	Maximum data rate		1.8 to 5.0	V_L to 5.0	13			Mbps

1. For normal operation, ensure $V_L < (V_{CC} + 0.3\ V)$. During power-up, $V_L > (V_{CC} + 0.3\ V)$ will not damage the device.
2. For $V_{CC} = V_L = 1.8$ V, $t_r = t_f \leq 4$ ns.
3. Power supply range: V_L, V_{CC} 1.8 V ± 5%, 2.5 ± 0.2 V, 3.3 ± 0.3 V, 5.0 ± 0.5 V.
4. Typical values are referred to T_A = 25 °C.
5. Rise time: 10% to 90%, fall time 90% to 10%.
6. Propagation delay time: 50% to 50%.
7. Skew is defined as the absolute value of the difference between the actual propagation delay for any two outputs of the same device switching in the same direction, either HIGH or LOW ($t_{OSLH} = |\ t_{PLHm} - t_{PLHn}|$, $t_{OSHL} = |\ t_{PHLm} - t_{PHLn}|$.
8. Each translator equally loaded; parameter guaranteed by design.

chanhvinh.com

Table 6. AC characteristic (open drain driving)

Symbol	Parameter		Test condition(1)		Value			Unit
			C_L = 15 pF, $t_r = t_f \leq 6$ ns(2) Driver output $R_T \leq 50\ \Omega$		-40 to +85 °C			
			V_L (V)(3)	V_{CC} (V)(3)	Min.	Typ.(4)	Max.	
t_{RVCC}	Rise time I/O_{VCC}(5)		1.8	1.8		210	300	ns
			1.8	5.0		59	150	
t_{FVCC}	Fall time I/O_{VCC}(5)		1.8	1.8		12	30	ns
			1.8	5.0		20	30	
t_{RVL}	Rise time I/O_{VL}(5)		1.8	1.8		210	300	ns
			1.8	5.0		96	150	
t_{FVL}	Fall time I/O_{VL}(5)		1.8	1.8		11	30	ns
			1.8	5.0		11	30	
$t_{IOVL-VCC}$	Propagation delay time(6) I/O_{VL-LH} to I/O_{VCC-LH} I/O_{VL-HL} to I/O_{VCC-HL}	t_{PLH}	1.8	1.8		210	300	ns
			1.8	5.0		100	150	
		t_{PHL}	1.8	1.8		7	20	
			1.8	5.0		14	20	
$t_{IOVCC-VL}$	Propagation delay time(6) I/O_{VCC-LH} to I/O_{VL-LH} I/O_{VCC-HL} to I/O_{VL-HL}	t_{PLH}	1.8	1.8		210	300	ns
			1.8	5.0		57	150	
		t_{PHL}	1.8	1.8		7	20	
			1.8	5.0		8	20	
t_{PZL} t_{PZH} t_{PLZ} t_{PZL}	Output enable and disable time		1.8	1.8		60	80	ns
			1.8	5.0		150	200	
t_{OSLH} t_{OSHL}	Channel to channel skew time(7),(8)		1.8	1.8		10	20	ns
			1.8	5.0		2	10	
DR	Maximum data rate		1.8 to 5.0	V_L to 5.0	800			kbps

1. For normal operation, ensure $V_L < (V_{CC} + 0.3\ V)$. During power-up, $V_L > (V_{CC} + 0.3\ V)$ will not damage the device.
2. For $V_{CC} = V_L = 1.8$ V, $t_r = t_f \leq 4$ ns.
3. Power supply range: V_L, V_{CC} 1.8 V ± 5%, 2.5 ± 0.2 V, 3.3 ± 0.3 V, 5.0 ± 0.5 V.
4. Typical values are referred to $T_A = 25$ °C.
5. Rise time:10% to 90%, fall time 90% to 10%.
6. Propagation delay time: 50% to 50%.
7. Skew is defined as the absolute value of the difference between the actual propagation delay for any two outputs of the same device switching in the same direction, either HIGH or LOW ($t_{OSLH} = |\ t_{PLHm} - t_{PLHn}|$, $t_{OSHL} = |\ t_{PHLm} - t_{PHLn}|$.
8. Each translator equally loaded; parameter guaranteed by design.

chanhvinh.com

5 Test circuit

Figure 4. Test circuit




Table 7. Test circuit switches

Test	Switch		
	Driving I/O_{VL}	Driving I/O_{VCC}	Open drain driving
t_{PLH}, t_{PHL}	Open	Open	Open
t_{PZL}, t_{PLZ}	V_{CC}	V_L	-
t_{PZH}, t_{PHZ}	GND	GND	-

Note: C_L = 15/50 pF or equivalent (includes jig and probe capacitance).
R_1 = 1 KΩ or equivalent.
$R_T = Z_{OUT}$ of pulse generator (typically 50 Ω).

Table 8. Truth table

Control pin	Bidirectional input/outputs	
OE	I/O_{VL}	I/O_{VCC}
H(1)	H(1)	H(2)
H(1)	L	L
L	Z	Z

1. High level V_L power supply referred.
2. High level V_{CC} power supply referred.

Note: X = do not care; Z = high impedance.


chanhvinh.com

6 Waveforms

Table 9. Waveform symbol value


Symbol	Driving I/O_{VL}		Driving I/O_{VCC}	
	$1.8\ V \le V_L \le V_{CC} \le 2.5\ V$	$3.3\ V \le V_L \le V_{CC} \le 5.0\ V$	$1.8\ V \le V_L \le V_{CC} \le 2.5\ V$	$3.3\ V \le V_L \le V_{CC} \le 5.0\ V$
V_{IH}	V_L	V_L	V_{CC}	V_{CC}
V_{IM}	50% V_L	50% V_L	50% V_{CC}	50% V_{CC}
V_{OM}	50% V_{CC}	50% V_{CC}	50% V_{CC}	50% V_{CC}
V_X	V_{OL} +0.15 V	V_{OL} +0.3 V	V_{OL} +0.15 V	V_{OL} +0.3 V
V_Y	V_{OH} -0.15 V	V_{OH} -0.3 V	V_{OH} -0.15 V	V_{OH} -0.3 V

Figure 5. Waveform - propagation delay (f = 1 MHz; 50% duty cycle)



chanhvinh.com

Figure 6. Waveform - output enable and disable time (f = 1 MHz; 50% duty cycle)



chanhvinh.com

7 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: *www.st.com*. ECOPACK is an ST trademark.

chanhvinh.com

Figure 7. TSSOP20 package outline




Table 10. TSSOP20 package mechanical data

Symbol	Dimensions					
	mm			inch		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A			1.2			0.047
A1	0.05		0.15	0.002	0.004	0.006
A2	0.8	1	1.05	0.031	0.039	0.041
b	0.19		0.30	0.007		0.012
c	0.09		0.20	0.004		0.0079
D	6.4	6.5	6.6	0.252	0.256	0.260
E	6.2	6.4	6.6	0.244	0.252	0.260
E1	4.3	4.4	4.48	0.169	0.173	0.176
e		0.65 BSC			0.0256 BSC	
K	0°		8°	0°		8°
L	0.45	0.60	0.75	0.018	0.024	0.030

chanhvinh.com

Figure 8. Flip-Chip20 package outline





Table 11. Flip-Chip20 package mechanical data

Symbol	Dimensions					
	mm			mils		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	0.81	0.89	1.00	31.9	35.0	39.4
A1	0.15	0.24	0.35	5.9	9.4	13.8
A2		0.65			25.6	
b	0.25	0.30	0.35	9.8	11.8	13.8
D	2.41	2.46	2.51	94.9	96.9	98.8
D1		2.00			78.7	
E	1.93	1.98	2.03	76.0	78.0	79.9
E1		1.5			59.1	
e		0.50			19.7	
SE		0.25			9.8	

chanhvinh.com

Figure 9. TSSOP20 tape and reel outline




1. Drawing not in scale.

Table 12. TSSOP20 tape and reel mechanical data

Symbol	Dimensions					
	mm			inch		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A			330			12.992
C	12.8		13.2	0.504		0.519
D	20.2			0.795		
N	60			2.362		
T			22.4			0.882
Ao	6.8		7	0.268		0.276
Bo	6.9		7.1	0.272		0.280
Ko	1.7		1.9	0.067		0.075
Po	3.9		4.1	0.153		0.161
P	11.9		12.1	0.468		0.476

chanhvinh.com

Figure 10. Flip-Chip20 tape and reel outline



1. Drawing not in scale.

Table 13. Flip-Chip20 tape and reel mechanical data

Symbol	Dimensions					
	mm			inch		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A			180			7.086
C	12.8		13.2	0.504		0.519
D	20.2			0.795		
N	60			2.362		
T			14.4			0.567
Ao	2.13	2.23	2.33	0.084	0.088	0.092
Bo	2.62	2.72	2.82	0.103	0.107	0.111
Ko	1.05	1.15	1.25	0.041	0.045	0.049
Po	3.9		4.1	0.153		0.161
P	3.9		4.1	0.153		0.161

chanhvinh.com

8 Revision history

Table 14. Document revision history

Date	Revision	Changes
10-Apr-2006	1	Initial release.
18-Sep-2012	2	Updated *Figure 2* (added resistor values). Updated notes and cross-references of the notes below *Table 4* to *Table 6*, replaced t_{FCC} by t_{FVCC} in *Table 5* and *Table 6*. Updated ECOPACK text in *Section 7.*, reformatted *Section 7* (added *Table 10* to *Table 13*, moved note below *Figure 9* and *Figure 10*). Minor corrections throughout document.

chanhvinh.com

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST’s terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST’S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY TWO AUTHORIZED ST REPRESENTATIVES, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER’S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2012 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com