
chanhvinh.com


STL160N6LF7

Datasheet

N-channel logic level 60 V, 2.5 mΩ max., 160 A, STripFET F7 Power MOSFET in a PowerFLAT 5x6 package



PowerFLAT 5x6



Features

Order codes	V_{DS}	$R_{DS(on)}$max.	I_D
STL160N6LF7	60 V	2.5 mΩ	160 A

- Among the lowest $R_{DS(on)}$ on the market
- Excellent FoM (figure of merit)
- Low C_{rss}/C_{iss} ratio for EMI immunity
- High avalanche ruggedness
- Logic level $V_{GS(th)}$

Applications

- Switching applications

Description

This N-channel Power MOSFET utilizes STripFET F7 technology with an enhanced trench gate structure that results in very low on-state resistance, while also reducing internal capacitance and gate charge for faster and more efficient switching.

Product status link
STL160N6LF7

Product summary	
Order code	STL160N6LF7
Marking	160N6LF7
Package	PowerFLAT 5x6
Packing	Tape and reel

chanhvinh.com

1 Electrical ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{DS}	Drain-source voltage	60	V
V_{GS}	Gate-source voltage	±20	V
I_D (1)	Drain current (continuous) at T_C = 25 °C(2)	160	A
	Drain current (continuous) at T_C = 100 °C(2)	110	
	Drain current (continuous) at T_C = 25 °C(3)	120	
I_{DM}(1)(2)(4)	Drain current (pulsed)	640	A
P_{TOT}	Total power dissipation at T_C = 25 °C	125	W
I_{AS}	Single pulse avalanche current (pulse width limited by maximum junction temperature)	60	A
E_{AS}	Single pulse avalanche energy (starting T_J = 25 °C, I_{AV} = 60 A, $R_{Gmin.}$ = 25 Ω)	141	mJ
T_J	Operating junction temperature range	-55 to 175	°C

1. *Specified by design, not tested in production.*
2. *This is the theoretical current value only related to the silicon.*
3. *This current value is limited by package.*
4. *Pulse width is limited by safe operating area.*

Table 2. Thermal data

Symbol	Parameter	Value	Unit
R_{thJA}(1)	Thermal resistance, junction-to-ambient (on 2s2p FR-4 board vertical in still air)	15.6	°C/W
R_{thJC}	Thermal resistance, junction-to-case	1.2	°C/W

1. *Defined according to JEDEC standards (JESD51-5, -7).*

chanhvinh.com

2 Electrical characteristics

(T_C = 25 °C unless otherwise specified).

Table 3. On /off states

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	I_D = 1 mA, V_{GS} = 0 V	60			V
I_{DSS}	Zero gate voltage drain current	V_{GS} = 0 V, V_{DS} = 60 V			1	µA
		V_{GS} = 0 V, V_{DS} = 60 V, T_C = 125 °C(1)			100	µA
I_{GSS}	Gate-body leakage current	V_{GS} = 20 V, V_{DS} = 0 V			100	nA
$V_{GS(th)}$	Gate threshold voltage	V_{DS} = V_{GS}, I_D = 250 µA	1.2		2.5	V
$R_{DS(on)}$	Static drain-source on-resistance	V_{GS} = 10 V, I_D = 60 A		2.0	2.5	mΩ
		V_{GS} = 4.5 V, I_D = 60 A		3.0	4.2	

1. *Specified by design and evaluated by characterization, not tested in production.*

Table 4. Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{iss}(1)	Input capacitance	V_{DS} = 30 V, f = 1 MHz, V_{GS} = 0 V	-	3700	-	pF
C_{oss} (1)	Output capacitance		-	1550	-	pF
C_{rss} (1)	Reverse transfer capacitance		-	70	-	pF
Q_g(1)	Total gate charge	V_{DD} = 30 V, I_D = 60 A, V_{GS} = 0 to 10 V (see Figure 18. Test circuit for gate charge behavior)	-	63	-	nC
		V_{DD} = 30 V, I_D = 60 A, V_{GS} = 0 to 4.5 V (see Figure 18. Test circuit for gate charge behavior)	-	33	-	nC
Q_{gs}(1)	Gate-source charge	V_{DD} = 30 V, I_D = 60 A, V_{GS} = 0 to 4.5 V (see Figure 18. Test circuit for gate charge behavior)	-	12	-	nC
Q_{gd}(1)	Gate-drain charge		-	14	-	nC
R_g(1)	Intrinsic gate resistance		-	2	-	Ω
$Q_{g(sync)}$(1)	Total gate charge, sync. MOSFET	I_D = 60 A, V_{GS} = 0 to 10 V	-	52	-	nC
Q_{oss}(1)	Output charge	V_{DD} = 30 V, V_{GS} = 0 V	-	64	-	nC

1. *Specified by design and evaluated by characterization, not tested in production.*

chanhvinh.com

Table 5. Switching times

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$ (1)	Turn-on delay time	V_{DD} = 30 V, I_D = 60 A, R_G = 4.7 Ω, V_{GS} = 10 V (see Figure 17. Test circuit for resistive load switching times and Figure 21. Unclamped inductive waveform)	-	14	-	ns
t_r (1)	Rise time		-	7	-	ns
$t_{d(off)}$ (1)	Turn-off delay time		-	57	-	ns
t_f (1)	Fall time		-	16	-	ns

1. *Specified by design and evaluated by characterization, not tested in production.*

Table 6. Source-drain diode

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_{SD} (1) (2)	Forward on current (continuous)		-		83	A
V_{SD}	Forward on voltage	I_{SD} = 60 A, V_{GS} = 0 V	-		1.2	V
t_{rr} (1)	Reverse recovery time	I_{SD} = 60 A, di/dt = 100 A/µs V_{DD} = 48 V (see Figure 19. Test circuit for inductive load switching and diode recovery times)	-	44		ns
Q_{rr} (1)	Reverse recovery charge		-	40		nC
I_{RRM} (1)	Reverse recovery current		-	1.8		A

1. *Specified by design and evaluated by characterization, not tested in production.*
2. *This is the theoretical current value only related to the silicon.*

chanhvinh.com

2.1 Electrical characteristics (curves)

Figure 1. Total power dissipation




Figure 2. Drain current vs case temperature




Figure 3. Safe operating area




Figure 4. Normalized transient thermal impedance




Figure 5. Typical output characteristics





Figure 6. Typical transfer characteristics



chanhvinh.com

Figure 7. Typical gate charge characteristics




Figure 8. Typical capacitance characteristics




Figure 9. Avalanche characteristics




Figure 10. Avalanche energy




Figure 11. Typical drain-source on-resistance





Figure 12. Typical on-resistance vs gate-source voltage



chanhvinh.com

Figure 13. Normalized on-resistance vs temperature




Figure 14. Normalized gate threshold voltage vs temperature




Figure 15. Typical reverse diode forward characteristics






Figure 16. Normalized $V_{(BR)DSS}$ vs temperature



chanhvinh.com


3 Test circuits

Figure 17. Test circuit for resistive load switching times




AM01468v1

Figure 18. Test circuit for gate charge behavior




AM01469v10

Figure 19. Test circuit for inductive load switching and diode recovery times




AM01470v1

Figure 20. Unclamped inductive load test circuit




AM01471v1

Figure 21. Unclamped inductive waveform



AM01472v1

Figure 22. Switching time waveform



AM01473v1


chanhvinh.com

4 Package information

To meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions, and product status are available at: www.st.com. ECOPACK is an ST trademark.

4.1 PowerFLAT 5x6 type B package information

Figure 23. PowerFLAT 5x6 type B package outline



Drawing_8472137_typeB rev5


chanhvinh.com

Table 7. **PowerFLAT 5x6 type B mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A	0.90	0.95	1.00
A1		0.02	
b	0.35	0.40	0.45
b1		0.30	
c	0.21	0.25	0.34
D	4.80		5.10
D1	4.80	4.90	5.00
D2	4.01	4.21	4.31
e	1.17	1.27	1.37
E	5.90	6.00	6.10
E1	5.70	5.75	5.80
E2	3.54	3.64	3.74
E4	0.15	0.25	0.35
E5	0.26	0.36	0.46
H	0.51	0.61	0.71
K	0.95		
L	0.51	0.61	0.71
L1	0.06	0.13	0.20
L2			0.10
P	1.00	1.10	1.20
θ	8°	10°	12°

chanhvinh.com


Figure 24. **PowerFLAT 5x6 recommended footprint (dimensions are in mm)**



Footprint_8472137_typeB rev5

4.2 PowerFLAT 5x6 packing information

Figure 25. **PowerFLAT 5x6 tape (dimensions are in mm)**



Ao	6.30 +/– 0.1
Bo	5.30 +/– 0.1
Ko	1.20 +/– 0.1
F	5.50 +/– 0.1
P1	8.00 +/– 0.1
W	12.00 +/– 0.3

(I) Measured from centreline of sprocket hole to centreline of pocket.

(II) Cumulative tolerance of 10 sprocket holes is ±0.20.

(III) Measured from centreline of sprocket hole to centreline of pocket

Base and bulk quantity 3000 pcs
All dimensions are in millimeters

8234350_Tape_rev_C

chanhvinh.com

Figure 26. **PowerFLAT 5x6 package orientation in carrier tape**





Figure 27. **PowerFLAT 5x6 reel**




All dimensions are in millimeters

8234350_Reel_rev_C

chanhvinh.com

4.3 PowerFLAT 5x6 marking information

Figure 28. **PowerFLAT 5x6 marking information**



Note: Engineering Samples: these samples can be clearly identified by a dedicated special symbol in the marking of each unit. These samples are intended to be used for electrical compatibility evaluation only; usage for any other purpose may be agreed only upon written authorization by ST. ST is not liable for any customer usage in production and/or in reliability qualification trials.

Commercial Samples: fully qualified parts from ST standard production with no usage restrictions.

chanhvinh.com

Revision history

Table 8. **Document revision history**

Date	Version	Changes
09-Nov-2018	1	First release.
20-Sep-2024	2	Updated title and *Features* in cover page. Updated *Section 1: Electrical ratings*, *Section 2: Electrical characteristics* and *Section 4.1: PowerFLAT 5x6 type B package information*. Added *Section 2.1: Electrical characteristics (curves)*. Minor text changes.
13-Dec-2024	3	Updated Table 2. Thermal data. Added Figure 3. Safe operating area, Figure 5. Typical output characteristics and Figure 6. Typical transfer characteristics.

chanhvinh.com

Contents

1 **Electrical ratings** 2
2 **Electrical characteristics** 3
2.1 Electrical characteristics (curves) 5
3 **Test circuits** 8
4 **Package information** 9
4.1 PowerFLAT 5x6 type B package information 9
4.2 PowerFLAT 5x6 packing information 11
4.3 PowerFLAT 5x6 marking information 13
Revision history 14

chanhvinh.com

IMPORTANT NOTICE – READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgment.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2024 STMicroelectronics – All rights reserved

chanhvinh.com