chanhvinh.com


life.augmented

T1605G-6I

Datasheet

16 A Triac for LED light dimmer





TO-220AB Ins.

STPOWER

Features

- Three quadrants with logic level gate
- Benefits:
  - Super low holding current I_H = 5 mA
  - Optimized thermal performance with low power dissipation
  - Optimized turn-off commutation for lighting loads

Application

- Lighting:
  - Universal light dimmers
  - LED light dimmers
- Heating
- Overvoltage crowbar protection

Description

The T1605G-6I Triac in TO-220AB insulated can be used for the on/off or phase angle control function in general purpose AC switching where high commutation capability is required.

Its super low holding current I_H enables deep dimming for LED light dimmers without flickering nor jittering.

Package environmentally friendly ECOPACK2, RoHS (2011/65/EU) and halogen free compliant.

TO-220AB insulated package is UL-94, V0 flammability resin compliance.

This component is recognized by UL. Representative samples of this component have been evaluated by UL and meet applicable UL requirements for UL 1557 standard (File Ref. 81734).

Product status link
T1605G-6I

Product summary	
Order code	T1605G-6I
Package	TO-220AB Ins.
V_{DRM}/V_{RRM}	600 V
I_{GT}	5 mA
I_H	5 mA

chanhvinh.com

1 Characteristics

Table 1. Absolute maximum ratings (limiting values)

Symbol	Parameters			Value	Unit
$I_{T(RMS)}$	RMS on-state current (full sine wave)		T_c = 85 °C	16	A
I_{TSM}	Non repetitive surge peak on-state current, (full cycle, T_j initial = 25 °C)	t_p = 16.7 ms	T_j = 25 °C	140	A
		t_p = 20 ms	T_j = 25 °C	132	
I^2t	I^2t value for fusing	t_p = 10 ms	T_j = 25 °C	116	A^2s
dI/dt	Critical rate of rise of on-state current I_G = 2 x I_{GT} , t_r ≤ 100 ns	f = 50 Hz	T_j = 25 °C	50	A/µs
V_{DRM}/V_{RRM}	Repetitive peak off-state voltage		T_j = 125 °C	600	V
V_{DSM}/V_{RSM}	Non repetitive surge peak off-state voltage	t_p = 20 ms	T_j = 25 °C	700	V
I_{GM}	Peak gate current	t_p = 20 µs	T_j = 125 °C	4	A
$P_{G(AV)}$	Average gate power dissipation		T_j = 125 °C	1	W
T_{stg}	Storage junction temperature range			-40 to +150	°C
T_j	Operating junction temperature range			-40 to +125	°C

Table 2. Electrical characteristics (T_j = 25 °C, unless otherwise specified)

Symbol	Parameters	Quadrant		Value	Unit
I_{GT}	V_D = 12 V, R_L = 33 Ω	I - II - III	Min.	0.25	mA
			Max.	5	
V_{GT}			Max.	1.3	V
V_{GD}	V_D = V_{DRM}, R_L = 3.3 kΩ, T_j = 125 °C	I - II - III	Min.	0.2	V
I_H(1)	I_T = 500 mA, gate open		Max.	5	mA
I_L	I_G = 1.2 I_{GT}	I - III	Max.	10	mA
		II		15	
dV/dt(1)	V_D = 67% V_{DRM}, gate open	T_j = 125 °C	Min.	10	V/µs
(dI/dt)c(1)	(dV/dt)c = 0.1 V/µs	T_j = 125 °C	Min.	2.5	A/ms

1. *For both polarities of A2 referenced to A1*

Table 3. Static electrical characteristics

Symbol	Test conditions	T_j		Value	Unit
V_{TM}(1)	I_{TM} = 22.5 A, t_p = 380 µs	25 °C	Max.	1.55	V
V_{TO}(1)	threshold on-state voltage	125 °C	Max.	0.83	V
R_D(1)	Dynamic resistance	125 °C	Max.	28	mΩ
I_{DRM}/I_{RRM}	V_{DRM} = V_{RRM} = 600 V	25 °C	Max.	5	µA
		125 °C		1	mA

1. *For both polarities of A2 referenced to A1*

chanhvinh.com

Table 4. Thermal resistance

Symbol	Parameters		Value	Unit
$R_{th(j-c)}$	Max. junction to case (AC)	Max.	2.1	°C/W
$R_{th(j-a)}$	Junction to ambient	Typ.	60	

chanhvinh.com

1.1 Characteristics (curves)

Figure 1. Maximum power dissipation versus on-state RMS current (full cycle)




Figure 2. RMS on-state current versus case temperature (full cycle)




Figure 3. Relative variation of thermal impedance versus pulse duration




Figure 4. On-state characteristics (maximum values)




Figure 5. Surge peak on-state current versus number of cycles





Figure 6. Non-repetitive surge peak on-state current for a sinusoidal pulse with width tp < 10 ms



chanhvinh.com

Figure 7. Relative variation of critical rate of decrease of main current versus junction temperature





Figure 8. Relative variation of gate trigger current holding current and latching current versus junction temperature (typical values)



chanhvinh.com


2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: www.st.com. ECOPACK is an ST trademark.

2.1 TO-220AB insulated package information

- Epoxy meets UL 94,V0
- Cooling method: by conduction (C)
- Recommended torque value: 0.55 N·m
- Maximum torque value: 0.70 N·m

Figure 9. TO-220AB insulated package outline



(1)Resin gate position accepted in one of the two positions or in the symmetrical opposites.

chanhvinh.com

Table 5. **TO-220AB insulated package mechanical data**

Ref.	Dimensions					
	Millimeters			Inches[1]		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	15.20		15.90	0.5984		0.6260
a1		3.75			0.1476	
a2	13.00		14.00	0.5118		0.5512
B	10.00		10.40	0.3937		0.4094
b1	0.61		0.88	0.0240		0.0346
b2	1.23		1.32	0.0484		0.0520
C	4.40		4.60	0.1732		0.1811
c1	0.49		0.70	0.0193		0.0276
c2	2.40		2.72	0.0945		0.1071
e	2.40		2.70	0.0945		0.1063
F	6.20		6.60	0.2441		0.2598
I	3.73		3.88	0.1469		0.1528
L	2.65		2.95	0.1043		0.1161
l2	1.14		1.70	0.0449		0.0669
l3	1.14		1.70	0.0449		0.0669
l4	15.80	16.40	16.80	0.6220	0.6457	0.6614
M		2.6			0.1024	

1. *Inch dimensions are for reference only.*

chanhvinh.com

3 Ordering information

Figure 10. **Ordering information scheme**




Table 6. **Ordering information**

Order code	Marking	Package	Weight	Base qty.	Delivery mode
T1605G-6I	T1605G-6I	TO-220AB-Ins.	2.3 g	50	Tube

chanhvinh.com

Revision history

Table 7. **Document revision history**

Date	Version	Changes
07-Oct-2020	1	Initial release.
28-Oct-2020	2	Updated Table 6.

chanhvinh.com

chanhvinh.com

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, please refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2020 STMicroelectronics – All rights reserved