
chanhvinh.com


life.augmented

T835H-8G

Datasheet

8 A - 800 V - 150 °C 8H Triac in D²PAK





D²PAK

STPOWER

Product status link
T835H-8G

Product summary	
$I_{T(RMS)}$	8 A
V_{DRM}/V_{RRM}	800 V
V_{DSM}/V_{RSM}	900 V
I_{GT}	35 mA
T_j max.	150 °C

Features

- 8 A medium current Triac
- 800 V symmetrical blocking voltage
- 150 °C maximum junction temperature T_j
- Three triggering quadrants
- High noise immunity - static dV/dt
- Robust dynamic turn-off commutation - (dI/dt)c
- ECOPACK2 compliant component
- Molding resin UL94-V0 flammability certified

Applications

- General purpose AC line load control
- AC induction and universal motor control
- Lighting and automation I/O control
- Water heater, room heater and coffee machine
- Home automation smart AC plug
- Inrush current limiter in AC DC rectifiers

Description

Specifically designed to operate at 800 V and 150 °C, the T835H-8G Triac housed in D²PAK provides an enhanced thermal management: this 8 A Triac is the right choice for a compact drive of AC loads and enables the heatsink size reduction.

D²PAK package is ideal for compact SMD designs on surface mount boards or insulated metal substrate boards.

Based on the ST high temperature Snubberless technology, it offers higher specified turn off commutation and noise immunity levels up to the T_j max.

The T835H-8G safely optimizes the control of the hardest universal motors, heaters and inductive loads for industrial control and home appliances.

Snubberless is a trademark of STMicroelectronics.

chanhvinh.com

1 Characteristics

Table 1. Absolute maximum ratings (limiting values)

Symbol	Parameter		Value	Unit
$I_{T(RMS)}$	RMS on-state current (full sine wave)	T_c = 139 °C	8	A
I_{TSM}	Non repetitive surge peak on-state current (full cycle, T_j initial = 25 °C)	t = 16.7 ms	84	A
		t = 20 ms	80	
I^2t	I^2t value for fusing	t_p = 10 ms	42	A^2s
dI/dt	Critical rate of rise of on-state current, I_G = 2 x I_{GT}, tr ≤ 100 ns, f = 100 Hz	T_j = 25 °C	100	A/µs
V_{DRM}/V_{RRM}	Repetitive peak off-state voltage		800	V
V_{DSM}/V_{RSM}	Non Repetitive peak off-state voltage	t_p = 10 ms, T_j = 25 °C	900	V
I_{GM}	Peak gate current	t_p = 20 µs, T_j = 150 °C	4	A
P_{GM}	Maximum gate power dissipation		5	W
$P_{G(AV)}$	Average gate power dissipation	T_j = 150 °C	1	W
T_{stg}	Storage temperature range		-40 to +150	°C
T_j	Operating junction temperature range		-40 to +150	°C

Table 2. Electrical characteristics (T_j = 25 °C, unless otherwise specified)

Symbol	Test conditions		Quadrants		Value	Unit
I_{GT}	V_D = 12 V, R_L = 30 Ω		I - II - III	Min.	5	mA
				Max.	35	mA
V_{GT}	V_D = 12 V, R_L = 30 Ω		I - II - III	Max.	1.3	V
V_{GD}	V_D = V_{DRM}, R_L = 3.3 kΩ	T_j = 150 °C	I - II - III	Min.	0.15	V
I_L	I_G = 1.2 x I_{GT}		I - III	Max.	50	mA
			II	Max.	80	mA
I_H (1)	I_T = 500 mA, gate open			Max.	35	mA
dV/dt (1)	V_D = V_R = 536 V, gate open		T_j = 150 °C	Min.	2000	V/µs
(dI/dt)c (1)	Without snubber network		T_j = 150 °C	Min.	8	A/ms

1. *For both polarities of A2 referenced to A1.*

chanhvinh.com

Table 3. Static characteristics

Symbol	Test conditions	T_j		Value	Unit
V_{TM} (1)	I_{TM} = 11 A, t_p = 380 µs	25 °C	Max.	1.50	V
V_{TO} (1)	Threshold voltage	150 °C	Max.	0.83	V
R_D (1)	Dynamic resistance	150 °C	Max.	45	mΩ
I_{DRM}/I_{RRM}	$V_D = V_R = V_{DRM} = V_{RRM}$	25 °C	Max.	1.5	µA
		150°C		3.5	mA
	$V_D = V_R$ = 400 V, peak voltage	150 °C	Max.	1.3	mA

1. *For both polarities of A2 referenced to A1.*

Table 4. Thermal resistance

Symbol	Parameter		Value	Unit
$R_{th(j-c)}$	Junction to case (AC)	Max.	1.2	°C/W
$R_{th(j-a)}$	Junction to ambient (S_{CU} (1) = 2 cm^2)	Typ.	45	°C/W

1. *Scu : copper pad surface under tab, 35 µm copper thickness on FR4 PCB.*

chanhvinh.com

1.1 Characteristics (curves)

Figure 1. Maximum power dissipation versus on-state RMS current (full cycle)




Figure 2. On-state RMS current versus case temperature (full cycle)




Figure 3. On-state RMS current versus ambient temperature (free air convection)




Figure 4. On-state characteristics (maximum values)




Figure 5. Relative variation of thermal impedance versus pulse duration





Figure 6. Recommended maximum case-to-ambient thermal resistance versus ambient temperature for different peak off-state voltages



chanhvinh.com

Figure 7. Thermal resistance junction to ambient versus copper surface under tab




Figure 8. Relative variation of leakage current versus junction temperature for different values of blocking voltage




Figure 9. Relative variation of gate trigger voltage and current versus junction temperature (typical values)




Figure 10. Relative variation of holding current and latching current versus junction temperature (typical values)




Figure 11. Surge peak on-state current versus number of cycles





Figure 12. Non repetitive surge peak on-state current for a sinusoidal pulse with width t_p < 10 ms



chanhvinh.com

Figure 13. Relative variation of static dV/dt immunity versus junction temperature





Figure 14. Relative variation of critical rate of decrease of main current versus junction temperature



chanhvinh.com


2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: www.st.com. ECOPACK is an ST trademark.

2.1 D²PAK package information

- ECOPACK2 compliant
- Lead-free package leads finishing
- Molding compound resin is halogen-free and meets UL94 flammability standard level V0

Figure 15. D²PAK package outline



(1) Resin gate is accepted in each of position shown on the drawing, or their symmetrical.

chanhvinh.com

Table 5. D²PAK package mechanical data

Ref.	Dimensions					
	Millimeters			Inches[1]		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.30		4.60	0.1693		0.1811
A1	2.49		2.69	0.0980		0.1059
A2	0.03		0.23	0.0012		0.0091
A3		0.25			0.0098	
b	0.70		0.93	0.0276		0.0366
b2	1.25		1.7	0.0492		0.0669
c	0.45		0.60	0.0177		0.0236
c2	1.21		1.36	0.0476		0.0535
D	8.95		9.35	0.3524		0.3681
D1	7.50		8.00	0.2953		0.3150
D2	1.30		1.70	0.0512		0.0669
e	2.54			0.10000		
E	10.00		10.28	0.3937		0.4047
E1	8.30		8.70	0.3268		0.3425
E2	6.85		7.25	0.2697		0.2854
G	4.88		5.28	0.1921		0.2079
H	15		15.85	0.5906		0.6240
L	1.78		2.28	0.0701		0.0898
L2	1.19		1.40	0.0468		0.0551
L3	1.40		1.75	0.0551		0.0689
R		0.40			0.0157	
V2[2]	0°		8°	0°		8°

1. *Dimensions in inches are given for reference only*
2. *Degrees*

chanhvinh.com

Figure 16. D²PAK recommended footprint (dimensions are in mm)





Figure 17. D²PAK stencil definitions (dimensions are in mm)



chanhvinh.com

3 Ordering information

Figure 18. **Ordering information scheme**




Table 6. **Ordering information**

Order code	Marking	Package	Weight	Base qty.	Delivery mode
T835H-8G-TR	T835H-8G	D^2PAK	1.6 g	1000	Tape and reel 13”
T835H-8G				50	Tube

chanhvinh.com

Revision history

Table 7. **Document revision history**

Date	Version	Changes
20-Nov-2020	1	Initial release.
11-Dec-2020	2	Updated general description. Inserted STPOWER logo.

chanhvinh.com

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, please refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2020 STMicroelectronics – All rights reserved