chanhvinh.com

TS331, TS332, TS334

Micropower low-voltage, rail-to-rail comparators

Datasheet - production data

TS331 (single)




SOT23-5/SC70-5




DFN6 1.2x1.3

TS332 (dual)



SO8




MiniSO8




DFN8 2x2

DFN8 2x2 wettable flanks

TS334 (quad)



QFN16 3x3



SO14



TSSOP14

Features

- Supply operation from 1.6 V to 5 V
- Low current consumption: 20 µA
- Rail-to-rail inputs
- Wide temperature range: -40 °C to +125 °C
- Low output saturation voltage
- Low propagation delay: 210 ns
- Open-drain output
- ESD tolerance: 2 kV HBM/200 V MM
- SMD packages
- Automotive qualified

Applications

- Mobile phones
- Notebooks and PDAs
- Battery-supplied electronics
- General-purpose portable devices
- General-purpose low voltage applications

Description

The TS331, TS332 and TS334 are single, dual and quad micropower and low-voltage comparators. They can operate with a supply voltage ranging from 1.6 V to 5 V with a typical current consumption as low as 20 µA. In addition, rail-to-rail inputs make them a perfect choice for low-voltage applications.

Their availability in tiny packages is a real advantage for overcoming space constraints.

The TS33x are specified for temperatures between -40 °C to +125 °C, making them ideal for a wide range of applications.

This is information on a product in full production. www.st.com

chanhvinh.com

Contents

1 Package pin connections 3

2 Absolute maximum ratings and operating conditions 4

3 Electrical characteristics 6

4 Package information 13

4.1 SOT23-5 package information 14

4.2 SC70-5 (SOT323-5) package information 15

4.3 DFN6 1.2x1.3 package information 16

4.4 DFN8 2x2 package information 17

4.5 DFN8 2 x 2 wettable flank package information 19

4.6 SO8 package information 21

4.7 MiniSO8 package information 22

4.8 QFN16 3x3 package information 23

4.9 SO14 package information 25

4.10 TSSOP14 package information 26


5 Ordering information 27

6 Revision history 28

chanhvinh.com

1 Package pin connections

Figure 1. Pin connections for each package (top view)



1. NC = not connected
2. The exposed pads of the DFN8 2x2 and the QFN16 3x3 can be connected to VCC- or left floating.

chanhvinh.com

2 Absolute maximum ratings and operating conditions

Table 1. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{CC}	Supply voltage(1)	5.5	V
V_{ID}	Differential input voltage	± 5.5	
V_{IN}	Input voltage range	(V_{CC}-) - 0.3 to (V_{CC}+) + 0.3	
V_{out}	Output voltage(1)	5.5	
R_{thja}	Thermal resistance junction to ambient(2) SOT23-5 SC70-5 DFN6 1.2x1.3 DFN8 2x2 SO8 MiniSO8 QFN16 3x3 SO14 TSSOP14	 250 205 40 57 125 190 39 105 100	°C/W
R_{thjc}	Thermal resistance junction to case (2) SOT23-5 SC70-5 DFN8 2x2 SO8 MiniSO8 QFN16 3x3 SO14 TSSOP14	 81 172 26 40 39 5 31 32	
T_{stg}	Storage temperature	-65 to +150	°C
T_j	Junction temperature	150	
T_{LEAD}	Lead temperature (soldering 10 seconds)	260	
ESD	Human body model (HBM)(3)	2000	V
	Machine model (MM)(4)	200	
	Charged device model (CDM)(5)	1500	
	Latchup immunity	200	mA

1. All voltage values, except differential voltage, are referenced to V_{cc}-
2. Short-circuits can cause excessive heating. These values are typical
3. According to JEDEC standard JESD22-A114F.
4. According to JEDEC standard JESD22-A115A.
5. According to ANSI/ESD STM5.3.1.

chanhvinh.com

Table 2. Operating conditions

Symbol	Parameter	Value	Unit
T_{oper}	Operating temperature range	-40 to +125	°C
V_{CC}	Supply voltage (V_{CC}+) - (V_{CC}-) -40°C < T_{amb} < +125°C	1.6 to 5.0	V
V_{ICM}	Common mode input voltage range T_{amb} = +25°C -40°C < T_{amb} < +125°C	(V_{CC}-) - 0.2 to (V_{CC}+) + 0.2 (V_{CC}-) to (V_{CC}+)	

chanhvinh.com

3 Electrical characteristics

Table 3. V_{CC}+ = +1.8 V, V_{CC}- = 0 V, T_{amb} = +25°C (unless otherwise specified)

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
V_{IO}	Input offset voltage			0.5	5	mV
		-40 °C < T_{amb} < +125 °C			6	
$\Delta V_{io}/\Delta T$	Input offset voltage drift	-40 °C < T_{amb} < +125 °C		4.5		µV/°C
I_{IB}	Input bias current(1)			25	40	nA
		-40°C < T_{amb} < +125 °C			100	
I_{IO}	Input offset current(1)			1	10	
		-40°C < T_{amb} < +125 °C			100	
I_{CC}	Supply current	No load, output low, V_{ICM} = 0 V		20	26	µA
		-40 °C < T_{amb} < +125 °C			30	
		No load, output high, V_{ICM} = 0 V		22	29	
		-40 °C < T_{amb} < +125 °C			33	
I_{OH}	Output current leakage	V_{OUT} = V_{CC}+		1	10	nA
		-40 °C < T_{amb} < +125 °C			500	
V_{OL}	Output voltage low	I_{SINK} = 1 mA		24	30	mV
		-40 °C < T_{amb} < +125 °C			50	
I_{SINK}	Output sink current	V_{OUT} = 1.5 V	20	22		mA
		-40°C < T_{amb} < +125°C	15			
CMRR	Common mode rejection ratio	0 < V_{ICM} < 1.8 V	50	68		dB
TP_{HL}	Propagation delay(2) High to low output level	V_{ICM} = 0 V, R_L = 5.1 kΩ, C_L = 50 pF, overdrive = 10 mV		300		ns
		V_{ICM} = 0 V, R_L = 5.1 kΩ, C_L = 50 pF, overdrive = 100 mV		210	310	
TP_{LH}	Propagation delay(3) Low to high output level	V_{ICM} = 0 V, R_L = 5.1 kΩ, C_L = 50 pF, overdrive = 10 mV		540		
		V_{ICM} = 0 V, R_L = 5.1 kΩ, C_L = 50 pF, overdrive = 100 mV		420	620	

1. Maximum values include unavoidable inaccuracies of the industrial tests.
2. TP_{HL} is measured when the output signal crosses a voltage level at 50% of Vcc with the following conditions: inverting input voltage (IN-) = VICM and non-inverting input voltage (IN+) moving from VICM + 100 mV to VICM - overdrive.
3. TP_{LH} is measured when the output signal crosses a voltage level at 50% of Vcc with the following conditions: inverting input voltage (IN-) = VICM and non-inverting input voltage (IN+) moving from VICM - 100 mV to VICM + overdrive.

chanhvinh.com

Table 4. V_{CC}+ = +2.7 V, V_{CC}- = 0 V, T_{amb} = +25°C (unless otherwise specified)

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
V_{IO}	Input offset voltage			0.5	5	mV
		-40 °C < T_{amb} < +125 °C			6	
$\Delta V_{io}/\Delta T$	Input offset voltage drift	-40 °C < T_{amb} < +125 °C		3.3		µV/°C
I_{IB}	Input bias current(1)			25	40	nA
		-40 °C < T_{amb} < +125 °C			100	
I_{IO}	Input offset current(1)			1	10	
		-40 °C < T_{amb} < +125 °C			100	
I_{CC}	Supply current	No load, output low, V_{ICM} = 0 V		21	27	µA
		-40 °C < T_{amb} < +125 °C			31	
		No load, output high, V_{ICM} = 0 V		23	30	
		-40°C < T_{amb} < +125 °C			34	
I_{OH}	Output current leakage	V_{OUT} = V_{CC}+		1	10	nA
		-40 °C < T_{amb} < +125 °C			500	
V_{OL}	Output voltage low	I_{SINK} = 1 mA		17	30	mV
		-40 °C < T_{amb} < +125 °C			50	
I_{SINK}	Output sink current	V_{OUT} = 1.5 V	40	47		mA
		-40 °C < T_{amb} < +125 °C	30			
CMRR	Common mode rejection ratio	0 < V_{ICM} < 2.7 V	54	74		dB
		-40 °C < T_{amb} < +125 °C	53			
TP_{HL}	Propagation delay(2) High to low output level	V_{ICM} = 0 V, R_L = 5.1 kΩ, C_L = 50 pF, overdrive = 10 mV		320		ns
		V_{ICM} = 0 V, R_L = 5.1 kΩ, C_L = 50 pF, overdrive = 100 mV		220	320	
TP_{LH}	Propagation delay(3) Low to high output level	V_{ICM} = 0 V, R_L = 5.1 kΩ, C_L = 50 pF, overdrive = 10 mV		550		
		V_{ICM} = 0 V, R_L = 5.1 kΩ, C_L = 50 pF, overdrive = 100 mV		420	640	

1. Maximum values include unavoidable inaccuracies of the industrial tests.
2. TP_{HL} is measured when the output signal crosses a voltage level at 50% of Vcc with the following conditions: Inverting input voltage (IN-) = VICM and non-inverting input voltage (IN+) moving from VICM + 100 mV to VICM - overdrive.
3. TP_{LH} is measured when the output signal crosses a voltage level at 50% of Vcc with the following conditions: Inverting input voltage (IN-) = VICM and non-inverting input voltage (IN+) moving from VICM - 100 mV to VICM + overdrive.

chanhvinh.com

Table 5. V_{CC}+ = +5 V, V_{CC}- = 0 V, T_{amb} = +25°C (unless otherwise specified)

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
V_{IO}	Input offset voltage			0.5	5	mV
		-40 °C < T_{amb} < +125 °C			6	
$\Delta V_{io}/\Delta T$	Input offset voltage drift	-40 °C < T_{amb} < +125 °C		1.3		µV/°C
I_{IB}	Input bias current(1)			30	40	nA
		-40 °C < T_{amb} < +125 °C			100	
I_{IO}	Input offset current(1)			1	10	
		-40 °C < T_{amb} < +125 °C			100	
I_{CC}	Supply current	No load, output low, V_{ICM} = 0 V		23	30	µA
		-40 °C < T_{amb} < +125 °C			34	
		No load, output high, V_{ICM} = 0 V		26	34	
		-40 °C < T_{amb} < +125 °C			38	
I_{OH}	Output current leakage	V_{OUT} = V_{CC}+		1	10	nA
		-40 °C < T_{amb} < +125 °C			600	
V_{OL}	Output voltage low	I_{SINK} = 1 mA		48	60	mV
		-40 °C < T_{amb} < +125 °C			80	
I_{SINK}	Output sink current	V_{OUT} = 1.5 V	82	93		mA
		-40 °C < T_{amb} < +125 °C	60			
A_V	Voltage gain		40	100		V/mV
CMRR	Common mode rejection ratio	0 < V_{ICM} < 5 V	60	79		dB
		-40 °C < T_{amb} < +125 °C	58			
SVR	Supply voltage rejection	ΔV_{CC} = 1.8 to 5 V	56	75		
		-40 °C < T_{amb} < +125 °C	56			
TP_{HL}	Propagation delay(2) High to low output level	V_{ICM} = 0 V, R_L = 5.1 kΩ, C_L = 50 pF, overdrive = 10 mV		380		ns
		V_{ICM} = 0 V, R_L = 5.1 kΩ, C_L = 50 pF, overdrive = 100 mV		270	430	
TP_{LH}	Propagation delay(3) Low to high output level	V_{ICM} = 0 V, R_L = 5.1 kΩ, C_L = 50 pF, overdrive = 10 mV		570		
		V_{ICM} = 0 V, R_L = 5.1 kΩ, C_L = 50 pF, overdrive = 100 mV		450	720	

1. Maximum values include unavoidable inaccuracies of the industrial tests.
2. TP_{HL} is measured when the output signal crosses a voltage level at 50% of Vcc with the following conditions: Inverting input voltage (IN-) = VICM and non-inverting input voltage (IN+) moving from VICM + 100 mV to VICM - overdrive.
3. TP_{LH} is measured when the output signal crosses a voltage level at 50% of Vcc with the following conditions: Inverting input voltage (IN-) = VICM and non-inverting input voltage (IN+) moving from VICM - 100 mV to VICM + overdrive.

chanhvinh.com

Figure 2. Supply current versus supply voltage with output high, V_{ICM} = 0 V




Figure 3. Supply current versus supply voltage with output high, V_{ICM} = V_{CC}




Figure 4. Supply current versus supply voltage with output low, V_{ICM} = 0 V




Figure 5. Supply current versus supply voltage with output low, V_{ICM} = V_{CC}




Figure 6. Supply current versus temperature





Figure 7. Input bias current versus input common-mode voltage



chanhvinh.com

Figure 8. Input current versus differential input voltage




Figure 9. Input offset voltage versus temperature




Figure 10. Output voltage versus output sink current, V_{CC} = 1.8 V




Figure 11. Output voltage versus output sink current, V_{CC} = 2.7 V




Figure 12. Output voltage versus output sink current, V_{CC} = 5 V





Figure 13. Output sink current versus output voltage



chanhvinh.com

Figure 14. Output voltage versus temperature




Figure 15. Propagation delay versus overdrive with negative transition, V_{CC} = 1.8 V




Figure 16. Propagation delay versus overdrive with positive transition, V_{CC} = 1.8 V




Figure 17. Propagation delay versus common mode voltage, V_{CC} = 1.8 V




Figure 18. Propagation delay versus overdrive with negative transition, V_{CC} = 2.7 V





Figure 19. Propagation delay versus overdrive with positive transition, V_{CC} = 2.7 V



chanhvinh.com

Figure 20. Propagation delay versus common mode voltage, V_{CC} = 2.7 V




Figure 21. Propagation delay versus overdrive with negative transition, V_{CC} = 5 V




Figure 22. Propagation delay versus overdrive with positive transition, V_{CC} = 5 V




Figure 23. Propagation delay versus common mode voltage, V_{CC} = 5 V




Figure 24. Propagation delay versus time with negative transition





Figure 25. Propagation delay versus time with positive transition



chanhvinh.com

4 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: *www.st.com*. ECOPACK is an ST trademark.

chanhvinh.com chanhvinh.com chanhvinh.com chanhvinh.com chanhvinh.com chanhvinh.com

chanhvinh.com

4.1 SOT23-5 package information

Figure 26. SOT23-5 package mechanical drawing




Table 6. SOT23-5 package mechanical data

Ref.	Dimensions					
	Millimeters			Inches[1]		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	0.90	1.20	1.45	0.035	0.047	0.057
A1			0.15			0.006
A2	0.90	1.05	1.30	0.035	0.041	0.051
B	0.35	0.40	0.50	0.013	0.015	0.019
C	0.09	0.15	0.20	0.003	0.006	0.008
D	2.80	2.90	3.00	0.110	0.114	0.118
D1		1.90			0.075	
e		0.95			0.037	
E	2.60	2.80	3.00	0.102	0.110	0.118
F	1.50	1.60	1.75	0.059	0.063	0.069
L	0.10	0.35	0.60	0.004	0.013	0.023
K	0°		10°	0°		10°

1. Values in inches are rounded to three decimal digits.

chanhvinh.com

4.2 SC70-5 (SOT323-5) package information

Figure 27. SC70-5 (SOT323-5) package mechanical drawing




Table 7. SC70-5 (or SOT323-5) package mechanical data

Ref	Dimensions					
	Millimeters			Inches[1]		
	Min	Typ	Max	Min	Typ	Max
A	0.80		1.10	0.315		0.043
A1			0.10			0.004
A2	0.80	0.90	1.00	0.315	0.035	0.039
b	0.15		0.30	0.006		0.012
c	0.10		0.22	0.004		0.009
D	1.80	2.00	2.20	0.071	0.079	0.087
E	1.80	2.10	2.40	0.071	0.083	0.094
E1	1.15	1.25	1.35	0.045	0.049	0.053
e		0.65			0.025	
e1		1.30			0.051	
L	0.26	0.36	0.46	0.010	0.014	0.018
<	0°		8°	0°		8°

1. Values in inches are rounded to three decimal digits.

chanhvinh.com

4.3 DFN6 1.2x1.3 package information

Figure 28. DFN6 1.2x1.3 package mechanical drawing




Table 8. DFN6 1.2x1.3 package mechanical data

Ref	Dimensions					
	Millimeters			Inches(1)		
	Min	Typ	Max	Min	Typ	Max
A	0.45	0.50	0.55	0.018	0.020	0.022
A1	0.00	0.02	0.05	0.000	0.001	0.002
b	0.15	0.18	0.25	0.006	0.007	0.002
c		0.05			0.002	
D		1.20			0.047	
E		1.30			0.051	
e		0.4			0.016	
L	0.475	0.525	0.575	0.019	0.021	0.023
L3	0.375	0.425	0.475	0.015	0.017	0.019

1. Values in inches are rounded to three decimal digits.

chanhvinh.com

4.4 DFN8 2x2 package information

Figure 29. DFN8 2x2 package mechanical drawing





Table 9. DFN8 2x2x0.6 mm package mechanical data (pitch 0.5 mm)

Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	0.51	0.55	0.60	0.020	0.022	0.024
A1			0.05			0.002
A3		0.15			0.006	
b	0.18	0.25	0.30	0.007	0.010	0.012
D	1.85	2.00	2.15	0.073	0.079	0.085
D2	1.45	1.60	1.70	0.057	0.063	0.067
E	1.85	2.00	2.15	0.073	0.079	0.085
E2	0.75	0.90	1.00	0.030	0.035	0.039
e		0.50			0.020	
L			0.425			0.017
ddd			0.08			0.003

chanhvinh.com


Figure 30. DFN8 2x2 footprint recommendation



chanhvinh.com

4.5 DFN8 2 x 2 wettable flank package information

Figure 31. DFN8 2 x 2 wettable flank package outline




chanhvinh.com

Table 10. DFN8 2 x 2 wettable flank package mechanical data

Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	0.70	0.75	0.80	0.028	0.030	0.031
A1	0.10			0.004		
b	0.20	0.25	0.30	0.008	0.010	0.012
D	1.95	2.00	2.05	0.077	0.079	0.081
D1	0.80	0.90	1.00	0.031	0.035	0.039
E	1.95	2.00	2.05	0.077	0.079	0.081
E1	1.50	1.60	1.70	0.059	0.063	0.067
e		0.50			0.020	
F		0.05			0.002	
G	0.25	0.30	0.35	0.010	0.012	0.014
aaa		0.10			0.004	

Figure 32. DFN8 2 x 2 wettable flank recommended footprint



chanhvinh.com

4.6 SO8 package information

Figure 33. SO8 package mechanical drawing




Table 11. SO8 package mechanical data

Ref.	Dimensions					
	Millimeters			Inches[1]		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A			1.75			0.069
A1	0.10		0.25	0.004		0.010
A2	1.25			0.049		
b	0.28		0.48	0.011		0.019
c	0.17		0.23	0.007		0.010
D	4.80	4.90	5.00	0.189	0.193	0.197
E	5.80	6.00	6.20	0.228	0.236	0.244
E1	3.80	3.90	4.00	0.150	0.154	0.157
e		1.27			0.050	
h	0.25		0.50	0.010		0.020
L	0.40		1.27	0.016		0.050
L1		1.04			0.040	
k	0		8°	1°		8°
ccc			0.10			0.004

1. Values in inches are rounded to three decimal digits.

chanhvinh.com

4.7 MiniSO8 package information

Figure 34. MiniSO8 package mechanical drawing




Table 12. MiniSO8 package mechanical data


Ref.	Dimensions					
	Millimeters			Inches[1]		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A			1.1			0.043
A1	0		0.15	0		0.006
A2	0.75	0.85	0.95	0.030	0.033	0.037
b	0.22		0.40	0.009		0.016
c	0.08		0.23	0.003		0.009
D	2.80	3.00	3.20	0.11	0.118	0.126
E	4.65	4.90	5.15	0.183	0.193	0.203
E1	2.80	3.00	3.10	0.11	0.118	0.122
e		0.65			0.026	
L	0.40	0.60	0.80	0.016	0.024	0.031
L1		0.95			0.037	
L2		0.25			0.010	
k	0°		8°	0°		8°
ccc			0.10			0.004

1. Values in inches are rounded to three decimal digits.

chanhvinh.com

4.8 QFN16 3x3 package information

Figure 35. QFN16 3 x 3 mm package mechanical drawing




chanhvinh.com

Table 13. QFN16 3 x 3 mm package mechanical data (pitch 0.5 mm)

Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	0.80	0.90	1.00	0.031	0.035	0.039
A1	0		0.05	0		0.002
A3		0.20			0.008	
b	0.18		0.30	0.007		0.012
D	2.90	3.00	3.10	0.114	0.118	0.122
D2	1.50		1.80	0.059		0.071
E	2.90	3.00	3.10	0.114	0.118	0.122
E2	1.50		1.80	0.059		0.071
e		0.50			0.020	
L	0.30		0.50	0.012		0.020

Figure 36. QFN16 3 x 3 mm footprint recommendation



chanhvinh.com

4.9 SO14 package information

Figure 37. SO14 package mechanical drawing




Table 14. SO14 package mechanical data

Dimensions						
Ref.	Millimeters			Inches[1]		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	1.35		1.75	0.050		0.068
A1	0.10		0.25	0.004		0.009
A2	1.10		1.65	0.040		0.060
B	0.33		0.51	0.010		0.020
C	0.19		0.25	0.007		0.009
D	8.55		8.75	0.330		0.340
E	3.80		4.0	0.150		0.150
e		1.27			0.05	
H	5.80		6.20	0.220		0.240
h	0.25		0.50	0.009		0.020
L	0.40		1.27	0.015		0.050
k	8° (max.)					
ddd			0.10			0.004

1. Values in inches are rounded to three decimal digits.

chanhvinh.com

4.10 TSSOP14 package information

Figure 38. TSSOP14 package mechanical drawing




Table 15. TSSOP14 package mechanical data

Ref.	Dimensions					
	Millimeters			Inches[1]		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A			1.20			0.047
A1	0.05		0.15	0.002	0.004	0.006
A2	0.80	1.00	1.05	0.031	0.039	0.041
b	0.19		0.30	0.007		0.012
c	0.09		0.20	0.004		0.0089
D	4.90	5.00	5.10	0.193	0.197	0.201
E	6.20	6.40	6.60	0.244	0.252	0.260
E1	4.30	4.40	4.50	0.169	0.173	0.176
e		0.65			0.0256	
L	0.45	0.60	0.75	0.018	0.024	0.030
L1		1.00			0.039	
k	0°		8°	0°		8°
aaa			0.10			0.004

1. Values in inches are rounded to three decimal digits.

chanhvinh.com

5 Ordering information

Table 16. Order codes

Order code	Temperature range	Package	Packaging	Marking
TS331ILT	-40 °C, +125 °C	SOT23-5	Tape and reel	K506
TS331IYLT (1)				K513
TS331ICT		SC70-5		K55
TS331IQT		DFN6 1.2x1.3		K3
TS332IQ2T		DFN8 2x2		K55
TS332IYQ3T (1)		DFN8 2x2 wettable flanks		K5D
TS332IDT		SO8		332I
TS332IYDT (1)				332IY
TS332IST		MiniSO8		K507
TS334IQ4T		QFN16 3x3		K307
TS334IDT		SO14		334I
TS334IYDT (1)				334IY
TS334IPT		TSSOP14		334I
TS334IYPT (1)				334IY

1. Qualified and characterized according to AEC Q100 and Q003 or equivalent, advanced screening according to AEC Q001 and Q 002 or equivalent.

chanhvinh.com

6 Revision history

Table 17. Document revision history

Date	Revision	Changes
29-Mar-2010	1	Initial release.
01-Dec-2011	2	– Added TS332 and TS334 devices. – Added V_{out} parameter in Table 1: Absolute maximum ratings. – Removed note "*The magnitude of input and output voltages must never exceed the supply rail ±0.3 V.*" from Table 1. – Removed note "*All values over the temperature range are guaranteed through correlation and simulation. No production tests have been performed at the temperature range limits.*" from Table 3, Table 4 and Table 5. – Removed "*Vicm = 0 V*" from *Test conditions* column in Table 3, Table 4 and Table 5. – Modified minimal Isink value in Table 5.
29-Oct-2012	3	– Added DFN6 package for TS331 – Modified notes 3, 4, and 5 in Table 1. – Added Automotive grade order codes in Table 15
30-Apr-2013	4	– Added DFN8 2x2 and QFN16 3x3 silhouette, pinout, and package information. – Figure 1: updated pinout diagrams; added footnote 2 – Table 1: updated R_{thjc} and R_{thjc} – Table 3, Table 4, Table 5: updated symbol for input offset voltage drift. – Table 15: added order codes TS332IQ2T, TS334IQ4T, and TS334IYDT.
31-Jan-2022	5	– Updated I_{SINK} value test condition in Table 5.
01-Feb-2024	6	– Added new part number TS332IYQ3T in *Table 16* and new *Section 4.5*.

chanhvinh.com

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, please refer to *www.st.com/trademarks*. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2024 STMicroelectronics – All rights reserved