
chanhvinh.com

life.augmented

X0402MB

Datasheet

4 A Sensitive gate SCR in DPAK package



DPAK

Product status link
X0402MB

Product summary	
$I_{T(RMS)}$	4 A
V_{DSM}/V_{RSM}	750 V
I_{GT}	200 µA
T_j max.	125 °C

Features

- 4 A Triac
- Sensitive SCR: I_{GT} = 200 µA
- V_{DRM} / V_{RRM} = 600 V and V_{DSM} / V_{RSM} = 750 V
- 125 °C maximum junction temperature T_j
- DPAK SMD package
- Halogen-free molding, lead-free plating
- ECOPACK2 compliant

Application

- Actuators
- Ignitors
- Inrush current limiting circuits

Description

The X04 series is 4 A SCR housed in compact SMD DPAK package. This highly sensitive device is suited to home appliances or power tools and industrial systems and drives loads up to 4 A.

chanhvinh.com

1 Characteristics

Table 1. Absolute maximum ratings (limiting values)

Symbol	Parameter		Value	Unit
$I_{T(RMS)}$	RMS on-state current (full sine wave)	T_c = 114 °C	4	A
$I_{T\ AV}$	RMS on-state average current (full sine wave)	T_c = 114 °C	2.5	A
I_{TSM}	Non repetitive surge peak on-state current (full cycle, T_j initial = 25 °C)	t = 8.3 ms	33	A
		t = 10 ms	30	
I^2t	I^2t value for fusing	t_p = 10 ms	9	A^2s
dI/dt	Critical rate of rise of on-state current, I_G = 2 x I_{GT}, tr ≤ 100 ns, f = 60 Hz	T_j = 125 °C	50	A/µs
V_{DRM}/V_{RRM}	Repetitive peak off-state voltage	T_j = 125 °C	600	V
V_{DSM}/V_{RSM}	Non Repetitive peak off-state voltage, 10 ms		750	V
I_{GM}	Maximum peak gate current	t_p = 20 µs, T_j = 125 °C	1.2	A
P_{GM}	Maximum gate power dissipation		0.5	W
T_{stg}	Storage temperature range		-40 to +125	°C
T_j	Operating junction temperature range		-40 to +125	°C
T_L	Maximum lead temperature for soldering during 10 s		260	°C

Table 2. Electrical characteristics (T_j = 25 °C, unless otherwise specified)

Symbol	Test conditions			Value	Unit
I_{GT} (1)	V_D = 12 V, R_L = 140 Ω		Max.	200	µA
V_{GT}			Max.	0.8	V
V_{GD}	V_D = V_{DRM}, R_L = 3.3 kΩ	T_j = 125 °C	Min.	0.1	V
V_{RGM}	I_{RG} = 10 µA		Max.	8	V
I_L	I_G = 1.2 x I_{GT}		Max.	6	mA
I_H (2)	I_T = 500 mA, gate open		Max.	5	mA
dV/dt (2)	V_D = 67 % V_{DRM} , R_{GK} = 1 kΩ	T_j = 110 °C	Min.	10	V/µs

1. *For both polarities of OUT pin referenced to COM pin.*
2. *For both polarities of A2 referenced to A1.*

Table 3. Static characteristics

Symbol	Test conditions	T_j		Value	Unit
V_{TM} (1)	I_{TM} = 8 A, t_p = 380 µs	25 °C	Max.	1.8	V
V_{TO} (1)	Threshold voltage	125 °C	Max.	0.85	V
R_D (1)	Dynamic resistance	125 °C	Max.	100	mΩ
I_{DRM}/I_{RRM}	V_D = V_{DRM}; V_R = V_{RRM}; R_{GK} = 1 kΩ	25 °C	Max.	5	µA
		125°C		1	mA

1. *For both polarities of A2 referenced to A1.*

chanhvinh.com

Table 4. Thermal resistance

Symbol	Parameter		Value	Unit
$R_{th(j-c)}$	Junction to case	Max.	3	°C/W
$R_{th(j-a)}$	Junction to ambient: S_{CU} = 0.5 cm²	Typ.	70	°C/W

chanhvinh.com

chanhvinh.com

1.1 Characteristics (curves)

Figure 1. Maximum average power dissipation versus on-state RMS current




Figure 2. Average and DC on-state current versus case temperature




Figure 3. On-state RMS current versus ambient temperature (full cycle)




Figure 4. Relative variation of thermal impedance versus pulse duration




Figure 5. Relative variation of gate triggering current and voltage versus junction temperature (typical values)





Figure 6. Surge peak on-state current versus number of cycles



chanhvinh.com

Figure 7. Non repetitive surge peak on-state current for a sinusoidal pulse with width t_p < 10 ms and corresponding value of I^2t




Figure 8. On-state characteristics (maximum values)




Figure 9. Relative variation of static dV/dt immunity versus gate-to-cathode resistance (typical values)




Figure 10. Relative variation of static dV/dt immunity versus gate-to-cathode capacitance (typical values)




Figure 11. Relative variation of static dV/dt immunity versus junction temperature





Figure 12. Thermal resistance junction to ambient versus copper surface under tab (typical values)



chanhvinh.com


2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: www.st.com. ECOPACK is an ST trademark.

2.1 DPAK package information

- Molding compounded resin is halogen free and meets UL94 flammability standard, level V0
- Lead-free package leads plating

Figure 13. DPAK package outline



chanhvinh.com

Table 5. **DPAK package mechanical data**


Ref.	Dimensions					
	Millimeters			Inches[1]		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	2.20	2.30	2.38	0.0866	0.0906	0.0937
A1	0.90	1.01	1.10	0.0354	0.0398	0.0433
A2	0.00		0.10	0.0000		0.0039
b	0.72		0.85	0.0283		0.335
b4	5.13	5.33	5.46	0.2020	0.2098	0.2150
c	0.47		0.60	0.0185		0.0236
c2	0.47		0.60	0.0185		0.0236
D	6.00	6.10	6.20	0.2362	0.2402	0.2441
D1	5.15	5.40	5.65	0.2028	0.2126	0.2224
E	6.50	6.60	6.70	0.2550	0.2598	0.2638
E1	4.70	4.85	5.00	0.1850	0.1909	0.1969
e	2.186	2.286	2.386	0.0860	0.0900	0.0940
H	9.80	10.10	10.40	0.3858	0.3976	0.4094
L	1.40	1.50	1.70	0.0551	0.0591	0.0669
L1		2.90 REF			0.1142 REF	
L2	0.90		1.25	0.0354		0.0492
L3		0.51 BSC			0.201 BSC	
L4	0.60	0.80	1.00	0.0236	0.0315	0.0394
L6		1.80 BSC			0.0709 BSC	
Θ1	5°	7°	9°	5°	7°	9°
Θ2	5°	7°	9°	5°	7°	9°
V2	0°		8°	0°		8°

1. *Dimensions in inches are given for reference only*

Note: This package drawing may slightly differ from the physical package. However, all the specified dimensions are guaranteed.

chanhvinh.com

Figure 14. **DPAK recommended footprint (dimensions are in mm)**



chanhvinh.com

3 Ordering information

Figure 15. **Ordering information scheme**




Table 6. **Ordering information**

Order code	Marking	Package	Weight	Base qty.	Delivery mode
X0402MB	X0402MB	DPAK	0.3 g	2500	Tape and reel

chanhvinh.com

Revision history

Table 7. **Document revision history**

Date	Revision	Changes
06-Sep-2022	1	Initial release.

chanhvinh.com

chanhvinh.com

IMPORTANT NOTICE – READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgment.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2022 STMicroelectronics – All rights reserved