chanhvinh.com

N-Channel Power MOSFET

150V, 24A, 65mΩ

FEATURES

- Low $R_{DS(ON)}$ to minimize conductive losses
- Low gate charge for fast power switching
- 100% UIS and R_g tested
- Compliant to RoHS directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21

APPLICATIONS


- PoE
- LED Lighting
- Telecom Power

KEY PERFORMANCE PARAMETERS			
PARAMETER		**VALUE**	**UNIT**
V_{DS}		150	V
$R_{DS(on)}$ (max)	V_{GS} = 10V	65	mΩ
	V_{GS} = 6V	80	
Q_g		24	nC

Pb-Free RoHS COMPLIANT HALOGEN FREE

PDFN56





Note: MSL 1 (Moisture Sensitivity Level) per J-STD-020

ABSOLUTE MAXIMUM RATINGS (T_A = 25°C unless otherwise noted)				
PARAMETER		**SYMBOL**	**LIMIT**	**UNIT**
Drain-Source Voltage		V_{DS}	150	V
Gate-Source Voltage		V_{GS}	±20	V
Continuous Drain Current	T_C = 25°C	I_D	24	A
	T_A = 25°C		4	
Pulsed Drain Current (Note 1)		I_{DM}	96	A
Single Pulse Avalanche Current (Note 2)		I_{AS}	18	A
Single Pulse Avalanche Energy (Note 2)		E_{AS}	49	mJ
Total Power Dissipation	T_C = 25°C	P_D	96	W
	T_C = 125°C		19	
Total Power Dissipation	T_A = 25°C	P_D	2.6	W
	T_A = 125°C		0.5	
Operating Junction and Storage Temperature Range		T_J, T_{STG}	- 55 to +150	°C

THERMAL PERFORMANCE			
PARAMETER	**SYMBOL**	**LIMIT**	**UNIT**
Junction to Case Thermal Resistance	$R_{\Theta JC}$	1.3	°C/W
Junction to Ambient Thermal Resistance	$R_{\Theta JA}$	48	°C/W

Thermal Performance Note: $R_{\Theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistances. The case-thermal reference is defined at the solder mounting surface of the drain pins. $R_{\Theta JA}$ is guaranteed by design while $R_{\Theta CA}$ is determined by the user's board design.

chanhvinh.com

ELECTRICAL SPECIFICATIONS (T_A = 25°C unless otherwise noted)						
PARAMETER	**CONDITIONS**	**SYMBOL**	**MIN**	**TYP**	**MAX**	**UNIT**
Static						
Drain-Source Breakdown Voltage	V_{GS} = 0V, I_D = 250μA	BV_{DSS}	150	--	--	V
Gate Threshold Voltage	V_{GS} = V_{DS}, I_D = 250μA	$V_{GS(TH)}$	2	2.7	4	V
Gate-Source Leakage Current	V_{GS} = ±20V, V_{DS} = 0V	I_{GSS}	--	--	±100	nA
Drain-Source Leakage Current	V_{GS} = 0V, V_{DS} = 150V	I_{DSS}	--	--	1	μA
	V_{GS} = 0V, V_{DS} = 150V T_J = 125°C		--	--	100	
Drain-Source On-State Resistance (Note 3)	V_{GS} = 10V, I_D = 4A	$R_{DS(on)}$	--	47	65	mΩ
	V_{GS} = 6V, I_D = 4A		--	55	80	
Forward Transconductance (Note 3)	V_{DS} = 5V, I_D = 4A	g_{fs}	--	11	--	S
Dynamic (Note 4)						
Total Gate Charge	V_{GS} = 10V, V_{DS} = 75V, I_D = 4A	Q_g	--	36	--	nC
Total Gate Charge	V_{GS} = 6V, V_{DS} = 75V, I_D = 4A	Q_g	--	24	--	
Gate-Source Charge		Q_{gs}	--	10	--	
Gate-Drain Charge		Q_{gd}	--	12	--	
Input Capacitance	V_{GS} = 0V, V_{DS} = 75V f = 1.0MHz	C_{iss}	--	1829	--	pF
Output Capacitance		C_{oss}	--	94	--	
Reverse Transfer Capacitance		C_{rss}	--	65	--	
Gate Resistance	f = 1.0MHz, open drain	R_g	0.5	1.5	3	Ω
Switching (Note 4)						
Turn-On Delay Time	V_{GS} = 10V, V_{DS} = 75V, I_D = 4A, R_G = 2Ω,	$t_{d(on)}$	--	9.4	--	ns
Turn-On Rise Time		t_r	--	6.4	--	
Turn-Off Delay Time		$t_{d(off)}$	--	19.4	--	
Turn-Off Fall Time		t_f	--	4.8	--	
Source-Drain Diode						
Forward Voltage (Note 3)	V_{GS} = 0V, I_S = 4A	V_{SD}	--	--	1	V
Reverse Recovery Time	I_S = 4A , dI/dt = 100A/μs	t_{rr}	--	51	--	ns
Reverse Recovery Charge		Q_{rr}	--	105	--	nC

Notes:

1. Current limited by package.
2. L = 0.3mH, V_{GS} = 10V, V_{DD} = 50V, R_G = 25Ω, I_{AS} = 18A, Starting T_J = 25°C
3. Pulse test: Pulse Width ≤ 300μs, duty cycle ≤ 2%.
4. Switching time is essentially independent of operating temperature.

ORDERING INFORMATION


PART NO.	PACKAGE	PACKING
TSM650N15CR RLG	PDFN56	2,500pcs / 13” Reel

chanhvinh.com


CHARACTERISTICS CURVES

(T_A = 25°C unless otherwise noted)


Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current




Gate-Source Voltage vs. Gate Charge



On-Resistance vs. Junction Temperature



On-Resistance vs. Gate-Source Voltage




chanhvinh.com


CHARACTERISTICS CURVES

(T_A = 25°C unless otherwise noted)


Capacitance vs. Drain-Source Voltage




BV_{DSS} vs. Junction Temperature




Maximum Safe Operating Area, Junction-to-Case



Source-Drain Diode Forward Current vs. Voltage




Normalized Thermal Transient Impedance, Junction-to-Case




chanhvinh.com

PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)

PDFN56



SUGGESTED PAD LAYOUT (Unit: Millimeters)



MARKING DIAGRAM



G = Halogen Free
Y = Year Code
WW = Week Code (01~52)
F = Factory Code

chanhvinh.com

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.