chanhvinh.com

Creation Date : December 28, 2021 (GMT)

DC-DC Converters

CC10-2403SF-E

RoHS

Sales Region	Worldwide
Series	CC-E
Model	CC10-E
Status	Production
Option	DIP type
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	



Electrical Characteristics	
Nominal Input Voltage[DC]	24Vdc
Input Voltage Range[DC]	18 to 36Vdc
Efficiency	84% Typ.
Rated Output Voltage[DC]	3.3Vdc
Output Voltage Range[DC]	3.15 to 3.6Vdc
Maximum Output Current	2.5A
Maximum Ripple Noise	120mV
Maximum Output Power	8.25W
Withstanding Voltage1	Input - Case: 500AC: 1min.
Withstanding Voltage2	Input - Output: 500AC: 1min.
Withstanding Voltage3	Output - Case: 500AC: 1min.

Package Type & Size	
Package / Mounting	PCB mount
Width(W)	35.56mm Nom. (1.40in Nom.)
Height(H)	8.5mm Nom. (0.33in Nom.)
Depth(D)	22.6mm Nom. (0.89in Nom.)
Weight	10g Typ.
Industry Standard Size	
Terminal Style	DIP

Other	
Operating Temp. Range	-40 to 85°C
Isolation	Isolated
Feature	
Safety Standard(Certified)	CSA60950-1 EN60950-1 UL60950-1 CSA62368-1 EN62368-1 UL62368-1

chanhvinh.com

Safety Standard(Conformed)	
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

chanhvinh.com

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

Copyright(c) TDK Corporation. All rights reserved.