chanhvinh.com

TDK·Lambda

HQA120 Series

120W MIL-COTS , 9 to 40V Input Isolated Quarter Brick

https://product.tdk.com/en/power/hqa
www.emea.lambda.tdk.com/HQA





Industrial COTS COMM

The HQA series of isolated DC-DC converters bring a high performance quarter brick in a rugged-encapsulated package for MIL-COTS applications. With its high efficiency performance, magnetic feedback loop and wide operating baseplate temperatures of -55 to 115°C (-40°C for -S suffix), it provides high useable power at elevated temperatures and altitude for demanding and harsh environments. Various MIL-STD compliance can be supported when paired with the FQA or FQB MIL-COTS input filters.

Features	Benefits
• Up to 120 W in an Industry Quarter Brick package	• High Power Density, Less Board Area Needed
• Encapsulated and Rugged design	• Operation in Harsh and Demanding Environments
• Maximum Baseplate Temperature of 115°C	• High Useable Power at Elevated Temperatures
• No Optocouplers used	• Increased Reliability in High Altitude
• Enhanced Screening Option (-M Suffix)	• Reduces End System Test Screening Requirement
• Designed to meet MIL-STD-461; MIL-STD-1275; MIL-STD-704; RTCA/DO-160 Sec 16-18 with FQA / FQB Input Filters	• Facilitates Compliance to Various MIL-STD

Model Selector

Model	Input Voltage (V)	Output Voltage (V)	Max Current (A)	Max Power (W)	Remote Sense	Baseplate	Screening
HQA2W120W050V-007-S	9 - 40	5	24	120	Yes	Flanged	-S : Standard
HQA2W120W050V-N07-M	9 - 40	5	24	120	Yes	Non-Flanged	-M : Enhanced
HQA2W120W050V-N07-S	9 - 40	5	24	120	Yes	Non-Flanged	-S : Standard
HQA2W120W120V-007-M	9 - 40	12	10	120	Yes	Flanged	-M : Enhanced
HQA2W120W120V-007-S	9 - 40	12	10	120	Yes	Flanged	-S : Standard
HQA2W120W120V-N07-M	9 - 40	12	10	120	Yes	Non-Flanged	-M : Enhanced
HQA2W120W120V-N07-S	9 - 40	12	10	120	Yes	Non-Flanged	-S : Standard
HQA2W120W150V-007-M	9 - 40	15	8	120	Yes	Flanged	-M : Enhanced
HQA2W120W150V-007-S	9 - 40	15	8	120	Yes	Flanged	-S : Standard
HQA2W120W150V-N07-S	9 - 40	15	8	120	Yes	Non-Flanged	-S : Standard
HQA2W120W240V-007-M	9 - 40	24	5	120	NA	Flanged	-M : Enhanced
HQA2W120W240V-007-S	9 - 40	24	5	120	NA	Flanged	-S : Standard
HQA2W120W240V-N07-M	9 - 40	24	5	120	NA	Non-Flanged	-M : Enhanced
HQA2W120W240V-N07-S	9 - 40	24	5	120	NA	Non-Flanged	-S : Standard
HQA2W120W280V-007-M	9 - 40	28	4.2	120	NA	Flanged	-M : Enhanced
HQA2W120W280V-007-S	9 - 40	28	4.2	120	NA	Flanged	-S : Standard
HQA2W120W280V-N07-M	9 - 40	28	4.2	120	NA	Non-Flanged	-M : Enhanced
HQA2W120W280V-N07-S	9 - 40	28	4.2	120	NA	Non-Flanged	-S : Standard
HQA24120W480V-007-M	18 - 40	48	2.5	120	NA	Flanged	-M : Enhanced
HQA24120W480V-007-S	18 - 40	48	2.5	120	NA	Flanged	-S : Standard
HQA24120W480V-N07-S	18 - 40	48	2.5	120	NA	Non-Flanged	-S : Standard

Consult factory for other valid part number suffixes not shown on the table.

HQA	2W	120W	240V	-	007	-	M

Input Voltage
2W: 9 - 40 V
24: 18 - 40 V

Output Power
120W: 120Watts

Output Voltage
280V: 28 V
050V: 5 V

Baseplate Construction:
007: Flanged Baseplate
N07: Non-Flanged Baseplate

Screening Options:
M: Enhanced Screening
S: Standard Screening
See Screening Option Table below

chanhvinh.com

Screening Options

Operation	S-Grade (Standard Screeening)	M-Grade (Enhanced Screening)
Functional Test	Room and Hot Test	Cold, Room and Hot Test
Burn-In	Yes	Extended, 96 hour
Temperature Cycling	No	10 Cycles
Hi-Pot	2250 Vdc	2250 Vdc
Visual Inspection	Yes	Yes

Related Products

Type	Type	Description
Isolated DC-DC Converter	HQA85	85W MIL-COTS, Input 9-40V, Isolated Quarter Brick
Isolated DC-DC Converter	GQA	120W Industrial, Input 9-36V, Isolated Quarter Brick
Input Filter	FQA	40V / 20A MIL-COTS Filter for MIL-STD-461
Input Filter	FQB	40V / 20A MIL-COTS Filter for MIL-STD-461; MIL-STD-1275; MIL-STD-704; DO-160G
Evaluation Board	FQX-HQA-EVK-D0	Evaluation board (no modules) that fits 2X HQA or GQA DC-DC converters and FQA/FQB filters

Specifications

Model		5	12	15	24	28	48
Input							
Input Voltage Range	Vdc	9 - 40					18 - 40
Input Transient (t < 1s)	Vdc	50					
Input Current (max)	A	18					10
Turn-ON Input Voltage	Vdc	9.5					17.0
Turn-OFF Input Voltage	Vdc	8.5					15.5
Efficiency	%	90	90	89	87	89	91.5
Safety Certifications and Markings	-	IEC/UL/CSA/EN 62368-1, 60950-1, CE Mark and UKCA Mark					
Output							
Output Voltage Tolerance	%	±4 (Rated input, Load and Temperature)					
Output Voltage Adjustment Range	Vdc	4.5 - 5.5	10.8 - 13.2	13.5 - 16.5	21.6 - 26.4	25.2 - 30.8	45.6 - 52.8
Line Regulation	%	0.05					
Load Regulation	%	0.03					
External Load Capacitance	uF	22 - 2400	0 - 1800	0 - 1500	0 - 1000	0 - 1000	0 - 1000
Ripple & Noise	mVpp	40	40	100	100	100	125
Switching Frequency	kHz	270					
Overcurrent Protection Threshold (typ)	A	37	14.5	12	6.2	5.2	4
Over Voltage protection (typ)	Vdc	6.5	15	18	32	35	54
Over Temperature Protection	-	Shutdown - Autorecovery					
Environmental							
Operating Temperature (Tc)	°C	-40 to 115 (-S : Standard Screening) -55 to 115 (-M : Enhanced Screening)					
Storage Temperature	°C	-65 to 125					
Humidity (non condensing)	%RH	10 - 95					
Cooling	-	Conduction Cooling					
Isolation Voltage	Vdc	2250 (Input to Output / Input to Baseplate / Output to Baseplate)					
Isolation Resistance	MΩ	> 10					
Shock	-	MIL-STD-202G, Method 213B, Table 213-1, Test Condition I					
Vibration	-	MIL-STD-202G, Method 201A					
Altitude	ft	70,000; MIL-STD-883F Method 1001 / MIL-STD-810G Method 500.5 Procedure I, II, III					
Qualification Methods		MIL-STD-883F; MIL-STD-202G and MIL-STD-810G					
Other							
Weight (max)	g	100 (Flanged Baseplate)					
Size (LxWxH)	mm	Flanged Baseplate: 60.6 x 55.9 x 12.7 Non-Flanged Baseplate: 60.6 x 39 x 12.7					
Size (LxWxH)	Inches	Flanged Baseplate: 2.39 x 2.2 x 0.5 Non-Flanged Baseplate: 2.39 x 1.54 x 0.5					
MTBF - Telcordia SR-332	-	> 4 MHrs; 100% Load; Ta = 40°C					
Warranty	yrs	3					

Notes:
See website for detailed product specifications.


chanhvinh.com

PIN Assignment


PIN	Function	PIN	Function
1	Vin (+)	5	Sense (-), select models*
2	On/Off	6	Trim
3	Vin (-)	7	Sense (+), select models*
4	Vo (-)	8	Vo (+)

Pin base material is tellurium copper with tin over nickel plating.
* Sense pins are available on 5, 12 and 15 V models.

HQA DC-DC Modules with FQB Active Input Filter Module




HQA DC-DC Modules with FQA Passive Input Filter Module





chanhvinh.com

Mechanical Specification: (Flanged Baseplate)

Dimensions are in mm [in]. Unless otherwise specified tolerances are:
x.x [x.xx] ± 0.5 [0.02] , x.xx [x.xxx] ± 0.25 [0.010]










chanhvinh.com

Mechanical Specification: (Non-Flanged Baseplate)

Dimensions are in mm [in]. Unless otherwise specified tolerances are:
x.x [x.xx] ± 0.5 [0.02] , x.xx [x.xxx] ± 0.25 [0.010]
To avoid damaging components, do not exceed 3.0mm [0.12"] depth for M3 screws








chanhvinh.com


Recommended Hole Pattern

(Pin Side Down – Flanged Baseplate)



Recommended Hole Pattern

(Pin Side Down – Non-Flanged Baseplate)



chanhvinh.com

TDK·Lambda

Trusted • Innovative • Reliable

TDK-Lambda France SAS
Tel: +33 1 60 12 71 65
tlf.fr-powersolutions@tdk.com
www.emea.lambda.tdk.com/fr

Italy Sales Office
Tel: +39 02 61 29 38 63
tlf.it-powersolutions@tdk.com
www.emea.lambda.tdk.com/it

Netherlands
tlf.nl-powersolutions@tdk.com
www.emea.lambda.tdk.com/nl

TDK-Lambda Germany GmbH
Tel: +49 7841 666 0
tlg.powersolutions@tdk.com
www.emea.lambda.tdk.com/de

Austria Sales Office
Tel: +43 2256 655 84
tlg.at-powersolutions@tdk.com
www.emea.lambda.tdk.com/at

Switzerland Sales Office
Tel: +41 44 850 53 53
tlg.ch-powersolutions@tdk.com
www.emea.lambda.tdk.com/ch

Nordic Sales Office
Tel: +45 8853 8086
tlg.dk-powersolutions@tdk.com
www.emea.lambda.tdk.com/dk

TDK-Lambda UK Ltd.
Tel: +44 (0) 12 71 85 66 66
tlu.powersolutions@tdk.com
www.emea.lambda.tdk.com/uk

TDK-Lambda Ltd.
Tel: +9 723 902 4333
tli.powersolutions@tdk.com
www.emea.lambda.tdk.com/il-en

TDK-Lambda Americas
Tel: +1 800-LAMBDA-4 or 1-800-526-2324
tla.powersolutions@tdk.com
www.us.lambda.tdk.com

TDK Electronics do Brasil Ltda
Tel: +55 11 3289-9599
sales.br@tdk-electronics.tdk.com
www.tdk-electronics.tdk.com/en

TDK-Lambda Corporation
Tel: +81-3-6778-1113
www.jp.lambda.tdk.com

TDK-Lambda (China) Electronics Co. Ltd.
Tel: +86 21 6485-0777
tlc.powersolutions@tdk.com
www.lambda.tdk.com.cn

TDK-Lambda Singapore Pte Ltd.
Tel: +65 6251 7211
tls.marketing@tdk.com
www.sg.lambda.tdk.com

TDK India Private Limited, Power Supply Division
Tel: +91 80 4039-0660
mathew.philip@tdk.com
www.sg.lambda.tdk.com

chanhvinh.com

For Additional Information, please visit
https://product.tdk.com/en/power/