
chanhvinh.com

Miniature Power PCB RYII & RYII Reflow Solderable

- **1 pole 8A, 1 form C (CO) or 1 form A (NO) or 1 form B (NC) contact**
- **Low component height 12.3mm**
- **5kV/8mm coil-contact**
- **Reinforced insulation (protection class II)**
- **Pinnings: 3.2mm and 5mm**
- **Reflow-solderable version**
- **Especially suitable for resistive and inductive loads on form A (NO) and form B (NC) contacts**
- **Plastic materials according to IEC 60335-1 (domestic appliances)**

Typical applications
heating control, interface technology, domestic appliances, timers, temperature control



F0142-E

Approvals

VDE Cert. No. 40009639, UL E214025
Technical data of approved types on request


Contact Data

Contact arrangement	1 form C (CO) or 1 form A (NO) or 1 form B (NC)
Rated voltage	250VAC
Max. switching voltage	400VAC
Rated current	8A
Breaking capacity max.	2000VA
Contact material	AgNi0.15, $AgSnO_2$
Frequency of operation, with/without load	6/1200min^{-1}
Operate/release time max.	9/5ms
Bounce time max., form A/form B	6/10ms


Contact ratings

Type	Contact	Load	Cycles
IEC61810			
RY531	A (NO)	8A, 250VAC, 70°C	100x10^3
RY211	A (NO)	8A, 250VAC, 75°C	100x10^3
RY211	A (NO)	8A, 250VAC, 85°C	50x10^3
RY211	B (NC)	8A, 250VAC, 70°C	50x10^3
UL61810-1 (UL508)			
RY211	A/B (NO/NC)	10A, 250VAC, general purpose, 70°C	30x10^3
RY211	A (NO)	1/2hp, 240VAC, 85°C	30x10^3
RY211	B (NC)	B300, 70°C	6x10^3
RY211	A (NO)	8A, 250VAC, 85°C	100x10^3
RY211	A (NO)	8A, 24VDC, 85°C	30x10^3
RY211	A (NO)	B300, 85°C	30x10^3
RY211	A (NO)	C300, 105°C	30x10^3
RY211	A (NO)	1/3 hp, 250VAC, 85°C	30x10^3
RY211	A (NO)	1/4 hp, 120VAC, 70°C	30x10^3
EN60730-1			
RY211	A/B (NO/NC)	6(4)A, 250VAC, 85°C	100x10^3
RY211	A (NO)	8(4)A, 250VAC, 75°C	50x10^3
RY211	A (NO)	8(4)A, 250VAC, 85°C	30x10^3
RY211	A (NO)	2(2)A, 250VAC, -40 / +105°C	100x10^3
RY211	C (CO)	2(2)A, 250VAC, -40 / +105°C	30x10^3
Mechanical endurance, DC coil		30x10^6 operations	

Max. DC load breaking capacity



Electrical endurance



Coil Data


Coil voltage range	5 to 60VDC
Operative range, IEC 61810	2

Coil versions, DC coil

Coil code	Rated voltage VDC	Operate voltage VDC	Release voltage VDC	Coil resistance Ω±10%	Rated coil power mW
005	5	3.5	0.5	112	223
006	6	4.2	0.6	162	222
009	9	6.3	0.9	320	253
012	12	8.4	1.2	627	230
024	24	16.8	2.4	2350	245
048	48	33.6	4.8	9391	245
060	60	42.0	6.0	14000	257

All figures are given for coil without pre-energization, at ambient temperature +23°C
Other coil voltages on request

Coil operating range DC



Insulation Data

Initial dielectric strength	
between open contacts	1000V$_{rms}$
between contact and coil	5000V$_{rms}$
Clearance/creepage	
between contact and coil	≥8/8mm
Material group of insulation parts	IIIa
Tracking index of relay base	PTI250
reflow-solderable version	PTI175

12-2021 Rev. 1221
www.te.com
© 2015 Tyco Electronics Corporation,
a TE Connectivity Ltd. company

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.

Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions

Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.

chanhvinh.com

Miniature Power PCB RYII & RYII Reflow Solderable (Continued)

Other Data

Material compliance: EU RoHS/ELV, China RoHS, REACH, Halogen content refer to the Product Compliance Support Center at www.te.com/customersupport/rohssupportcenter	
Ambient temperature	-40 to +70°C +85°C at 6A
Category of environmental protection IEC 61810	 RTII - flux proof RTIII - wash tight[1)]
Vibration resistance (functional), form A (NO)/form B (NC)	 20/5g
Shock resistance (functional) form A (NO)/form B (NC)	 20/5g
Shock resistance (destructive)	100g
Terminal type	PCB-THT, PCB-THR
Weight	8g
Resistance to soldering heat THT IEC 60068-2-20	 RTII : 270°C/10s RTIII : 260°C/5s
Resistance to soldering heat THR IEC 60068-2-58	 250°C, no infrared heating allowed
Packaging/unit standard version reflow version	 tube/20 pcs., box/500 pcs. reel/280 pcs. box/1120 pcs. (4 reels)


1) not available as reflow-solderable version

Accessories


For details see datasheet	Accessories Miniature PCB Relay RY

Dimensions

Pinning 3.2mm



Pinning 5mm




2) Values in brakets are valid for reflow-solderable version


PCB layout / terminal assignment

Bottom view on solder pins

1 form C (CO) contact, 3.2mm



1 form A (NO), 1 form B (NC) contact 5mm



12-2021, Rev. 1221
www.te.com
© 2015 Tyco Electronics Corporation,
a TE Connectivity Ltd. company

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.


Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions

Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.


chanhvinh.com

Miniature Power PCB RYII & RYII Reflow Solderable (Continued)


Soldering profile for reflow-solderable version



Tape dimensions



Reel dimensions



Product code structure

Typical product code	**RY**	**6**	**1**	**1**	**012**	

Type
RY Miniature Power PCB RYII & RYII reflow solderable

Version

2	pinning 3.2mm, flux proof	**6**	pinning 3.2mm, wash tight [2]
5	pinning 5mm, flux proof	**A**	pinning 5mm, wash tight [2]

Contact arrangement

1	1 form C (1 CO), pinning 3.2mm	**3**	1 form A (1 NO), pinning 5mm
		5	1 form B (1 NC), pinning 5mm

Contact material

1	AgNi 0.15	**2**	AgNi 0.15 gold plated
3	$AgSnO_2$		

Coil
Coil code: please refer to coil versions table

Version

Blank	Standard version
R	reflow-solderable

2) not available as reflow-solderable version

12-2021 Rev. 1221
www.te.com
© 2015 Tyco Electronics Corporation,
a TE Connectivity Ltd. company

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.

Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions

Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.

chanhvinh.com

Miniature Power PCB RYII & RYII Reflow Solderable (Continued)

Product code	Version	Contacts	Contact material	Coil	Part Number
RY211005	Pinning 3.2 mm	1 form C,	AgNi 0.15	5VDC	4-1393224-2
RY211006				6VDC	4-1393224-3
RY211012	flux proof	1 CO contact		12VDC	4-1393224-6
RY211024				24VDC	4-1393224-9
RY211048				48VDC	5-1393224-1
RY212005			AgNi 0.15	5VDC	5-1393224-2
RY212006			gold plated	6VDC	5-1393224-3
RY212012				12VDC	5-1393224-5
RY212024				24VDC	5-1393224-8
RY212048				48VDC	5-1393224-9
RY213005			$AgSnO_2$	5VDC	6-1393224-0
RY213006				6VDC	9-1393224-0
RY213012				12VDC	6-1393224-1
RY213024				24VDC	6-1393224-2
RY213048				48VDC	6-1393224-3
RY531005	Pinning 5 mm	1 form A,	AgNi 0.15	5VDC	7-1393224-6
RY531006	flux proof	1 NO contact		6VDC	7-1393224-7
RY531012				12VDC	7-1393224-9
RY531024				24VDC	8-1393224-2
RY531048				48VDC	8-1393224-3
RY532012			AgNi 0.15	12VDC	8-1393224-4
RY532024			gold plated	24VDC	8-1393224-5
RY533006			$AgSnO_2$	6VDC	8-1393224-6
RY533012				12VDC	8-1393224-8
RY533024				24VDC	8-1393224-9
RY533048				48VDC	9-1393224-0
RY611005	Pinning 3.2 mm	1 form C,	AgNi 0.15	5VDC	1-1393225-7
RY611006	wash tight	1 CO contact		6VDC	1-1393225-8
RY611012				12VDC	1-1393225-9
RY611024				24VDC	2-1393225-1
RY611048				48VDC	2-1393225-2
RY612005			AgNi 0.15	5VDC	2-1393225-3
RY612006			gold plated	6VDC	2-1393225-4
RY612012				12VDC	2-1393225-6
RY612024				24VDC	2-1393225-9
RY612048				48VDC	3-1393225-0
RY613005			$AgSnO_2$	5VDC	5-1419136-2
RY613012				12VDC	3-1393225-1
RY613024				24VDC	3-1393225-3
RY613048				48VDC	3-1393225-4
RY631024		1 form A,	AgNi 0.15	24VDC	4-1415400-1
RYA31005	Pinning 5 mm	1 NO contact		5VDC	1393224-7
RYA31006	wash tight			6VDC	1393224-8
RYA31012				12VDC	1393224-9
RYA31024				24VDC	1-1393224-2
RYA31048				48VDC	1-1393224-3
RYA32005			AgNi 0.15	5VDC	1-1393224-4
RYA32006			gold plated	6VDC	8-1393224-8
RYA32012				12VDC	1-1393224-6
RYA32024				24VDC	1-1393224-8
RYA33005			$AgSnO_2$	5VDC	1-1393224-9
RYA33024				24VDC	2-1393224-1

Product code	Version	Contacts	Contact material	Coil	Part number
RY211005R	pinning 3.2mm	1 form C,	AgNi 0.15	5VDC	1-1956170-2
RY211012R	flux proof	1 CO contact		12VDC	1-1956170-6
RY211024R	reflow solderable			24VDC	1956164-1
RY531005R	pinning 5.0mm	1 form A,		5VDC	1-1956171-1
RY531012R	flux proof	1 NO contact		12VDC	1-1956171-4
RY531024R	reflow solderable			24VDC	1-1956171-7

12-2021, Rev. 1221
www.te.com
© 2015 Tyco Electronics Corporation,
a TE Connectivity Ltd. company

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.

Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions

Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.