chanhvinh.com

TEGERA®





TEGERA® INFINITY 8807R

Learn more

SUPER SOFT, THIN GLOVE, CUT LEVEL D

Dexterous, thin glove with cut resistant level D, suitable for fine assembly work. 15 gg knitted with CRF® cut resistant technology. Palm dipped with super soft nitrile foam that provides excellent grip on dry surfaces. Reinforced thumb crotch for improved longevity. Breathable materials for all day comfort. Protection against contact heat up to 100°C/212°F. Wide range of sizes means a perfectly fitting glove for everyone. Skin friendly with Derma-test and Oeko-Tex certificate. Retail packed with descriptive hangtag to help customers with their in-store choice.

CHARACTERISTICS

- High level of protection
- Good fingertip sensitivity
- Good grip
- Extra comfortable
- Flexible
- Durable

FUNCTIONS

- Withstands contact heat up to 100°C
- Approved for handling foodstuffs
- Thin
- Reinforcement between index finger and thumb

CRF®

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

chanhvinh.com

TEGERA® INFINITY 8807R

PREVENTS RISK OF
Cut injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping

PRIMARY ENVIRONMENTS OF USE
Cut risk environments, dry environments, moist environments, dirty environments

PRIMARY AREAS OF USE
Fine assembly, assembly, machine operating, building and construction, carpentry, installation work, hvac installation, sheet-metal work, engineering, transport work, machine driving, warehouse work, airport work, metalwork, glass industry work, repair work, paper industry work, service work, shop work

PRIMARY INDUSTRIES OF USE
Pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, mro, automotive, transportation, utilities, building and construction, logistics, facilities, service, retail

TYPE OF WORK
Medium weight

SPECIFICATION
TYPE Cut resistant gloves, Heat protection gloves
CATEGORY Cat. II
COLLECTION Infinity
LINING MATERIAL 15 gg, CRF® Technology, Glass fibre thread, HPPE, Nylon, Spandex
LENGTH 205-265 mm
DEXTERITY 5
GRIP DESIGN Foam grip pattern
COLOUR Black, Yellow
PAIRS PER: BUNDLE/CARTON 6/72
DISPLAY TYPE Hangtag with euro slot
DIPPING Palm-dipped
DIPPING MATERIAL Nitrile foam, Waterbased PU
CUFF STYLE Knitwrist cuff
CUFF MATERIAL Textile
CUT RESISTANCE (EN ISO 13997) Cut resistance level D
CUT RESISTANCE (EN ISO 13997) TDM: 17 N
INNER MATERIAL SPECIFICATION HPPE (High performance polyethylene), Nylon, Glass fibre thread, Elastane
OUTER MATERIAL SPECIFICATION Nitrile

COMPLIANCE
CE Cat. II
UKCA Cat. II
EAC
TP TC 019:2011
Information/UIS
EN 407:2004 X1XXXX
EN 388:2016 4X43D
EN 420:2003 +A1:2009
ANSI A4 CUT
ANSI 4 ABR
OEKO-TEX® STANDARD 100 SE 14-214 RISE www.oeko-tex.com
ORIGINAL dermatest 04 EXCELLENT 2019 dermatest-guarantee.de

Contact heat rating valid for palm area only

FEATURES
Cut protection

SIZE		ARTICLE NUMBER	EAN
6	XS	8807R-6	7340118369860
7	S	8807R-7	7340118369952
8	M	8807R-8	7340118370040
9	L	8807R-9	7340118370132
10	XL	8807R-10	7340118370224
11	XXL	8807R-11	7340118370316

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.