chanhvinh.com

CUT RESISTANT GLOVES

TEGERA®





TEGERA® INFINITY 8815R

Learn more

OUR THINNEST NITRILE DIPPED CUT F

Dexterous cut resistant glove with highest cut level F, suitable for precision work. Ultra light thanks to 18 gg knitted with CRF® Omni cut resistant technology. Palm dipped with super soft nitrile foam that provides excellent grip on dry surfaces. Reinforced thumb crotch for improved longevity. Breathable materials for all day comfort. Wide range of sizes means a perfectly fitting glove for everyone. Skin friendly with Derma-test and Oeko-Tex certificate. Retail packed with descriptive hangtag to help customers with their in-store choice.

CHARACTERISTICS

- Highest level of protection
- Good fingertip sensitivity
- Good grip
- Extra comfortable
- Flexible
- Durable

FUNCTIONS

- Soft
- Approved for handling foodstuffs
- Thin
- Reinforcement between index finger and thumb

CRF® omni

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

chanhvinh.com

TEGERA® INFINITY 8815R

PREVENTS RISK OF
Cut injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping

PRIMARY ENVIRONMENTS OF USE
Cut risk environments, dry environments, moist environments, dirty environments

PRIMARY AREAS OF USE
Assembly, building and construction, carpentry, fine assembly, glass industry work, machine driving, machine operating, metalwork, paper industry work, repair work, sheet-metal work, shop work

PRIMARY INDUSTRIES OF USE
Pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, mro, automotive, transportation, utilities, building and construction, logistics, retail

TYPE OF WORK
Medium weight

SPECIFICATION
TYPE Cut resistant gloves
CATEGORY Cat. II
COLLECTION Infinity
LINING MATERIAL 18 gg, CRF® Omni Technology, HPPE, Nylon, Spandex
LENGTH 220-270 mm
DEXTERITY 5
GRIP DESIGN Foam grip pattern
COLOUR Grey, Yellow
PAIRS PER: BUNDLE/CARTON 6/72
DISPLAY TYPE Hangtag with euro slot
DIPPING Palm-dipped
DIPPING MATERIAL Nitrile foam, Waterbased PU
CUFF STYLE Knitwrist cuff
CUFF MATERIAL Textile
CUT RESISTANCE (EN ISO 13997) Cut resistance level F
CUT RESISTANCE (EN ISO 13997) TDM: 31.2 N
INNER MATERIAL SPECIFICATION HPPE (High performance polyethylene), Nylon, Tungsten fibre thread, Elastane
OUTER MATERIAL SPECIFICATION Nitrile

COMPLIANCE
CE Cat. II
UKCA Cat. II
EAC
TP TC 019:2011
Information/UIS
EN 388:2016+A1:2018 4X43F
EN ISO 21420:2020
ANSI A6 CUT
ANSI 4 ABR
OEKO-TEX® STANDARD 100 SE 14-214 RISE www.oeko-tex.com
ORIGINAL dermatest EXCELLENT 04 2019 dermatest-guarantee.de

FEATURES
Cut protection

SIZE		ARTICLE NUMBER	EAN
6	XS	8815R-6	7340118414607
7	S	8815R-7	7340118414751
8	M	8815R-8	7340118414904
9	L	8815R-9	7340118415055
10	XL	8815R-10	7340118415208
11	XXL	8815R-11	7340118415352

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.