chanhvinh.com

tesa® 60013

Product Information

tesa® 60013 – Self-Adhesive Reinforced Paper Tape

tesa® 60013 is a high adhesion paper packaging tape featuring a fiberglass reinforced paper backing with a silicone release coating and a solvent-free synthetic rubber adhesive system. tesa® The paper backing for 60013 is reinforced with a fibergalss scrim, making this product the perfect solution for those packaging applications where a secure seal is required. Moreover, tesa®

Features

- It provides very strong adhesion and tack on a wide variety of carton qualities and is therefore ideal for the sealing of heavy-weight cartons
- It has excellent adhesion and very agressive tack
- A tamper evidence effect is achieved if this tape is removed from the cardboard

Main Application

- Suitable for heavy-duty packaging applications (> 25 kg)
- Suitable for packaging applications where a security seal is required (tamper evidence effect)
- High adhesion and very aggresive tack
- High tensile strength
- Suitable for manual and automatic dispensers

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

• Backing material	paper	• Elongation at break	6 %
• Total thickness	200 µm	• Tensile strength	125 N/cm
• Type of adhesive	synthetic rubber		

Adhesion to

• steel	11.0 N/cm

Properties

• Automatic application	yes	• Hand tearability	●●
• Manual application	yes	• Printability	●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

Additional Information

tesa® 60013 is only available in havana.

For latest information on this product please visit
http://l.tesa.com/?ip=60013

chanhvinh.com

tesa® 60013

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit
http://l.tesa.com/?ip=60013