chanhvinh.com

Data sheet
NTT05

Time / Immersion & General Purpose Timeswitches

NTT05

24 Hour Slimline General Purpose Timeswitch



Features & Benefits

- 96 Quick-Set Segments for up to 48 ON/48 OFF Programmes Per 24 Hrs
- Red LED ‘Mains ON’ & Green LED ‘Output’
- ‘Traffic Light’ Slide Switch for Easy ON (green), Auto (green & red) and OFF (red) Mode Indication
- Switches ON & OFF At Preset Times
- Captive Segment Dial
- Permanent ON/OFF Control
- Voltage Free Contacts

Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface Mount
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP20
Setting Type	Segment
Program Modes	24 Hour
Switch type	Single Pole
Voltage Free Contacts	Normally Open, Normally Closed (Changeover)

chanhvinh.com

Data sheet
NTT05

Time / Immersion & General Purpose Timeswitches

Mounting Hole Centres (mm)	90
Standby Consumption	<1.43W
Number of Channels	1
Switch rating	16A Resistive , 750W Halogen/Fluorescent, 100W CFL, 100W LED
Shortest Switching Time	15 Minute
Programmable Slots	48 ON 48 OFF (96 Segments)
Permanent ON Facility	Yes (Slider Switch)
Cable Capacity (mm2)	1.5 - 2.5mm2 Flexible Cable
Cable Entry(s)	Back Entry (Knockouts), Bottom Entry

General

Weight (g)	197
Height (mm)	120
Width (mm)	74
Depth (mm)	47
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Fittings (Rawl Plugs, Screws)
EAN Number	5012483012338
Guarantee Period	3 Years

chanhvinh.com

Data sheet
NTT05

Time / Immersion & General Purpose Timeswitches

Line Diagrams

