
chanhvinh.com

TRACO POWER

AC/DC Power Supply

TPI 65A-J Series, 65 Watt

- **65 Watt open frame power supplies in a 3" x 2" package**
- **Compact and cost efficient design**
- **Peak power function up to 140%**
- **I/O reinforced isolation 3000 VAC**
- **Operating temperature range –40°C to +85°C**
- **No load input power <0.3W (acc. ErP directive)**
- **High efficiency up to 93%**
- **Internal EN 55032 class B filter**
- **Protection class II prepared**
- **3-year product warranty**



UL 62368-1 IEC 62368-1

The TPI 65A-J is a 65 Watt AC/DC open frame power supplies series with a 3000 VAC reinforced isolation system. Our TPI line specifically focuses on providing cost efficient industrial power supplies in compact designs. This series offers a peak power function which enables the unit to deliver up to 140% of the rated power for up to 10 seconds. Excellent efficiency of up to 93% allows a compact design and an operating temperature range (natural convection) of –40°C to +70°C without derating, while going up to +85°C with either load derating or forced cooling. They are designed to meet the ErP directive (< 0.3 W no load power consumption) and come with an EMC characteristics dedicated for applications in industrial/automation and test & measurement fields. High reliability is provided by use of industrial high-quality grade components and an excellent thermal management. It makes the TPI 65A-J an ideal solution for any demanding industrial devices or space critical applications.

Models

Order Code	Output Power max.	Output Voltage nom. (adjustable)	Output Current max.	Output Current peak	Efficiency typ.
TPI 65-105A-JP	50 W	5 VDC (4.0 - 5.5 VDC)	10'000 mA	13'000 mA	90 %
TPI 65-112A-JP	65 W	12 VDC (9.6 - 13.2 VDC)	5'420 mA	7'500 mA	93 %
TPI 65-115A-JP		15 VDC (12.0 - 16.5 VDC)	4'340 mA	6'000 mA	94 %
TPI 65-124A-JP		24 VDC (19.2 - 26.4 VDC)	2'710 mA	3'750 mA	94 %
TPI 65-136A-JP		36 VDC (28.8 - 39.6 VDC)	1'810 mA	2'500 mA	93 %
TPI 65-148A-JP		48 VDC (38.4 - 52.8 VDC)	1'360 mA	1'875 mA	93 %
TPI 65-153A-JP		53 VDC (42.4 - 58.3 VDC)	1'240 mA	1'698 mA	93 %

chanhvinh.com

Input Specifications

Input Voltage	- AC Range	Operational Range:	85 - 264 VAC (Full Range)
		Rated Range:	100 - 240 VAC (Full Range)
	- DC Range	Operational Range:	120 - 370 VDC (Designed for, no certification)
		Polarity:	+DC: L / –DC: N
Input Frequency		Operational Range:	47 - 440 Hz
		Certified:	50/60 Hz
Power Consumption	- No load & Vin = 230 VAC		180 mW max. (Ready to meet ErP directive)
	- No load & Vin = 115 VAC		180 mW max.
Input Current	- Full load & Vin = 230 VAC		900 mA max.
	- Full load & Vin = 115 VAC		1'600 mA max.
Input Inrush Current	- At 230 VAC		75 A max.
	- At 115 VAC		40 A max.
Input Protection			T 3.15 A / 250 VAC (Internal Fuse in L)
Recommended Input Fuse			(The need of an external fuse has to be assessed in the final application.)

Output Specifications

Output Voltage Adjustment			–20% to +10% (By trim potentiometer) Output power must not exceed rated power!
Voltage Set Accuracy			±1% max.
Regulation	- Input Variation (Vmin - Vmax)		0.2% max.
	- Load Variation (0 - 100%)		0.7% max. (5 VDC model) 0.5% max. (other output models)
Boost Power			Output Current peak: See model table Peak power time: 5 s max. Peak power duty cycle: 20% max. Average operation power: 70% of full load (detailed description see application note)
Ripple and Noise (20 MHz Bandwidth)		5 VDC model:	75 mVp-p typ. (w/ 10 µF, 25 V, MLCC)
		12 VDC model:	75 mVp-p typ. (w/ 10 µF, 25 V, MLCC)
		15 VDC model:	75 mVp-p typ. (w/ 10 µF, 25 V, MLCC)
		24 VDC model:	75 mVp-p typ. (w/ 1 µF,50 V, MLCC)
		36 VDC model:	75 mVp-p typ. (w/ 1 µF,50 V, MLCC)
		48 VDC model:	150 mVp-p typ. (w/ 0.1 µF,100 V, MLCC)
		53 VDC model:	150 mVp-p typ. (w/ 0.1 µF,100 V, MLCC)
Capacitive Load		5 VDC model:	20'000 µF max.
		12 VDC model:	4'520 µF max.
		15 VDC model:	2'900 µF max.
		24 VDC model:	1'130 µF max.
		36 VDC model:	520 µF max.
		48 VDC model:	285 µF max.
		53 VDC model:	235 µF max.
Minimum Load			Not required
Temperature Coefficient			±0.02 %/K max.
Hold-up Time	- At 230 VAC		90 ms min.
	- At 115 VAC		15 ms min.
Start-up Time	- At 230 VAC		800 ms max.
	- At 115 VAC		950 ms max.
Short Circuit Protection			Continuous, Automatic recovery
Output Current Limitation			165% typ. of Iout max.
Overvoltage Protection			125 - 140% of Vout nom.
Transient Response	- Response Deviation		3% max. (50% to 75% Load Step at 2.5 A/µs)
	- Response Time		600 µs typ. (50% to 75% Load Step at 2.5 A/µs)

All specifications valid at nominal voltage, resistive full load and +25°C after warm-up time, unless otherwise stated.

chanhvinh.com

Safety Specifications

Standards	- IT / Multimedia Equipment	EN 62368-1 IEC 62368-1 UL 62368-1
	- Certification Documents	www.tracopower.com/overview/tpi65a-j
Protection Class		Class I & II (Prepared): Reinforced Insulation
Pollution Degree		PD 2

EMC Specifications

EMI Emissions	- Conducted Emissions		EN 55011 class B (internal filter) EN 55032 class B (internal filter) FCC Part 15 class B (internal filter)
	- Radiated Emissions		EN 55011 class B (internal filter) EN 55032 class B (internal filter) FCC Part 15 class B (internal filter)
	- Harmonic Current Emissions		EN 61000-3-2, class A
	- Voltage Fluctuations & Flicker		EN 61000-3-3
EMS Immunity			EN 55024 (IT Equipment) EN 55035 (Multimedia)
	- Electrostatic Discharge	Air:	EN 61000-4-2, ±15 kV, perf. criteria A
		Contact:	EN 61000-4-2, ±6 kV, perf. criteria A
	- RF Electromagnetic Field		EN 61000-4-3, 20 V/m, perf. criteria A
	- EFT (Burst) / Surge		EN 61000-4-4, ±4 kV, perf. criteria A
		L to L:	EN 61000-4-5, ±2 kV, perf. criteria A
		L to PE:	EN 61000-4-5, ±4 kV, perf. criteria A
	- Conducted RF Disturbances		EN 61000-4-6, 20 Vrms, perf. criteria A
	- PF Magnetic Field	Continuous:	EN 61000-4-8, 100 A/m, perf. criteria A
	- Voltage Dips & Interruptions	230 VAC / 50 Hz:	EN 61000-4-11
		115 VAC / 60 Hz:	EN 61000-4-11

General Specifications

Relative Humidity			95% max. (non condensing)
Temperature Ranges	- Operating Temperature		–40°C to +85°C
	- Storage Temperature		–40°C to +85°C
Power Derating	- High Temperature		Depending on model
	- Low Input Voltage		4 %/V below 90 VAC
		See application note:	www.tracopower.com/overview/tpi65a-j
Cooling System			Natural convection (20 LFM)
Altitude During Operation			5'000 m max.
Regulator Topology			Flyback Converter
Switching Frequency			60 kHz typ. (PWM QR) (5 VDC models) 120 kHz typ. (PWM QR) (other models)
Insulation System			Reinforced Insulation
Working Voltage (rated)			273 VAC
Isolation Test Voltage	- Input to Output, 60 s		3'000 VAC
Creepage	- Input to Output		8 mm min.
Clearance	- Input to Output		8 mm min.
Isolation Resistance	- Input to Output, 500 VDC		100 MΩ min.
Leakage Current (at 264 VAC)	- Earth Leakage Current		75 µA max.
Distance Through Isolation			0.4 mm
Reliability	- Calculated MTBF		1'490'000 h (MIL-HDBK-217F, ground benign)
Environment	- Vibration		IEC 60068-2-6
	- Mechanical Shock		IEC 60068-2-27
Housing Type			Open Frame
Mounting Type			Chassis Mount

All specifications valid at nominal voltage, resistive full load and +25°C after warm-up time, unless otherwise stated.


chanhvinh.com

Connection Type	Pin Connector
Weight	117 g
Environmental Compliance - REACH Declaration	www.tracopower.com/info/reach-declaration.pdf REACH SVHC list compliant REACH Annex XVII compliant
- RoHS Declaration	www.tracopower.com/info/rohs-declaration.pdf Exemptions: 7a, 7c-I (RoHS exemptions refer to the component concentration only, not to the overall concentration in the product (O5A rule).)
- SCIP Reference Number	54f38b10-a6c9-46f7-9475-640404133b0c

Supporting Documents

Overview Link (for additional Documents)	www.tracopower.com/overview/tpi65a-j

Outline Dimensions



Dimensions in mm (inch)
Tolerances: x.x ±0.5 (x.xx ±0.02)
Tolerances: x.xx±0.25 (x.xxx ±0.01)
Screw lock torque: Max. 0.49 Nm (5 kgfcm)

Pin connectors			
Input (CON1)		**Output** (CON2)	
Pin	**Function**	**Pin**	**Function**
1	Line	**1,2***	–Vout
3	Neutral	**3,4***	+Vout

*Terminal rated for 10 A max per pin.
(at higher current connection has to be split)

Input: JST series
mates with JST crimp terminal: SVH-21T-P1.1
and terminal housing: VHR-3N

Output: JST series
mates with JST crimp terminal: SVH-21T-P1.1
and terminal housing: VHR-4N

© Copyright 2024 Traco Electronic AG