

chanhvinh.com



## Power MOSFET




N-Channel MOSFET

### FEATURES

- Dynamic dV/dt rating
- Surface-mount (IRFR020, SiHFR020)
- Available in tape and reel
- Fast switching
- Ease of paralleling
- Simple drive requirements
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

RoHS COMPLIANT
HALOGEN FREE Available

### DESCRIPTION

Third generation power MOSFETs from Vishay provide the designer with the best combination of fast switching, ruggedized device design, low on-resistance and cost-effectiveness.

The DPAK is designed for surface mounting using vapor phase, infrared, or wave soldering techniques.

| PRODUCT SUMMARY | | |
|---|---|---|
| $V_{DS}$ (V) | 60 | |
| $R_{DS(on)}$ (Ω) | $V_{GS}$ = 10 V | 0.10 |
| $Q_g$ max. (nC) | 25 | |
| $Q_{gs}$ (nC) | 5.8 | |
| $Q_{gd}$ (nC) | 11 | |
| Configuration | Single | |

| ORDERING INFORMATION | | | |
|---|---|---|---|
| **PACKAGE** | **DPAK (TO-252)** | **DPAK (TO-252)** | **IPAK (TO-251)** |
| Lead (Pb)-free and halogen-free | SiHFR020-GE3 | SiHFR020TR-GE3 | SiHFU020-GE3 |
| Lead (Pb)-free | IRFR020TRRPbF [a] | IRFR020TRPbF [a] | - |

**Note**

a. See device orientation

| ABSOLUTE MAXIMUM RATINGS ($T_C$ = 25 °C, unless otherwise noted) | | | | | |
|---|---|---|---|---|---|
| **PARAMETER** | | | **SYMBOL** | **LIMIT** | **UNIT** |
| Drain-source voltage | | | $V_{DS}$ | 60 | V |
| Gate-source voltage | | | $V_{GS}$ | ± 20 | |
| Continuous drain current | $V_{GS}$ at 10 V | $T_C$ = 25 °C | $I_D$ | 14 | A |
| | | $T_C$ = 100 °C | | 9.0 | |
| Pulsed drain current [a] | | | $I_{DM}$ | 56 | |
| Linear derating factor | | | | 0.33 | W/°C |
| Linear derating factor (PCB mount) [e] | | | | 0.020 | |
| Single pulse avalanche energy [b] | | | $E_{AS}$ | 91 | mJ |
| Maximum power dissipation | $T_C$ = 25 °C | | $P_D$ | 42 | W |
| Maximum power dissipation (PCB mount) [e] | $T_A$ = 25 °C | | | 2.5 | |
| Peak diode recovery dV/dt [c] | | | dV/dt | 5.5 | V/ns |
| Operating junction and storage temperature range | | | $T_J$, $T_{stg}$ | -55 to +150 | °C |
| Soldering recommendations (peak temperature) [d] | for 10 s | | | 260 | |

**Notes**

a. Repetitive rating; pulse width limited by maximum junction temperature (see fig. 12)
b. $V_{DD}$ = 25 V, starting $T_J$ = 25 °C, L = 541 µH, $R_g$ = 25 Ω, $I_{AS}$ = 14 A (see fig. 13)
c. $I_{SD}$ ≤ 17 A, dI/dt ≤ 110 A/µs, $V_{DD}$ ≤ $V_{DS}$, $T_J$ ≤ 150 °C
d. 1.6 mm from case
e. When mounted on 1" square PCB (FR-4 or G-10 material)



For technical questions, contact: hvm@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000


chanhvinh.com



| THERMAL RESISTANCE RATINGS | | | | | |
|---|---|---|---|---|---|
| PARAMETER | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| Maximum junction-to-ambient | $R_{thJA}$ | - | - | 110 | °C/W |
| Maximum junction-to-ambient (PCB mount) [a] | $R_{thJA}$ | - | - | 50 | |
| Maximum junction-to-case (drain) | $R_{thJC}$ | - | - | 3.0 | |

**Note**

a. When mounted on 1" square PCB (FR-4 or G-10 material)

| SPECIFICATIONS ($T_J$ = 25 °C, unless otherwise noted) | | | | | | |
|---|---|---|---|---|---|---|
| PARAMETER | SYMBOL | TEST CONDITIONS | MIN. | TYP. | MAX. | UNIT |
| **Static** | | | | | | |
| Drain-source breakdown voltage | $V_{DS}$ | $V_{GS}$ = 0 V, $I_D$ = 250 µA | 60 | - | - | V |
| $V_{DS}$ temperature coefficient | $\Delta V_{DS}/T_J$ | Reference to 25 °C, $I_D$ = 1 mA | - | 0.073 | - | V/°C |
| Gate-source threshold voltage (N) | $V_{GS(th)}$ | $V_{DS}$ = $V_{GS}$, $I_D$ = 250 µA | 2.0 | - | 4.0 | V |
| Gate-source leakage | $I_{GSS}$ | $V_{GS}$ = ± 20 V | - | - | ± 100 | nA |
| Zero gate voltage drain current | $I_{DSS}$ | $V_{DS}$ = 60 V, $V_{GS}$ = 0 V | - | - | 25 | µA |
| | | $V_{DS}$ = 48 V, $V_{GS}$ = 0 V, $T_J$ = 125 °C | - | - | 250 | |
| Drain-source on-state resistance | $R_{DS(on)}$ | $V_{GS}$ = 10 V; $I_D$ = 8.4 A [b] | - | - | 0.10 | Ω |
| Forward transconductance | $g_{fs}$ | $V_{DS}$ = 25 V, $I_D$ = 8.4 A | 6.2 | - | - | S |
| **Dynamic** | | | | | | |
| Input capacitance | $C_{iss}$ | $V_{GS}$ = 0 V, $V_{DS}$ = 25 V, f = 1.0 MHz, see fig. 5 | - | 640 | - | pF |
| Output capacitance | $C_{oss}$ | | - | 360 | - | |
| Reverse transfer capacitance | $C_{rss}$ | | - | 79 | - | |
| Total gate charge | $Q_g$ | $V_{GS}$ = 10 V; $I_D$ = 17 A, $V_{DS}$ = 48 V, see fig. 6 and 13 [b] | - | - | 25 | nC |
| Gate-source charge | $Q_{gs}$ | | - | - | 5.8 | |
| Gate-drain charge | $Q_{gd}$ | | - | - | 11 | |
| Turn-on delay time | $t_{d(on)}$ | $V_{DD}$ = 30 V, $I_D$ = 17 A, $R_G$ = 18 Ω, $R_D$ = 1.7 Ω, see fig. 10 [b] | - | 13 | - | ns |
| Rise time | $t_r$ | | - | 58 | - | |
| Turn-off delay time | $t_{d(off)}$ | | - | 25 | - | |
| Fall time | $t_f$ | | - | 42 | - | |
| Internal drain inductance | $L_D$ | Between lead, 6 mm (0.25") from package and center of die contact [c]  | - | 4.5 | - | nH |
| Internal source inductance | $L_S$ | | - | 7.5 | - | |
| **Drain-Source Body Diode Characteristics** | | | | | | |
| Continuous source-drain diode current | $I_S$ | MOSFET symbol showing the integral reverse p - n junction diode  | - | - | 14 | A |
| Pulsed diode forward current [a] | $I_{SM}$ | | - | - | 56 | |
| Body diode voltage | $V_{SD}$ | $T_J$ = 25 °C, $I_S$ = 14 A, $V_{GS}$ = 0 V [b] | - | - | 1.5 | V |
| Body diode reverse recovery time | $t_{rr}$ | $T_J$ = 25 °C, $I_F$ = 17 A, dI/dt = 100 A/µs [b] | - | 88 | 180 | ns |
| Body diode reverse recovery charge | $Q_{rr}$ | | - | 0.29 | 0.64 | µC |
| Forward turn-on time | $t_{on}$ | Intrinsic turn-on time is negligible (turn-on is dominated by $L_S$ and $L_D$) | | | | |

**Notes**

a. Repetitive rating; pulse width limited by maximum junction temperature (see fig. 12)

b. Pulse width ≤ 300 µs; duty cycle ≤ 2 %



For technical questions, contact: hvm@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

chanhvinh.com



**TYPICAL CHARACTERISTICS** (25 °C, unless otherwise noted)





Fig. 1 - Typical Output Characteristics, $T_C$ = 25 °C





Fig. 3 - Typical Transfer Characteristics





Fig. 2 - Typical Output Characteristics, $T_C$ = 150 °C





Fig. 4 - Normalized On-Resistance vs. Temperature


For technical questions, contact: hvm@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

chanhvinh.com







Fig. 5 - Typical Capacitance vs. Drain-to-Source Voltage





Fig. 7 - Typical Source-Drain Diode Forward Voltage





Fig. 6 - Typical Gate Charge vs. Gate-to-Source Voltage





Fig. 8 - Maximum Safe Operating Area


For technical questions, contact: hvm@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

chanhvinh.com







**Fig. 9 - Maximum Drain Current vs. Case Temperature**





**Fig. 10 - Switching Time Test Circuit**





**Fig. 11 - Switching Time Waveforms**





**Fig. 12 - Maximum Effective Transient Thermal Impedance, Junction-to-Case**


For technical questions, contact: hvm@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

chanhvinh.com







Fig. 13 - Unclamped Inductive Test Circuit





Fig. 14 - Unclamped Inductive Waveforms





Fig. 15 - Maximum Avalanche Energy vs. Drain Current





Fig. 16 - Basic Gate Charge Waveform






Fig. 17 - Gate Charge Test Circuit



For technical questions, contact: hvm@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

chanhvinh.com



**Peak Diode Recovery dV/dt Test Circuit**




**Note**

a. $V_{GS}$ = 5 V for logic level devices

**Fig. 18 - For N-Channel**

*Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/ppg?90335.*




For technical questions, contact: hvm@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

chanhvinh.com



# TO-252AA Case Outline

## VERSION 1: FACILITY CODE = Y




| | MILLIMETERS | |
|---|---|---|
| DIM. | MIN. | MAX. |
| A | 2.18 | 2.38 |
| A1 | - | 0.127 |
| b | 0.64 | 0.88 |
| b2 | 0.76 | 1.14 |
| b3 | 4.95 | 5.46 |
| C | 0.46 | 0.61 |
| C2 | 0.46 | 0.89 |
| D | 5.97 | 6.22 |
| D1 | 4.10 | - |
| E | 6.35 | 6.73 |
| E1 | 4.32 | - |
| H | 9.40 | 10.41 |
| e | 2.28 BSC | |
| e1 | 4.56 BSC | |
| L | 1.40 | 1.78 |
| L3 | 0.89 | 1.27 |
| L4 | - | 1.02 |
| L5 | 1.01 | 1.52 |

**Note**

- Dimension L3 is for reference only




For technical questions, contact: pmostechsupport@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

chanhvinh.com



## VERSION 2: FACILITY CODE = N




| | MILLIMETERS | |
|---|---|---|
| DIM. | MIN. | MAX. |
| A | 2.18 | 2.39 |
| A1 | - | 0.13 |
| b | 0.65 | 0.89 |
| b1 | 0.64 | 0.79 |
| b2 | 0.76 | 1.13 |
| b3 | 4.95 | 5.46 |
| c | 0.46 | 0.61 |
| c1 | 0.41 | 0.56 |
| c2 | 0.46 | 0.60 |
| D | 5.97 | 6.22 |
| D1 | 5.21 | - |
| E | 6.35 | 6.73 |
| E1 | 4.32 | - |
| e | 2.29 BSC | |
| H | 9.94 | 10.34 |

| | MILLIMETERS | |
|---|---|---|
| DIM. | MIN. | MAX. |
| L | 1.50 | 1.78 |
| L1 | 2.74 ref. | |
| L2 | 0.51 BSC | |
| L3 | 0.89 | 1.27 |
| L4 | - | 1.02 |
| L5 | 1.14 | 1.49 |
| L6 | 0.65 | 0.85 |
| θ | 0° | 10° |
| θ1 | 0° | 15° |
| θ2 | 25° | 35° |

**Notes**

- Dimensioning and tolerance confirm to ASME Y14.5M-1994
- All dimensions are in millimeters. Angles are in degrees
- Heat sink side flash is max. 0.8 mm
- Radius on terminal is optional

ECN: E19-0649-Rev. Q, 16-Dec-2019
DWG: 5347



For technical questions, contact: pmostechsupport@vishay.com


THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

chanhvinh.com



# Case Outline for TO-251AA (High Voltage)

**OPTION 1:**




| | MILLIMETERS | | INCHES | |
|---|---|---|---|---|
| DIM. | MIN. | MAX. | MIN. | MAX. |
| A | 2.18 | 2.39 | 0.086 | 0.094 |
| A1 | 0.89 | 1.14 | 0.035 | 0.045 |
| b | 0.64 | 0.89 | 0.025 | 0.035 |
| b1 | 0.65 | 0.79 | 0.026 | 0.031 |
| b2 | 0.76 | 1.14 | 0.030 | 0.045 |
| b3 | 0.76 | 1.04 | 0.030 | 0.041 |
| b4 | 4.95 | 5.46 | 0.195 | 0.215 |
| c | 0.46 | 0.61 | 0.018 | 0.024 |
| c1 | 0.41 | 0.56 | 0.016 | 0.022 |
| c2 | 0.46 | 0.86 | 0.018 | 0.034 |
| D | 5.97 | 6.22 | 0.235 | 0.245 |

| | MILLIMETERS | | INCHES | |
|---|---|---|---|---|
| DIM. | MIN. | MAX. | MIN. | MAX. |
| D1 | 5.21 | - | 0.205 | - |
| E | 6.35 | 6.73 | 0.250 | 0.265 |
| E1 | 4.32 | - | 0.170 | - |
| e | 2.29 BSC | | 2.29 BSC | |
| L | 8.89 | 9.65 | 0.350 | 0.380 |
| L1 | 1.91 | 2.29 | 0.075 | 0.090 |
| L2 | 0.89 | 1.27 | 0.035 | 0.050 |
| L3 | 1.14 | 1.52 | 0.045 | 0.060 |
| θ1 | 0° | 15° | 0° | 15° |
| θ2 | 25° | 35° | 25° | 35° |

ECN: E21-0682-Rev. C, 27-Dec-2021
DWG: 5968

**Notes**

- Dimensioning and tolerancing per ASME Y14.5M-1994
- Dimension are shown in inches and millimeters
- Dimension D and E do not include mold flash. Mold flash shall not exceed 0.13 mm (0.005") per side. These dimensions are measured at the outermost extremes of the plastic body
- Thermal pad contour optional with dimensions b4, L2, E1 and D1
- Lead dimension uncontrolled in L3
- Dimension b1, b3 and c1 apply to base metal only
- Outline conforms to JEDEC® outline TO-251AA




For technical questions, contact: hvmos.techsupport@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

chanhvinh.com



## OPTION 2: FACILITY CODE = N




| DIM. | MIN. | NOM. | MAX. |
|---|---|---|---|
| A | 2.180 | 2.285 | 2.390 |
| A1 | 0.890 | 1.015 | 1.140 |
| b | 0.640 | 0.765 | 0.890 |
| b1 | 0.640 | 0.715 | 0.790 |
| b2 | 0.760 | 0.950 | 1.140 |
| b3 | 0.760 | 0.900 | 1.040 |
| b4 | 4.950 | 5.205 | 5.460 |
| c | 0.460 | - | 0.610 |
| c1 | 0.410 | - | 0.560 |
| c2 | 0.460 | - | 0.610 |
| D | 5.970 | 6.095 | 6.220 |
| D1 | 4.300 | - | - |

| DIM. | MIN. | NOM. | MAX. |
|---|---|---|---|
| D2 | 5.380 | - | - |
| E | 6.350 | 6.540 | 6.730 |
| E1 | 4.32 | - | - |
| e | 2.29 BSC | | |
| L | 8.890 | 9.270 | 9.650 |
| L1 | 1.910 | 2.100 | 2.290 |
| L2 | 0.890 | 1.080 | 1.270 |
| L3 | 1.140 | 1.330 | 1.520 |
| L4 | 1.300 | 1.400 | 1.500 |
| θ1 | 0° | 7.5° | 15° |
| θ2 | 4° | - | - |

ECN: E21-0682-Rev. C, 27-Dec-2021
DWG: 5968

**Notes**

- Dimensioning and tolerancing per ASME Y14.5M-1994
- All dimension are in millimeters, angles are in degrees
- Heat sink side flash is max. 0.8 mm




For technical questions, contact: hvmos.techsupport@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

chanhvinh.com



## RECOMMENDED MINIMUM PADS FOR DPAK (TO-252)




Recommended Minimum Pads
Dimensions in Inches/(mm)

Return to Index

APPLICATION NOTE

chanhvinh.com



# Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

*© 2022 VISHAY INTERTECHNOLOGY, INC. ALL RIGHTS RESERVED*