chanhvinh.com


IRFZ20, SiHFZ20


Vishay Siliconix

Power MOSFET

PRODUCT SUMMARY		
V_{DS} (V)	50	
$R_{DS(on)}$ (Ω)	V_{GS} = 10 V	0.10
Q_g (Max.) (nC)	17	
Q_{gs} (nC)	9.0	
Q_{gd} (nC)	3.0	
Configuration	Single	

TO-220AB





N-Channel MOSFET

FEATURES

- Extremely Low $R_{DS(on)}$
- Compact Plastic Package
- Fast Switching
- Low Drive Current
- Ease of Paralleling
- Excellent Temperature Stability
- Parts Per Million Quality
- Compliant to RoHS Directive 2002/95/EC

Pb Available

RoHS* COMPLIANT

DESCRIPTION

The technology has expanded its product base to serve the low voltage, very low $R_{DS(on)}$ MOSFET transistor requirements. Vishay's highly efficient geometry and unique processing have been combined to create the lowest on resistance per device performance. In addition to this feature all have documented reliability and parts per million quality!

The transistor also offer all of the well established advantages of MOSFETs such as voltage control, very fast switching, ease of paralleling, and temperature stability of the electrical parameters.

They are well suited for applications such as switching power supplies, motor controls, inverters, choppers, audio amplifiers, high energy pulse circuits, and in systems that are operated from low voltage batteries, such as automotive, portable equipment, etc.

ORDERING INFORMATION	
Package	TO-220AB
Lead (Pb)-free	IRFZ20PbF
	SiHFZ20-E3
SnPb	IRFZ20
	SiHFZ20

ABSOLUTE MAXIMUM RATINGS					
PARAMETER			SYMBOL	LIMIT	UNIT
Drain-Source Voltage[a]			V_{DS}	50	V
Gate-Source Voltage[a]			V_{GS}	± 20	
Continuous Drain Current	V_{GS} at 10 V	T_C = 25 °C	I_D	15	A
		T_C = 100 °C		10	
Pulsed Drain Current[b]			I_{DM}	60	
Single Pulse Avalanche Energy[c]			E_{AS}	5	mJ
Linear Derating Factor (see fig. 16)				0.32	W/°C
Maximum Power Dissipation (see fig. 16)	T_C = 25 °C		P_D	40	W
Operating Junction and Storage Temperature Range			T_J, T_{stg}	- 55 to + 150	°C
Soldering Recommendations (Peak Temperature)	for 10 s			300 (0.063" (1.6 mm) from case	

Notes

a. T_J = 25 °C to 150 °C


b. Repeditive rating: Pulse width limited by max. junction temperature. See transient temperature impedance curve (see fig. 11).

c. Starting T_J = 25 °C, L = 0.07 mH, R_g = 25 Ω, I_{AS} = 12 A

* Pb containing terminations are not RoHS compliant, exemptions may apply

chanhvinh.com

THERMAL RESISTANCE RATINGS				
PARAMETER	**SYMBOL**	**TYP.**	**MAX.**	**UNIT**
Typical Socket Mount, Junction-to-Ambient	R_{thJA}	-	80	°C/W
Case-to-Sink, Mounting Surface Flat, Smooth, and Greased	R_{thCS}	1.0	-	
Junction-to-Case	R_{thJC}	-	3.12	

ELECTRICAL CHARACTERISTICS (T_J = 25 °C, unless otherwise noted)							
PARAMETER	**SYMBOL**	**TEST CONDITIONS**		**MIN.**	**TYP.**	**MAX.**	**UNIT**
Static							
Drain-Source Breakdown Voltage	V_{DS}	V_{GS} = 0 V, I_D = 250 µA		50	-	-	V
Gate-Source Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = 250 µA		2.0	-	4.0	V
Gate-Source Leakage	I_{GSS}	V_{GS} = ± 20 V		-	-	± 500	nA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} > Max. Rating, V_{GS} = 0 V		-	-	250	µA
		V_{DS} = Max. Rating x 0.8, V_{GS} = 0 V, T_C = 125 °C		-	-	1000	
On-State Drain Current	$I_{D(on)}$	V_{GS} = 10 V	V_{DS} > $I_{D(on)}$ x $R_{DS(on)}$ max.	-	-	15	A
Drain-Source On-State Resistance[b]	$R_{DS(on)}$	V_{GS} = 10 V	I_D = 10 A	-	0.080	0.10	Ω
Forward Transconductance[b]	g_{fs}	V_{DS} > $I_{D(on)}$ x $R_{DS(on)}$ max., I_D = 9.0 A		5.0	6.0	-	S
Dynamic							
Input Capacitance	C_{iss}	V_{GS} = 0 V, V_{DS} = 25 V, f = 1.0 MHz, see fig. 11		-	560	860	pF
Output Capacitance	C_{oss}			-	250	350	
Reverse Transfer Capacitance	C_{rss}			-	60	100	
Total Gate Charge	Q_g	V_{GS} = 10 V	I_D = 20 A, V_{DS} = 0.8 max. rating, see fig. 18 for test circuit (Gate charge is essentially independent of operating temperature)	-	12	17	nC
Gate-Source Charge	Q_{gs}			-	9.0	-	
Gate-Drain Charge	Q_{gd}			-	3.0	-	
Turn-On Delay Time	$t_{d(on)}$	V_{DD} = 25 V, I_D = 9.0 A, Z_0 = 50 Ω, see fig. 5[b]		-	15	30	ns
Rise Time	t_r			-	45	90	
Turn-Off Delay Time	$t_{d(off)}$			-	20	40	
Fall Time	t_f			-	15	30	
Internal Drain Inductance	L_D	Modified MOSFET symbol showing the internal device inductances 		-	3.5	-	nH
Internal Source Inductance	L_S			-	4.5	-	
Drain-Source Body Diode Characteristics							
Continuous Source-Drain Diode Current	I_S	MOSFET symbol showing the integral reverse p - n junction rectifier 		-	-	15	A
Pulsed Diode Forward Current[a]	I_{SM}			-	-	60	
Body Diode Voltage[b]	V_{SD}	T_C = 25 °C, I_S = 15 A, V_{GS} = 0 V		-	-	1.5	V
Body Diode Reverse Recovery Time	t_{rr}	T_J = 150 °C, I_F = 15 A, dI_F/dt = 100 A/µs		-	100	-	ns
Body Diode Reverse Recovery Charge	Q_{rr}			-	0.4	-	µC
Forward Turn-On Time	t_{on}	Intrinsic turn-on time is negligible (turn-on is dominated by L_S and L_D)					

Notes

a. Repeditive rating: Pulse width limited by max. junction temperature. See transient temperature impedance curve (see fig. 5).

b. Pulse test: Pulse width ≤ 300 µs; duty cycle ≤ 2 %.

chanhvinh.com

TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)




Fig. 1 - Typical Output Characteristics




Fig. 3 - Typical Transfer Characteristics




Fig. 2 - Typical Saturation Characteristics




Fig. 4 - Normalized On-Resistance vs. Temperature

chanhvinh.com




Fig. 5 - Typical Capacitance vs. Drain-to-Source Voltage




Fig. 7 - Typical Source-Drain Diode Forward Voltage




Fig. 6 - Typical Gate Charge vs. Gate-to-Source Voltage




Fig. 8 - Maximum Safe Operating Area

chanhvinh.com




Fig. 9 - Maximum Drain Current vs. Case Temperature




Fig. 10a - Switching Time Test Circuit




Fig. 10b - Switching Time Waveforms




Fig. 11 - Maximum Effective Transient Thermal Impedance, Junction-to-Case vs. Pulse Duration




Fig. 12a - Clamped Inductive Test Circuit




Fig. 12b - Unclamped Inductive Waveforms

chanhvinh.com




Fig. 13 - Typical Transconductance vs. Drain Current




Fig. 14 - Breakdown Voltage vs. Temperature




Fig. 16 - Power vs. Temperature Derating Curve




Fig. 15 - Typical On-Resistance vs. Drain Current






Fig. 17 - Gate Charge Test Circuit

chanhvinh.com

Peak Diode Recovery dV/dt Test Circuit





Note


a. V_{GS} = 5 V for logic level devices

Fig. 14 - For N-Channel

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see http://www.vishay.com/ppg?91340.

chanhvinh.com

TO-220-1



DIM.	MILLIMETERS		INCHES	
	MIN.	MAX.	MIN.	MAX.
A	4.14	4.70	0.163	0.185
b	0.69	1.02	0.027	0.040
b(1)	1.14	1.73	0.045	0.068
c	0.36	0.61	0.014	0.024
D	14.33	15.85	0.564	0.624
E	9.96	10.52	0.392	0.414
e	2.41	2.67	0.095	0.105
e(1)	4.88	5.28	0.192	0.208
F	0.43	1.40	0.017	0.055
H(1)	6.10	6.48	0.240	0.255
J(1)	2.41	2.92	0.095	0.115
L	13.36	14.40	0.526	0.567
L(1)	3.33	4.04	0.131	0.159
Ø P	3.53	3.94	0.139	0.155
Q	2.59	3.00	0.102	0.118
ECN: X15-0003-Rev. A, 19-Jan-15 DWG: 6031				

Notes

- M* = 0.052 inches to 0.064 inches (dimension including protrusion), heatsink hole for HVM
- Outline conforms to JEDEC® outline TO-220AB with exception of dimension F

For technical questions, contact: hvm@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

chanhvinh.com

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay’s knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer’s responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer’s technical experts. Product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.