chanhvinh.com

MURS340 & MURS360

New Product Vishay General Semiconductor

Surface Mount Ultrafast Plastic Rectifier



DO-214AB (SMC)

FEATURES

- Glass passivated chip junction
- Ideal for automated placement
- Ultrafast reverse recovery time
- Low switching losses, high efficiency
- High forward surge capability
- Meets MSL level 1, per J-STD-020C, LF max peak of 260 °C
- Solder Dip 260 °C, 40 seconds
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC

MAJOR RATINGS AND CHARACTERISTICS	
$I_{F(AV)}$	3.0 A
V_{RRM}	400 V, 600 V
I_{FSM}	125 A
t_{rr}	50 ns
V_F	1.05 V
T_j max.	175 °C

TYPICAL APPLICATIONS

For use in high frequency rectification and free-wheeling application in switching mode converters and inverters for consumer, computer, automotive and telecommunication.

MECHANICAL DATA

Case: DO-214AB (SMC)

Epoxy meets UL 94V-0 flammability rating

Terminals: Matte tin plated leads, solderable per J-STD-002B and JESD22-B102D

E3 suffix for commercial grade, HE3 suffix for high reliability grade (AEC Q101 qualified)

Polarity: Color band denotes cathode end

MAXIMUM RATINGS (T_A = 25 °C unless otherwise noted)

PARAMETER		SYMBOL	MURS340	MURS360	UNIT
Device marking code			MG	MJ	
Maximum repetitive peak reverse voltage		V_{RRM}	400	600	V
Working peak reverse voltage		V_{RWM}	400	600	V
Maximum DC blocking voltage		V_{DC}	400	600	V
Maximum average forward rectified current at: (see Fig. 1)	T_L = 130 °C T_L = 115 °C	$I_{F(AV)}$	3.0 4.0		A
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load		I_{FSM}	125		A
Operating junction and storage temperature range		T_J, T_{STG}	- 65 to + 175		°C

chanhvinh.com

ELECTRICAL CHARACTERISTICS (T_A = 25 °C unless otherwise noted)					
PARAMETER	**TEST CONDITIONS**	**SYMBOL**	**MURS340**	**MURS360**	**UNIT**
Maximum instantaneous forward voltage (1)	I_F = 3.0 A, T_j = 25 °C I_F = 4.0 A, T_j = 25 °C I_F = 3.0 A, T_j = 150 °C	V_F	1.25 1.28 1.05		V
Maximum instantaneous reverse current at rated DC blocking voltage (1)	T_j = 25 °C T_j = 150 °C	I_R	10 250		µA
Maximum reverse recovery time	at I_F = 0.5 A, I_R = 1.0 A, I_{rr} = 0.25 A	t_{rr}	50		ns
Maximum reverse recovery time	at I_F = 1.0 A, di/dt = 50 A/µs, V_R = 30 V, I_{rr} = 10 % I_{RM}	t_{rr}	75		ns
Maximum forward recovery time	I_F = 1.0 A, di/dt = 100 A/µs, Rec. to 1.0 V	t_{fr}	25		ns

Note:

(1) Pulse test: t_p = 300 µs, duty cycle ≤ 2 %

THERMAL CHARACTERISTICS (T_A = 25 °C unless otherwise noted)				
PARAMETER	**SYMBOL**	**MURS340**	**MURS360**	**UNIT**
Typical thermal resistance junction to ambient	$R_{\theta JL}$	11		°C/W

ORDERING INFORMATION				
PREFERRED P/N	**UNIT WEIGHT (g)**	**PREFERRED PACKAGE CODE**	**BASE QUANTITY**	**DELIVERY MODE**
MURS340-E3/57T	0.211	57T	850	7" Diameter Plastic Tape & Reel
MURS340-E3/9AT	0.211	9AT	3200	13" Diameter Plastic Tape & Reel

RATINGS AND CHARACTERISTICS CURVES

(T_A = 25 °C unless otherwise noted)




Figure 1. Forward Current Derating Curve




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current

chanhvinh.com




Figure 3. Typical Instantaneous Forward Characteristics




Figure 5. Typical Junction Capacitance




Figure 4. Typical Reverse Characteristics





Figure 6. Typical Reverse Switching Characteristics

PACKAGE OUTLINE DIMENSIONS in inches (millimeters)



chanhvinh.com

Legal Disclaimer Notice

Vishay

Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.