
chanhvinh.com

Low Current 13 mm Seven Segment Display



FEATURES

- Low power consumption
- Suitable for DC and multiplex operation
- Evenly lighted segments
- Grey package surface
- Untinted segments
- Luminous intensity categorized
- Wide viewing angle
- Compliant to RoHS directive 2002/95/EC and in accordance to WEEE 2002/96/EC

Pb-free

e4

RoHS COMPLIANT

DESCRIPTION

The TDSL51.0 series are 13 mm character seven segment low current LED displays in a very compact package.
The displays are designed for a viewing distance up to 7 m and available in high efficiency red. The grey package surface and the evenly lighted untinted segments provide an optimum on-off contrast.
All displays are categorized in luminous intensity groups. That allows users to assemble displays with uniform appearence.
Typical applications include instruments, panel meters, point-of-sale terminals and household equipment.

APPLICATIONS

- Panel meters
- Test- and measure-equipment
- Point-of-sale terminals
- Control units

PRODUCT GROUP AND PACKAGE DATA

- Product group: display
- Package: 13 mm
- Product series: low current
- Angle of half intensity: ± 50°

PARTS TABLE

PART	COLOR	LUMINOUS INTENSITY at 2 mA	CIRCUITRY
TDSL5150	Red	I_V = 400 µcd (typ.)	Common anode
TDSL5150-GH	Red	I_V = (450 to 1400) µcd	Common anode
TDSL5160	Red	I_V = 400 µcd (typ.)	Common cathode
TDSL5160-GH	Red	I_V = (450 to 1400) µcd	Common cathode

ABSOLUTE MAXIMUM RATINGS (1) TDSL5150, TDSL5160

PARAMETER	TEST CONDITION	SYMBOL	VALUE	UNIT
Reverse voltage per segment		V_R	6	V
DC forward current per segment		I_F	15	mA
Peak forward current per segment		I_{FM}	45	mA
Surge forward current per segment	$t_p \leq 10$ µs (non repetitive)	I_{FSM}	100	mA
Power dissipation	$T_{amb} \leq 45$ °C	P_V	320	mW
Junction temperature		T_j	100	°C
Operating temperature range		T_{amb}	- 40 to + 85	°C
Storage temperature range		T_{stg}	- 40 to + 85	°C
Soldering temperature	t ≤ 3 s 2 mm below seating plane	T_{sd}	260	°C
Thermal resistance LED junction/ambient		R_{thJA}	180	K/W

Note

(1) T_{amb} = 25 °C, unless otherwise specified

chanhvinh.com

TDSL51..

Vishay Semiconductors Low Current 13 mm Seven Segment Display

OPTICAL AND ELECTRICAL CHARACTERISTICS (1) TDSL5150, TDSL5160, RED							
PARAMETER	**TEST CONDITION**	**PART**	**SYMBOL**	**MIN.**	**TYP.**	**MAX.**	**UNIT**
Luminous intensity per segment (2) (digit average)	I_F = 2 mA	TDSL5150	I_V	280	400	-	µcd
		TDSL5150-GH	I_V	450	-	1400	
		TDSL5160	I_V	280	400	-	
		TDSL5160-GH	I_V	450	-	1400	
	I_F = 5 mA	TDSL5150, TDSL5160	I_V	-	1600	-	
	I_F = 20 mA, t_p/T = 0.25		I_V	-	2000	-	
Dominant wavelength	I_F = 2 mA		λ_d	612	-	625	nm
Peak wavelength	I_F = 2 mA		λ_p	-	635	-	nm
Angle of half intensity	I_F = 2 mA		φ	-	± 50	-	deg
Forward voltage per segment	I_F = 2 mA		V_F	-	1.8	2.4	V
	I_F = 20 mA		V_F	-	2.7	3	V
Reverse voltage per segment	I_F = 10 µA		V_R	6	20	-	V
Junction capacitance	V_R = 0 V, f = 1 MHz		C_j	-	30	-	pF

Notes

(1) T_{amb} = 25 °C, unless otherwise specified

(2) $I_{Vmin.}$ and I_V groups are mean values of all segments (a to g, D1 to D4), matching factor within segments is ≥ 0.5, excluding decimal points and colon.

LUMINOUS INTENSITY CLASSIFICATION		
GROUP	**LIGHT INTENSITY (µcd)**	
STANDARD	**MIN.**	**MAX.**
E	180	360
F	280	560
G	450	900
H	700	1400
I	1100	2200
K	1800	3600

BASIC CHARACTERISTICS

T_{amb} = 25 °C, unless otherwise specified




Fig. 1 - Forward Current vs. Ambient Temperature




Fig. 2 - Rel. Luminous Intensity vs. Angular Displacement

chanhvinh.com




Fig. 3 - Forward Current vs. Forward Voltage




Fig. 6 - Relative Luminous Intensity vs. Forward Current




Fig. 4 - Rel. Luminous Intensity vs. Ambient Temperature




Fig. 7 - Relative Intensity vs. Wavelength






Fig. 5 - Rel. Lumin. Intensity vs. Forw. Current/Duty Cycle



chanhvinh.com

PACKAGE DIMENSIONS in millimeters



Drawing-No.: 6.544-5150.01-4
Issue: 1; 21.11.95
95 11344

chanhvinh.com

Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.