
chanhvinh.com


# Data Sheet | Item Number: 857-624

Solid-state timer relay module; Nominal input voltage: 24 VDC; Output voltage range: 0 … 24 VDC; Limiting continuous current: 2 A; 2-wire connection; Multifunction/ Multitime; Yellow status indicator; Module width: 6 mm

https://www.wago.com/857-624




Dimensions in mm

**Features:**

- 4 functions
- Function and time range adjustable via DIP switch

## Notes

| | |
|---|---|
| Note | Optocouplers and solid state relays are designed for use in signal processing networks, which are not supplied by the low-voltage power supply networks. |

## Technical data

### Control circuit

| | |
|---|---|
| Nominal input voltage $U_N$ | DC 24 V |
| Input voltage range | -15 … +30 % |
| Nominal input current at $U_N$ | 10 mA |
| Time range | adjustable: 0.1 … 10 s; 3 … 300 s; 0.3 … 30 min; 3 … 300 min |
| Reset time | 50 ms |
| Repeat accuracy | 1 % |

### Control circuit

| | |
|---|---|
| Functions | On-delay<br>Single-shot leading edge<br>On-delay and single-shot leading edge (1 s fixed)<br>Flashing |

chanhvinh.com



## Load circuit

| | |
|---|---|
| Circuit type | 2-wire connection |
| Limiting continuous current | 2 A |
| Nominal output voltage | DC 24 V |
| Output voltage range | DC 0 … 30 V |
| Voltage drop | ≤ 0.12 VDC |
| Leakage current at rated voltage | ≤ 1 µA |
| Switching current (min.) | 50 µA |
| Turn-on time | ≤ 100 µs |
| Turn-off time | ≤ 2 ms |

## Signaling

| | |
|---|---|
| Status indicator | Yellow LED |

## Safety and protection

| | |
|---|---|
| Dielectric strength (control/load circuit) (AC, 1 min) | 3.75 kVrms |
| Protection type | IP20 |

## Connection data

| | |
|---|---|
| Connection technology | Push-in CAGE CLAMP® |
| Solid conductor | 0.34 … 2.5 mm² / 22 … 14 AWG |
| Fine-stranded conductor | 0.34 … 2.5 mm² / 22 … 14 AWG |
| Strip length | 9 … 10 mm / 0.35 … 0.39 inches |

## Physical data

| | |
|---|---|
| Width | 6 mm / 0.236 inches |
| Height | 94 mm / 3.701 inches |
| Depth from upper-edge of DIN-rail | 81 mm / 3.189 inches |

## Mechanical data

| | |
|---|---|
| Mounting type | DIN-35 rail |

## Material data

| | |
|---|---|
| Fire load | 0.548 MJ |
| Weight | 29.5 g |

## Environmental requirements

| | |
|---|---|
| Ambient temperature (operation at $U_N$) | -20 … +60 °C |
| Ambient temperature (storage) | -40 … +70 °C |
| Processing temperature | -25 … +50 °C |
| Relative humidity | 5 … 95 % (no condensation permissible) |
| Operating altitude (max.) | 2000 m |

 Continued on next page

chanhvinh.com



## Standards and specifications

| | |
|---|---|
| Standards/specifications | EN 61812-1<br>EN 61373<br>EN 50121-3-2 |

## Basic relay

| | |
|---|---|
| WAGO Basic Relay | 857-161 |

## Commercial data

| | |
|---|---|
| Product Group | 6 (INTERFACE ELECTRONIC) |
| eCl@ss 10.0 | 27-37-16-05 |
| eCl@ss 9.0 | 27-37-16-05 |
| ETIM 8.0 | EC001439 |
| ETIM 7.0 | EC001439 |
| PU (SPU) | 1 pcs |
| Packaging type | Bag |
| Country of origin | DE |
| GTIN | 4050821565680 |
| Customs tariff number | 85364900990 |

## Environmental Product Compliance

| | |
|---|---|
| CAS-No. | 11120-22-2<br>1303-86-2<br>1317-36-8<br>7439-92-1<br>79-94-7 |
| REACH Candidate List Substance | 2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol<br>Diboron trioxide<br>Lead<br>Lead monoxide<br>Lead silicate |
| RoHS Compliance Status | Compliant,With Exemption |
| RoHS Exemption | 6(c)<br>7(a)<br>7(c)-I<br>7(c)-II |
| SCIP notification number (Austria) | debe81a1-15a1-4a4f-b8a1-1cc9dbf77da1 |
| SCIP notification number (Belgium) | 1e540a72-b56f-4b47-ab28-05b99f354198 |
| SCIP notification number (Bulgaria) | 8772d7cc-008d-4bb1-8cb9-a3a1c5824a42 |
| SCIP notification number (Czech Republic) | f7ef3336-16eb-4e06-9ed1-c774015b095b |
| SCIP notification number (Denmark) | b31d4dc5-36c3-4ba4-9839-2efc41d86e1e |
| SCIP notification number (Finland) | cd2ac7ab-5cd7-4d1e-b264-2fffe6874404 |
| SCIP notification number (France) | 9dbbbc0d-e475-438c-a2a5-8755a3762df2 |
| SCIP notification number (Germany) | ed5a1dd6-e2ff-40ea-8343-cf045e514b3c |
| SCIP notification number (Hungary) | be30e700-848b-4954-a0be-0b66c234ea76 |
| SCIP notification number (Italy) | cfeaaf04-aa7f-4a45-987d-7c85eebd14e8 |
| SCIP notification number (Netherlands) | 35b9475d-b09b-4049-8c2c-616fdae3d3e1 |
| SCIP notification number (Poland) | 6a2db9b3-9e52-452f-b652-7fd09598200b |
| SCIP notification number (Romania) | 237a1ca6-3558-42d5-86ae-62b71c17ec16 |
| SCIP notification number (Sweden) | edf543a3-85e1-42be-9ab9-092c88c92a7a |

chanhvinh.com



## Approvals / Certificates

### General approvals

| Approval | Standard | Certificate Name |
|---|---|---|
| EAC<br>Brjansker Zertifizierungs-stelle | TP TC 020/2011 | EAC_Certificate_RU_C-DE.AM02.B.00115_19 |
| UL<br>Underwriters Laboratories Inc. (ORDINARY LOCATI-ONS) | UL 508 | E175199 Sec.4 |

### Declarations of conformity and manufacturer's declarations

| Approval | Standard | Certificate Name |
|---|---|---|
| EU-Declaration of Confor-mity<br>WAGO GmbH & Co. KG | - | - |

## Downloads

### Environmental Product Compliance

**Compliance Search**

Environmental Product Compliance 857-624

## Documentation

**Bid Text**

| | | | |
|---|---|---|---|
| 857-624 | 19.02.2019 | xml<br>4.69 KB | |
| 857-624 | 20.02.2019 | docx<br>16.72 KB | |

**Instruction Leaflet**

| | | | |
|---|---|---|---|
| Zeitrelaismodul; Ein-gangsnennspannung DC 24 V | V 2.0.0<br>10.03.2022 | pdf<br>2021.26 KB | |

## CAD/CAE-Data

**CAD data**

2D/3D Models 857-624

**CAE data**

EPLAN Data Portal 857-624

WSCAD Universe 857-624

ZUKEN Portal 857-624

 Continued on next page

chanhvinh.com

# Data Sheet | Item Number: 857-624

https://www.wago.com/857-624

## 1 Compatible Products

### 1.1 Optional Accessories

#### 1.1.1 Basic relay

##### 1.1.1.1 Basic solid-state relay



Item No.: 857-161
Basic solid-state relay; Nominal input voltage: 24 VDC; Output voltage range: 0 … 30 VDC; Limiting continuous current: 3 A

#### 1.1.2 Ferrule

##### 1.1.2.1 Ferrule



Item No.: 216-241
Ferrule; Sleeve for 0.5 mm² / 20 AWG; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; white



Item No.: 216-242
Ferrule; Sleeve for 0.75 mm² / 18 AWG; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; gray



Item No.: 216-243
Ferrule; Sleeve for 1 mm² / AWG 18; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; red



Item No.: 216-244
Ferrule; Sleeve for 1.5 mm² / AWG 16; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; black

#### 1.1.3 Jumper

##### 1.1.3.1 Jumper



Item No.: 281-482
Jumper; 2-way; insulated; gray



Item No.: 859-410/000-006
Jumper; for jumper slot; 10-way; insulated; blue



Item No.: 859-410
Jumper; for jumper slot; 10-way; insulated; light gray



Item No.: 859-410/000-005
Jumper; for jumper slot; 10-way; insulated; red



Item No.: 859-410/000-029
Jumper; for jumper slot; 10-way; insulated; yellow



Item No.: 859-402/000-006
Jumper; for jumper slot; 2-way; insulated; blue



Item No.: 859-402
Jumper; for jumper slot; 2-way; insulated; light gray



Item No.: 859-402/000-005
Jumper; for jumper slot; 2-way; insulated; red



Item No.: 859-402/000-029
Jumper; for jumper slot; 2-way; insulated; yellow



Item No.: 859-403/000-006
Jumper; for jumper slot; 3-way; insulated; blue



Item No.: 859-403
Jumper; for jumper slot; 3-way; insulated; light gray



Item No.: 859-403/000-005
Jumper; for jumper slot; 3-way; insulated; red



Item No.: 859-403/000-029
Jumper; for jumper slot; 3-way; insulated; yellow



Item No.: 859-404/000-006
Jumper; for jumper slot; 4-way; insulated; blue



Item No.: 859-404
Jumper; for jumper slot; 4-way; insulated; light gray



Item No.: 859-404/000-005
Jumper; for jumper slot; 4-way; insulated; red



Item No.: 859-404/000-029
Jumper; for jumper slot; 4-way; insulated; yellow



Item No.: 859-405/000-006
Jumper; for jumper slot; 5-way; insulated; blue



Item No.: 859-405
Jumper; for jumper slot; 5-way; insulated; light gray



Item No.: 859-405/000-005
Jumper; for jumper slot; 5-way; insulated; red



Item No.: 859-405/000-029
Jumper; for jumper slot; 5-way; insulated; yellow



Item No.: 859-406/000-006
Jumper; for jumper slot; 6-way; insulated; blue



Item No.: 859-406
Jumper; for jumper slot; 6-way; insulated; light gray



Item No.: 859-406/000-005
Jumper; for jumper slot; 6-way; insulated; red



Item No.: 859-406/000-029
Jumper; for jumper slot; 6-way; insulated; signal yellow



Item No.: 859-407/000-006
Jumper; for jumper slot; 7-way; insulated; blue



Item No.: 859-407
Jumper; for jumper slot; 7-way; insulated; light gray



Item No.: 859-407/000-005
Jumper; for jumper slot; 7-way; insulated; red


Continued on next page

chanhvinh.com



### 1.1.3.1 Jumper



Item No.: 859-407/000-029
Jumper; for jumper slot; 7-way; insulated; yellow



Item No.: 859-408/000-006
Jumper; for jumper slot; 8-way; insulated; blue



Item No.: 859-408
Jumper; for jumper slot; 8-way; insulated; light gray



Item No.: 859-408/000-005
Jumper; for jumper slot; 8-way; insulated; red



Item No.: 859-408/000-029
Jumper; for jumper slot; 8-way; insulated; yellow



Item No.: 859-409/000-006
Jumper; for jumper slot; 9-way; insulated; blue



Item No.: 859-409
Jumper; for jumper slot; 9-way; insulated; light gray



Item No.: 859-409/000-005
Jumper; for jumper slot; 9-way; insulated; red



Item No.: 859-409/000-029
Jumper; for jumper slot; 9-way; insulated; yellow

## 1.1.4 Marking

### 1.1.4.1 Double marker carrier



Item No.: 209-128
Adaptor; gray

### 1.1.4.2 Group marker carrier



Item No.: 249-105
Group marker carrier; gray

### 1.1.4.3 Marker



Item No.: 209-183
Marker; white



Item No.: 793-5501
WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; white



Item No.: 793-502
WMB marking card; as card; MARKED; 1 ... 10 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 793-566
WMB marking card; as card; MARKED; 1 ... 50 (2x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 793-503
WMB marking card; as card; MARKED; 11 ... 20 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 793-504
WMB marking card; as card; MARKED; 21 ... 30 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 793-505
WMB marking card; as card; MARKED; 31 ... 40 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 793-506
WMB marking card; as card; MARKED; 41 ... 50 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 793-501
WMB marking card; as card; not stretchable; plain; snap-on type; white



Item No.: 2009-115
WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white


Continued on next page

chanhvinh.com



### 1.1.4.4 Marking device



Item No.: 210-110
Fiber-tip pen

### 1.1.4.5 Marking strip



Item No.: 2009-110
Marking strips; for Smart Printer; on reel; not stretchable; plain; snap-on type; white

### 1.1.4.6 Protective marker cover



Item No.: 209-184
Protection cover; transparent

## 1.1.5 Tool

### 1.1.5.1 Operating tool



Item No.: 210-720
Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured