chanhvinh.com

Date: 24/01/2024

A-10 ; 0...600 bar gauge; 4...20 mA, 2-W @ 8...30 V DC

Pressure transmitter Model A-10

Item number:	12797805
Quantity:	1 pcs.
Order code:	A-10-3-BG560-HD1Z-AA-AGZ-ZW W1011A10Z-SZ3S-ZZFWPA-2AZZZSAZZZA3Z
Overview:	A-10 ; 0...600 bar gauge; 4...20 mA, 2-W @ 8...30 V DC Pressure transmitter Model A-10 Non-linearity: 0.25% BFSL Process connection: G 1/4 A DIN EN ISO 1179-2; Sealing: NBR Electrical connection: valve connector, size A Pin assignment: U+=1, U-=2 Permissible medium temperature: 0...+80 °C Approvals: cULus Type of packaging: folding box single WIKA standard - specification according to data sheet PE 81.60
Details:	Pressure transmitter Model A-10 for general applications Specifications according to data sheet: PE 81.60 Wetted parts: 316L Case: 316L Non-linearity: 0.25% BFSL Unit: bar Pressure type: gauge Measuring range: 0...600 bar gauge Process connection: G 1/4 A DIN EN ISO 1179-2 Sealing: NBR Permissible medium temperature: 0...+80 °C Output signal: 4 ... 20 mA, 2-wire Power supply: 8...30 V DC Electrical connection: valve connector, size A Approvals: cULus W1 (Wika standard) Customer address: www.wika.com Model name customer-specific: A-10 Pressure port: Standard Type of packaging: folding box single Sealing colour: WIKA standard (blue) Test protocol: with test protocol Main Language: English Pin assignment: U+=1, U-=2 Customer-specific: WIKA standard - specification according to data sheet Model: A-10 2.0

© 2024 - WIKA Instruments s.a.r.l.

chanhvinh.com

Date: 24/01/2024

Operating Instructions: with printed OI
Additional Data: without

chanhvinh.com

© 2024 - WIKA Instruments s.a.r.l.