chanhvinh.com

Date: 11/04/2023

HP-2-S ; 0...5000 bar; 4...20 mA, 2-W

Pressure transmitter for highest pressure applications

Item number:	13160273
Quantity:	1 pcs.
Order code:	HP-2-S-G-BG650-ML-A-A4Z-ZZ W101-F2ASZZ-ZZ1SSS-ZP-GSEH
Overview:	HP-2-S ; 0...5000 bar; 4...20 mA, 2-W @ 10 ... 30 V DC; Accuracy: 0.5% of span M16 x 1.5 female, with sealing cone Standard 4-pin L-plug DIN EN 175301-803, IP65 UB=1, 0V=2 Specifications according to data sheet: PE 81.53
Details:	Pressure transmitter for highest pressure applications Model HP-2 Specifications according to data sheet: PE 81.53 Case: Stainless steel Type: Standard Accuracy: 0.5% of span Measuring range: 0...5000 bar Process connection: M16 x 1.5 female, with sealing cone Output signal: 4 ... 20 mA, 2-wire Electrical connection: 4-pin L-plug DIN EN 175301-803, IP65 Power supply: 10 ... 30 V DC Pin assignment: UB=1, 0V=2 shield: standard Main Language: standard Test protocol: with test protocol *Made in Germany* on label Customer-specific: WIKA standard - specification according to data sheet

© 2023 - WIKA Instruments s.a.r.l.