chanhvinh.com

*Date: 24/01/2024*

# S-20 ; 0...16 bar gauge; 0 ... 10 V, 3-wire @ DC 12...35 V

## S-20 ; 0...16 bar gauge; 0 ... 10 V, 3-wire @ DC 12...35 V

| | |
|---|---|
| Item number: | 14071204 |
| Quantity: | 1 pcs. |
| Order code: | S-20-3-BG416-HSC3K-F-AGGZZZ-ZWZ W1011S20Z-ZZZZ21Z3-SS1CLZ3APSZZE-ZZGFZZSAZZZS1 |
| Overview: | S-20 ; 0...16 bar gauge; 0 ... 10 V, 3-wire @ DC 12...35 V<br>Pressure transmitter Model S-20<br>Non-linearity: 0.25% BFSL<br>Overpressure limit: 2 times<br>Process connection: G 1/2 B EN 837 ; Sealing: copper<br>Pressure port: D 2.5 mm<br>Electrical connection: angular connector DIN 175301-803 A mating connector included<br>pin assignment el. connection: U+=1, U-=2, S+=3<br>Permissible medium temperature: -30...+100°C<br>shock and vibration resistance: 100 g shock, 20 g vibration<br>Approvals: cULus<br>Test protocol: with test protocol |
| Details: | S-20 ; 0...16 bar gauge; 0 ... 10 V, 3-wire @ DC 12...35 V<br>Pressure transmitter Model S-20<br>Non-linearity: 0.25% BFSL<br>Overpressure limit: 2 times<br>Process connection: G 1/2 B EN 837 ; Sealing: copper<br>Pressure port: D 2.5 mm<br>Electrical connection: angular connector DIN 175301-803 A mating connector included<br>pin assignment el. connection: U+=1, U-=2, S+=3<br>Permissible medium temperature: -30...+100°C<br>shock and vibration resistance: 100 g shock, 20 g vibration<br>Approvals: cULus<br>Test protocol: with test protocol |

© 2024 - WIKA Instruments s.a.r.l.