chanhvinh.com

Date: 22/01/2024

PSM-520; -0.4 ... +7 bar; G 1/4 B

PSM-520; -0.4 ... +7 bar; G 1/4 B

Item number:	14269089
Quantity:	1 pcs.
Order code:	PSM-520-B -1-GBL-Z W101AP521 52
Overview:	PSM-520; -0.4 ... +7 bar; G 1/4 B Pressure switch, heavy-duty version Specifications according to data sheet: PV 35.01 Switching function: Changeover SPDT Setting of switching point: Factory setting Rising pressure: switch point 3 bar, reset point 2 bar, switch differential 1 bar Wetted parts: Copper alloy, free cutting steel tin-plated Additional ordering information: without Non-repeatability: ≤ 2 % of span Measuring principle: Bellows Electrical connection: Rubber grommet for cables □6 ... 14 mm (□0.24 ... 0.55 in) Electrical rating: AC-1: 10 A, AC 230 V resistive load AC-15: 6 A, AC 230 V inductive load Permissible medium temperature: -20 … +100 °C / -4 … +212 °F
Details:	PSM-520; -0.4 ... +7 bar; G 1/4 B Pressure switch, heavy-duty version Specifications according to data sheet: PV 35.01 Switching function: Changeover SPDT Setting of switching point: Factory setting Rising pressure: switch point 3 bar, reset point 2 bar, switch differential 1 bar Wetted parts: Copper alloy, free cutting steel tin-plated Additional ordering information: without Non-repeatability: ≤ 2 % of span Measuring principle: Bellows Electrical connection: Rubber grommet for cables □6 ... 14 mm (□0.24 ... 0.55 in) Electrical rating: AC-1: 10 A, AC 230 V resistive load AC-15: 6 A, AC 230 V inductive load Permissible medium temperature: -20 … +100 °C / -4 … +212 °F

© 2024 - WIKA Instruments s.a.r.l.