chanhvinh.com

Date: 11/04/2023

FSD-4; m3/h; 105 mm; G1/2 A ISO1179-2; one switching output (PNP/NPN) + 4...20 mA/0…10 V

Specifications according to data sheet: FL 80.02

Item number: 14506238

Quantity: 1 pcs.

Order code: FSD-4-EZ-11C0200-1GN16-WWZ-ZZZ W1011FS4Z-2HOSGSEW

Overview:
FSD-4; m3/h; 105 mm; G1/2 A ISO1179-2; one switching output (PNP/NPN) + 4...20 mA/0…10 V
Output signal: one switching output (PNP/NPN) + 4...20 mA/0…10 V
IO-Link: without
Power supply: 15 ... 35 V DC
Unit, display: m3/h
Unit: °C
Probe length: 105 mm
Process connection: G1/2 A ISO1179-2
Sealing: NBR
Accessories process connection: without
Electrical connection: circular connector M12x1, 4-pin
Approvals: cULus
Configuration flow switch: Factory setting acc. to manual
Additional ordering information: without
Specifications according to data sheet: FL 80.02

Details:
Specifications according to data sheet: FL 80.02
Output signal: one switching output (PNP/NPN) + 4...20 mA/0…10 V
IO-Link: without
Unit, display: m3/h
Unit: °C
Pipe Diameter: 200
Process connection: G1/2 A ISO1179-2
Sealing: NBR
Probe length: 105 mm
Approvals: cULus
Configuration flow switch: Factory setting acc. to manual
Certificates: without
Accessories process connection: without
Additional ordering information: without
customer-name begins with: W1 (Wika standard)
Customer logo: WIKA standard
Customer address: www.wika.com
Permissible medium temperature: -20 ... +85°C
Model name customer-specific: FSD-4
Test protocol: without test protocol

© 2023 - WIKA Instruments s.a.r.l.

chanhvinh.com

Date: 11/04/2023

Type of packaging: twist pack
Import documentation CIS-States: without
label: country of origin: *Made in Germany* on label
Customer-specific: WIKA standard - specification according to data sheet
Model: FSD-4

© 2023 - WIKA Instruments s.a.r.l.