chanhvinh.com

Date: 12/04/2023

PSD-4; 0...16 bar gauge ; two switching outputs (PNP/NPN)

PSD-4; 0...16 bar gauge ; two switching outputs (PNP/NPN)

Item number:	45824215
Quantity:	1 pcs.
Order code:	PSD-4-9Z-BG416-861Z-WW-ZZ W1011PS4Z-SZAB-P-GSFI
Overview:	PSD-4; 0...16 bar gauge ; two switching outputs (PNP/NPN) Electronic pressure switch with display Output signal: two switching outputs (PNP/NPN) IO-Link: without Power supply: 15...35 V DC Measuring range: 0...16 bar gauge Process connection: G 1/2 B, flush diaphragm with O-ring Sealing: NBR Media temperature: -20 … 85 °C (-4 ... +185 °F) El. connection: Circular connector M12x1 (4-pin) pin assignment el. connection: U+=1, U-=3, SP1=4, SP2=2 Accuracy: ± 0.5% of span Approvals: cULus with test protocol Specifications according to data sheet: PE 81.86
Details:	PSD-4; 0...16 bar gauge ; two switching outputs (PNP/NPN) Electronic pressure switch with display Output signal: two switching outputs (PNP/NPN) IO-Link: without Power supply: 15...35 V DC Measuring range: 0...16 bar gauge Process connection: G 1/2 B, flush diaphragm with O-ring Sealing: NBR Media temperature: -20 … 85 °C (-4 ... +185 °F) El. connection: Circular connector M12x1 (4-pin) pin assignment el. connection: U+=1, U-=3, SP1=4, SP2=2 Accuracy: ± 0.5% of span Approvals: cULus with test protocol Specifications according to data sheet: PE 81.86

© 2023 - WIKA Instruments s.a.r.l.