chanhvinh.com

Date: 12/04/2023

MW-XXUN - 0...2,5 bar - Adaptor 1/2 NPT-M - 1/2 -14 NPT-F

Diaphragm pressure switch, Stainless steel case

Item number: 48619870

Quantity: 1 pcs.

Order code: MW-XXUN-BBGSB-2AMZZZZZZZZZZZZZZZZZZZZZZ ZCK1AW

Overview:

MW-XXUN - 0...2,5 bar - Adaptor 1/2 NPT-M - 1/2 -14 NPT-F
Diaphragm pressure switch, Stainless steel case
measuring elements and wetted materials: Diaphragm AISI 316, 304, Inconel or Hastelloy (Piston AISI 316)/ Process Connection AISI 316L
Contact version: 1x SPDT silver contact
setting range: 0...2,5 bar
Standard, working range = 0...2,5 bar, proof pressure 5 bar
Process connection: Adaptor 1/2 NPT-M
Electrical connection: 1/2 -14 NPT-F
Enclosure with plate for wall or direct mounting
Ingress Protection: IP66
Diaphragm: Stainless Steel AISI 316/O-Ring: FPM/Connection: Stainless steel AISI 316L
Brand: WIKA Instruments Italia
Specifications according to data sheet: PV 31.10
Repeatability of set point: ≤ 1% of span

Set point definition: Set Point not defined

Details:

Diaphragm pressure switch, Stainless steel case
Model MW
Specifications according to data sheet: PV 31.10
Repeatability of set point: ≤ 1% of span
Contact version: 1x SPDT silver contact
setting range: 0...2,5 bar
working range: Standard, working range = 0...2,5 bar, proof pressure 5 bar
Set Point not defined
Unit: bar
Process connection: Adaptor 1/2 NPT-M
Electrical connection: 1/2 -14 NPT-F
Enclosure with plate for wall or direct mounting
Brand: WIKA Instruments Italia
Ingress Protection: IP66
MW-XXUN
Diaphragm: Stainless Steel AISI 316/O-Ring: FPM/Connection: Stainless steel AISI 316L

© 2023 - WIKA Instruments s.a.r.l.