chanhvinh.com

Date: 11/04/2023

MH-2 ; 0 ... 100 bar; G1/4B; 4...20 mA, 2-W; 1.0% of span

Pressure Transmitter for Mobile Hydraulics

Item number:	48641274
Quantity:	1 pcs.
Order code:	MH-2-A-BBO-GB-MZFNA-ZZZ Z-SDEA
Overview:	MH-2 ; 0 ... 100 bar; G1/4B; 4...20 mA, 2-W; 1.0% of span flying lead, IP 69K 0.5 m Case material: high resistant reinforced glassfibre plastic (PBT) -40 ... +125 °C (-40 ... +257 °F) Manual: can be downloaded from www.wika.com
Details:	Pressure Transmitter for Mobile Hydraulics Model MH-2 Specifications according to data sheet: PE 81.37 Wetted parts: stainless steel 316L and 1.4542 Permissible medium temperature: -40 ... +125 °C (-40 ... +257 °F) Manual: can be downloaded from www.wika.com 4 ... 20 mA, 2-wire Unit: bar Measuring range: 0 ... 100 bar Process connection: G 1/4 B Case material: high resistant reinforced glassfibre plastic (PBT) Electrical connection: flying lead, IP 69K Cable length: 0.5 m WIKA standard - specification according to data sheet Accuracy: 1.0% of span

© 2023 - WIKA Instruments s.a.r.l.