

Date: 11/04/2023

MABXXUN - -50...50 mbar - Adaptor 1/2 NPT-F - 1/2 -14 NPT-F

Diaphragm pressure switch

Item number: 48780813

Quantity: 1 pcs.

[illegible]

Overview:

- MABXXUN - -50...50 mbar - Adaptor 1/2 NPT-F - 1/2 -14 NPT-F
- Diaphragm pressure switch
- measuring elements and wetted materials: Diaphragm AISI 316, 304, Inconel or Hastelloy (Piston AISI 316)/ Process Connection AISI 316L
- Contact version: 1x SPDT silver contact
- setting range: -50...50 mbar
- Standard, working range = -50...50 mbar, proof pressure -100/250 mbar
- Process connection: Adaptor 1/2 NPT-F
- Electrical connection: 1/2 -14 NPT-F
- Enclosure with plate for wall or direct mounting
- Ingress Protection: IP66
- Diaphragm: Stainless Steel AISI 316/O-Ring: PTFE/Connection: Stainless steel AISI 316L
- Brand: WIKA Instruments Italia
- Specifications according to data sheet: PV 31.11
- Repeatability of set point: $\leq 1\%$ of span

Set point definition: Set Point customer-specifically configured

1. set point: -5.00 mbar increasing.

Details:

- Diaphragm pressure switch
- Flameproof enclosure Ex d
- Model MA
- Specifications according to data sheet: PV 31.11
- Repeatability of set point: $\leq 1\%$ of span
- Contact version: 1x SPDT silver contact
- setting range: -50...50 mbar
- working range: Standard, working range = -50...50 mbar, proof pressure -100/250 mbar
- Set Point customer-specifically configured
- Unit: mbar
- Process connection: Adaptor 1/2 NPT-F
- Electrical connection: 1/2 -14 NPT-F
- Enclosure with plate for wall or direct mounting
- Brand: WIKA Instruments Italia
- Ingress Protection: IP66

Date: 11/04/2023



MABXXUN

Diaphragm: Stainless Steel AISI 316/O-Ring: PTFE/Connection: Stainless steel
AISI 316L

1. set point: -5.00 mbar increasing,