chanhvinh.com

Date: 22/04/2024

PCA2PA 40 … 250 bar Adaptor G 1/4 A-M , 1/2 -14 NPT-F

Compact pressure switch, flameproof Enclosure Ex d

Item number: 48782434

Quantity: 1 pcs.

Order code: PCA2PA-BAKC-5ASZZZ1ZZ CZKW
B023000IZZZZZZZZZ
F4-C5- - - - -

Overview:
PCA2PA 40 … 250 bar Adaptor G 1/4 A-M , 1/2 -14 NPT-F
Compact pressure switch, flameproof Enclosure Ex d PCA
switch enclosure: aluminium,copper-free
Measuring elements and wetted parts: Piston Stainless Steel 316, O-Ring FPM
Connection: Stainless steel AISI 316L
contact version: 1xSPDT, silver contact
40 … 250 bar, working range 0 … 400 bar, proof pressure 600 bar
Process connection: Adaptor G 1/4 A-M
Electrical connection: 1/2 -14 NPT-F
standard direct or wall mounting, fixing bore on the case
Ingress Protection: IP66
Brand: WIKA Instruments Italia
Specifications according to data sheet: PV 33.31
Repeatability of set point: ≤ 1% of end of setting range

1. set point: 230.00 bar increasing,

Approvals / Certificates
IECEx-ATEX Ex d

Details:
Compact pressure switch, flameproof Enclosure Ex d
Model PCA
Specifications according to data sheet: PV 33.31
Repeatability of set point: ≤ 1% of end of setting range
switch enclosure: aluminium,copper-free
Measuring elements and wetted parts: Piston Stainless Steel 316, O-Ring FPM
1xSPDT, silver contact
40 … 250 bar, working range 0 … 400 bar, proof pressure 600 bar
Process connection: Adaptor G 1/4 A-M
Electrical connection: 1/2 -14 NPT-F
standard direct or wall mounting, fixing bore on the case
Approvals / Certificates: with
Brand: WIKA Instruments Italia
Ingress Protection: IP66
PCA2PA 40 … 250 bar

© 2024 - WIKA Instruments s.a.r.l.

chanhvinh.com

Date: 22/04/2024

1. set point: 230.00 bar increasing,

Approvals / Certificates
IECEx-ATEX Ex d

chanhvinh.com

© 2024 - WIKA Instruments s.a.r.l.