chanhvinh.com

*Date: 10/04/2023*

# S-11 ; 0 ... 600 bar; 0 ... 10 V, 3-wire

## Pressure transmitter for general applications

| | |
|---|---|
| Item number: | 48783718 |
| Quantity: | 1 pcs. |
| Order code: | S-11-F-BBT-86-QLZGA4ZAZ-ZZZ W101Z-ZZ-C3ASZZ-ZFOSE3 |
| Overview: | S-11 ; 0 ... 600 bar; 0 ... 10 V, 3-wire<br>@ 14...30 V DC; Accuracy: 0.5% of span<br>G 1/2 B, flush diaphragm with O-ring<br>Wetted parts: stainless steel<br>Sealing: FPM/FKM;<br>4-pin L-plug DIN EN 175301-803, IP65 UB=1, 0V=2, S+=3<br>Permissible medium temperature: -30 ... +100 °C (-22 ... +212 °F)<br>Specifications according to data sheet: PE 81.02 |
| Details: | Pressure transmitter for general applications<br>Model S-11<br>with flush diaphragm<br>Specifications according to data sheet: PE 81.02<br>Power supply: DC 10 (14) ... 30 V<br>Case: stainless steel<br>Output signal: 0 ... 10 V, 3-wire<br>Measuring range: 0 ... 600 bar<br>Process connection: G 1/2 B, flush diaphragm with O-ring<br>Wetted parts: stainless steel<br>Sealing: FPM/FKM<br>Accuracy: 0.5% of span<br>Electrical connection: 4-pin L-plug DIN EN 175301-803, IP65<br>Permissible medium temperature: -30 ... +100 °C (-22 ... +212 °F)<br>Power supply: 14...30 V DC<br>Pin assignment: UB=1, 0V=2, S+=3<br>shield: standard<br>WIKA standard - specification according to data sheet<br>Test protocol: without test protocol<br>Certificates: without<br>Import documentation CIS-States: without |

© 2023 - WIKA Instruments s.a.r.l.