chanhvinh.com

Date: 22/04/2024

PCS2MA 1,6 … 10 bar 1/4 NPT-F, 1/2 -14 NPT-F

Compact Pressure Switch

Item number:	73233162
Quantity:	1 pcs.
Order code:	PCS2MA-BAEB-1ASZZZZZZ ZCKW
Overview:	PCS2MA 1,6 … 10 bar 1/4 NPT-F, 1/2 -14 NPT-F Compact Pressure Switch PCS switch enclosure: aluminium,copper-free Measuring elements and wetted parts: Diaphragm Inconel + O-Ring FPM Connection: Stainless steel AISI 316L contact version: 1xSPDT, silver contact Setting range, working range, proof pressure: 1,6 … 10 bar, working range -1 … 25 bar, proof pressure 40 bar Set point definition: Set Point not defined Process connection: 1/4 NPT-F Electrical connection: 1/2 -14 NPT-F standard direct or wall mounting, fixing bore on the case Ingress Protection: IP66 Brand: WIKA Instruments Italia Specifications according to data sheet: PV 33.30 Repeatability of set point: ≤ 1% of end of setting range
Details:	Compact Pressure Switch Model PCS Specifications according to data sheet: PV 33.30 Repeatability of set point: ≤ 1% of end of setting range switch enclosure: aluminium,copper-free Measuring elements and wetted parts: Diaphragm Inconel + O-Ring FPM 1xSPDT, silver contact 1,6 … 10 bar, working range -1 … 25 bar, proof pressure 40 bar Set Point not defined Process connection: 1/4 NPT-F Electrical connection: 1/2 -14 NPT-F standard direct or wall mounting, fixing bore on the case Approvals / Certificates: without Switch standard: without Brand: WIKA Instruments Italia Ingress Protection: IP66 PCS2MA 1,6 … 10 bar

© 2024 - WIKA Instruments s.a.r.l.