chanhvinh.com

CREE

V_{DS}	1200 V
$I_{D\ @\ 25^{\circ}C}$	36 A
$R_{DS(on)}$	80 mΩ

C2M0080120D

Silicon Carbide Power MOSFET
C2M™ MOSFET Technology

N-Channel Enhancement Mode

Features

- High Blocking Voltage with Low On-Resistance
- High Speed Switching with Low Capacitances
- Easy to Parallel and Simple to Drive
- Avalanche Ruggedness
- Halogen Free, RoHS Compliant


Benefits

- Higher System Efficiency
- Reduced Cooling Requirements
- Increased Power Density
- Increased System Switching Frequency

Applications

- Solar Inverters
- Switch Mode Power Supplies
- High Voltage DC/DC Converters
- Battery Chargers
- Motor Drives
- Pulsed Power applications


Package



TO-247-3

Halogen-Free

RoHS



Part Number	Package
C2M0080120D	TO-247-3

Maximum Ratings (T_C = 25 ˚C unless otherwise specified)

Symbol	Parameter	Value	Unit	Test Conditions	Note
V_{DSmax}	Drain - Source Voltage	1200	V	V_{GS} = 0 V, I_D = 100 µA	
V_{GSmax}	Gate - Source Voltage	-10/+25	V	Absolute maximum values	
V_{GSop}	Gate - Source Voltage	-5/+20	V	Recommended operational values	
I_D	Continuous Drain Current	36	A	V_{GS} = 20 V, T_C = 25˚C	Fig. 19
		24		V_{GS} = 20 V, T_C = 100˚C	
$I_{D(pulse)}$	Pulsed Drain Current	80	A	Pulse width t_P limited by T_{jmax}	Fig. 22
P_D	Power Dissipation	192	W	T_C=25˚C, T_J = 150 ˚C	Fig. 20
T_J , T_{stg}	Operating Junction and Storage Temperature	-55 to +150	˚C		
T_L	Solder Temperature	260	˚C	1.6mm (0.063”) from case for 10s	
M_d	Mounting Torque	1 8.8	Nm lbf-in	M3 or 6-32 screw	

chanhvinh.com

Electrical Characteristics (T_C = 25˚C unless otherwise specified)

Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions	Note
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	1200			V	V_{GS} = 0 V, I_D = 100 µA	
$V_{GS(th)}$	Gate Threshold Voltage	2.0	2.9	4	V	V_{DS} = V_{GS}, I_D = 5 mA	Fig. 11
			2.4		V	V_{DS} = V_{GS}, I_D = 5 mA, T_J = 150ºC	
I_{DSS}	Zero Gate Voltage Drain Current		1	100	µA	V_{DS} = 1200 V, V_{GS} = 0 V	
I_{GSS}	Gate-Source Leakage Current			250	nA	V_{GS} = 20 V, V_{DS} = 0 V	
$R_{DS(on)}$	Drain-Source On-State Resistance		80	98	mΩ	V_{GS} = 20 V, I_D = 20 A	Fig. 4, 5, 6
			144			V_{GS} = 20 V, I_D = 20A, T_J = 150ºC	
g_{fs}	Transconductance		10		S	V_{DS}= 20 V, I_{DS}= 20 A	Fig. 7
			9			V_{DS}= 20 V, I_{DS}= 20 A, T_J = 150ºC	
C_{iss}	Input Capacitance		1130		pF	V_{GS} = 0 V V_{DS} = 1000 V f = 1 MHz V_{AC} = 25 mV	Fig. 17, 18
C_{oss}	Output Capacitance		92				
C_{rss}	Reverse Transfer Capacitance		7.5				
E_{oss}	C_{oss} Stored Energy		50		µJ		Fig. 16
E_{AS}	Avalanche Energy, Single Pluse		1		J	I_D = 20A, V_{DD} = 50V	Fig. 29
E_{ON}	Turn-On Switching Energy		523		µJ	V_{DS} = 800 V, V_{GS} = -5/20 V, I_D = 20A, $R_{G(ext)}$ = 2.5Ω, L= 156 µH	Fig. 25
E_{OFF}	Turn Off Switching Energy		72				
$t_{d(on)}$	Turn-On Delay Time		15		ns	V_{DD} = 800 V, V_{GS} = -5/20 V I_D = 20 A, $R_{G(ext)}$ = 2.5 Ω, R_L = 40 Ω, Timing relative to V_{DS} Per IEC60747-8-4 pg 83	Fig. 27
t_r	Rise Time		22				
$t_{d(off)}$	Turn-Off Delay Time		24				
t_f	Fall Time		14				
$R_{G(int)}$	Internal Gate Resistance		3.9		Ω	f = 1 MHz, V_{AC} = 25 mV	
Q_{gs}	Gate to Source Charge		17		nC	V_{DS} = 800 V, V_{GS} = -5/20 V I_D = 20 A Per IEC60747-8-4 pg 21	Fig. 12
Q_{gd}	Gate to Drain Charge		29				
Q_g	Total Gate Charge		71				

Reverse Diode Characteristics

Symbol	Parameter	Typ.	Max.	Unit	Test Conditions	Note
V_{SD}	Diode Forward Voltage	4.3		V	V_{GS} = - 5 V, I_{SD} = 10 A	Fig. 8, 9, 10
		3.8		V	V_{GS} = - 5 V, I_{SD} = 10 A, T_J = 150 °C	
I_S	Continuous Diode Forward Current		36	A	T_C = 25˚C	Note 1
t_{rr}	Reverse Recover time	24		ns	V_{GS} = - 5 V, I_{SD} = 20 A, V_R = 800 V dif/dt = 1950 A/µs	Note 1
Q_{rr}	Reverse Recovery Charge	152		nC		
I_{rrm}	Peak Reverse Recovery Current	10		A		

Note (1): When using SiC Body Diode the maximum recommended V_{GS} = -5V

Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Unit	Test Conditions	Note
$R_{\theta JC}$	Thermal Resistance from Junction to Case	0.60	0.65	°C/W		Fig. 21
$R_{\theta JA}$	Thermal Resistance From Junction to Ambient		40			

chanhvinh.com

Typical Performance




Figure 1. Output Characteristics T_J = -55 °C




Figure 2. Output Characteristics T_J = 25 °C




Figure 3. Output Characteristics T_J = 150 °C




Figure 4. Normalized On-Resistance vs. Temperature




Figure 5. On-Resistance vs. Drain Current
For Various Temperatures




Figure 6. On-Resistance vs. Temperature
For Various Gate Voltage

chanhvinh.com

Typical Performance




Figure 7. Transfer Characteristic for Various Junction Temperatures




Figure 8. Body Diode Characteristic at -55 °C




Figure 9. Body Diode Characteristic at 25 °C




Figure 10. Body Diode Characteristic at 150 °C




Figure 11. Threshold Voltage vs. Temperature




Figure 12. Gate Charge Characteristics

chanhvinh.com

Typical Performance




Figure 13. 3rd Quadrant Characteristic at -55 °C




Figure 14. 3rd Quadrant Characteristic at 25 °C




Figure 15. 3rd Quadrant Characteristic at 150 °C




Figure 16. Output Capacitor Stored Energy




Figure 17. Capacitances vs. Drain-Source Voltage (0 - 200V)




Figure 18. Capacitances vs. Drain-Source Voltage (0 - 1000V)

chanhvinh.com

Typical Performance




Figure 19. Continuous Drain Current Derating vs. Case Temperature




Figure 20. Maximum Power Dissipation Derating vs. Case Temperature




Figure 21. Transient Thermal Impedance (Junction - Case)




Figure 22. Safe Operating Area




Figure 23. Clamped Inductive Switching Energy vs. Drain Current (V_{DD} = 800V)




Figure 24. Clamped Inductive Switching Energy vs. Drain Current (V_{DD} = 600V)

chanhvinh.com

Typical Performance




Figure 25. Clamped Inductive Switching Energy vs. $R_{G(ext)}$




Figure 26. Clamped Inductive Switching Energy vs. Temperature




Figure 27. Switching Times vs. $R_{G(ext)}$




Figure 28. Switching Times Definition




Figure 29. Single Avalanche SOA curve

chanhvinh.com

Test Circuit Schematic




Figure 30. Clamped Inductive Switching Waveform Test Circuit




Figure 31. Body Diode Recovery Test Circuit

ESD Ratings


ESD Test	Total Devices Sampled	Resulting Classification
ESD-HBM	All Devices Passed 1000V	2 (>2000V)
ESD-MM	All Devices Passed 400V	C (>400V)
ESD-CDM	All Devices Passed 1000V	IV (>1000V)

chanhvinh.com

CREE

Package Dimensions

Package TO-247-3






Pinout Information:

- Pin 1 = Gate
- Pin 2, 4 = Drain
- Pin 3 = Source

POS	Inches		Millimeters	
	Min	Max	Min	Max
A	.190	.205	4.83	5.21
A1	.090	.100	2.29	2.54
A2	.075	.085	1.91	2.16
b	.042	.052	1.07	1.33
b1	.075	.095	1.91	2.41
b2	.075	.085	1.91	2.16
b3	.113	.133	2.87	3.38
b4	.113	.123	2.87	3.13
c	.022	.027	0.55	0.68
D	.819	.831	20.80	21.10
D1	.640	.695	16.25	17.65
D2	.037	.049	0.95	1.25
E	.620	.635	15.75	16.13
E1	.516	.557	13.10	14.15
E2	.145	.201	3.68	5.10
E3	.039	.075	1.00	1.90
E4	.487	.529	12.38	13.43
e	.214 BSC		5.44 BSC	
N	3		3	
L	.780	.800	19.81	20.32
L1	.161	.173	4.10	4.40
ØP	.138	.144	3.51	3.65
Q	.216	.236	5.49	6.00
S	.238	.248	6.04	6.30
T	9°	11°	9°	11°
U	9°	11°	9°	11°
V	2°	8°	2°	8°
W	2°	8°	2°	8°

Recommended Solder Pad Layout



TO-247-3

Part Number	Package	Marking
C2M0080120D	TO-247-3	C2M0080120

chanhvinh.com

Notes

- **RoHS Compliance**
  The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS2), as implemented January 2, 2013. RoHS Declarations for this product can be obtained from your Cree representative or from the Product Documentation sections of www.cree.com.

- **REACh Compliance**
  REACh substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future,please contact a Cree representative to insure you get the most up-to-date REACh SVHC Declaration. REACh banned substance information (REACh Article 67) is also available upon request.

- This product has not been designed or tested for use in, and is not intended for use in, applications implanted into the human body nor in applications in which failure of the product could lead to death, personal injury or property damage, including but not limited to equipment used in the operation of nuclear facilities, life-support machines, cardiac defibrillators or similar emergency medical equipment, aircraft navigation or communication or control systems, air traffic control systems.

Related Links

- **C2M PSPICE Models: http://wolfspeed.com/power/tools-and-support**
- **SiC MOSFET Isolated Gate Driver reference design: http://wolfspeed.com/power/tools-and-support**
- **SiC MOSFET Evaluation Board: http://wolfspeed.com/power/tools-and-support**

Copyright © 2019 Cree, Inc. All rights reserved.
The information in this document is subject to change without notice.
Cree, the Cree logo, and Zero Recovery are registered trademarks of Cree, Inc.

Cree, Inc.
4600 Silicon Drive
Durham, NC 27703
USA Tel: +1.919.313.5300
Fax: +1.919.313.5451
www.cree.com/power