chanhvinh.com



# Quartz Crystal Specification

*IQD Part No. + Packaging: LFXTAL014219Bulk*
*Wurth Part No.* ***830014219B***

## Description

- Through-hole cylinder crystal in a press-sealed metal can
- -2X6


  Leaded crystal in a press sealed metal can 2 x 6mm
- Model WATCH-2X6
- Model Issue number 13



## Frequency Parameters

- Frequency 32.7680kHz
- Frequency Tolerance ±20.00ppm
- Tolerance Condition @ 25°C
- Frequency Stability ±0.00ppm
- Operating Temperature Range 0.00 to 0.00°C
- Overtone Order Fundamental
- Ageing ±5ppm max per year @ 25°C

**Outline (mm)**




## Electrical Parameters

- Load Capacitance (CL) 6.00pF
- Shunt Capacitance (C0) 2.5pF typ
- Drive Level 1.0µW max
- ESR 50.00kΩ max


## Environmental Parameters

- Drop: 75cm drop (3 times) onto hard wooden board
- Operable Temperature Range: -40 to 85°C
- Storage Temperature Range: -40 to 85°C

## Compliance

- RoHS Status (2011/65/EU) Compliant
- REACh Status Compliant
- MSL Rating (JDEC-STD-033): Not Applicable

**Typical Frequency Stability Characteristics**




## Packaging Details

- Pack Style: Bulk Loose in bulk pack
  Pack Size: 1,000
- *Alternative packing option available*

**USEFUL LINKS**

**Toolbox:**
www.we-online.com/toolbox

**Product Catalog:**
www.we-online.com/products

**CONTACT INFORMATION:**
Würth Elektronik eiSos GmbH & Co. KG
Max-Eyth-Str. 1, 74638 Waldenburg, Germany
Tel: +49(0) 7942 945-0

Email: eiSos@we-online.de
Web: www.we-online.com


chanhvinh.com



# Quartz Crystal Specification

*IQD Part No. + Packaging: LFXTAL014219Bulk*
*Wurth Part No.* ***830014219B***

**Typical Frequency Stability Characteristics**




**CONTACT INFORMATION:**
Würth Elektronik eiSos GmbH & Co. KG
Max-Eyth-Str. 1, 74638 Waldenburg, Germany
Tel: +49(0) 7942 945-0

Email: eiSos@we-online.de
Web: www.we-online.com