chanhvinh.com


DB subminiature switch



Features

- Precision switch with high repeat accuracy
- Available for up to 120 °C operating temperature
- Nominal current up to 10A at 250 VAC
- Various auxiliary actuators (can also be retrofitted) two mounting positions
- Various application-specific contact materials
- Mechanical operational life up to 15 x 10^6 actuations
- Wide variety of terminal types

Dimensions in mm



Technical specifications


Contact configuration	S.P.D.T., S.P.S.T. - N.O., S.P.S.T. - N.C.
Contact gap	< 3 mm (µ)
Switching voltage max.	250 V AC
Switched current	0,1 to 10 A AC, dependig on model (see table)
Operating force	70 to 280 cN without auxiliary actuator, depending on model
Total travel	1,6 mm
Mechanical life	Min. 10 x 10^6 operations (see table)
Electrical life (max. load)	Up to 10^6 operations (see table)
Ambient temperature	-40 to +85 °C/120 °C
Proof tracking index	PTI 175 (PTI 250 on request)
Materials	
Base	PET (UL 94 VO)
Cover	PBT (UL 94 VO)
Actuator	PBT (UL 94 VO) T120 POM (UL 94 HB) T85
Contacts	Ag, AgNi, AuAgPt (Crosspoint)
Terminals	CuZn (silver-plated)
Auxiliary actuator	Stainless steel or plastic
Approvals	dependig on model
Degree of protection (switch interior)	IP50

For detailed information and the layout of the details described above, please do not hesitate to ask for our technical specifications and drawing.


chanhvinh.com

Terminals


Q.C. terminal 2,8 x 0,5




Solder terminal, short




PCB terminal 1,3 x 0,5
straight




PCB terminal 0,6 x 0,5
straight




PCB terminal 0,6 x 0,5
RH-side w/o location pins




PCB terminal 0,6 x 0,5
LH-side w/o location pins



PCB terminal 0,6 x 0,5
RH-side with location pins




PCB terminal 0,6 x 0,5
LH-side with location pins



Side definition with terminals
and location pins


left




right

Auxiliary actuator options

Steel auxiliary actuator



Plastic auxiliary actuator with/without
adjusting screw



Electrical rating and operating life (2)

Electrical rating according to EN 61058	UL 1054	Electrical life at rated load for 40T85* acc. to EN (Operations)	acc. to UL	Mechanical life	Max. operating force (cN)	Code
6A 250 V AC	5 A 125–250 V AC	10.000	6.000	15×10^6	150	1
10 (1,5) A, 250 V AC	10,1 A, 125–250 AC, 1/4 HP, 125 V AC	10.000	6.000	10×10^6	250	2
0.1 A, 250 V AC	0,1 A 125–250 V AC	50.000	100.000	15×10^6	150	3
4 A, 250 V~	4 A, 125–250 V AC	50.000	6.000	15×10^6	90	4
1 A, 250 V AC	1 A, 125–250 V AC	50.000	6.000	15×10^6	70	5*
6 A, 250 V AC	5 A, 125–250 V AC	50.000	6.000	15×10^6	150	6*
10 (1,5) A, 250 V AC	10.1 A, 125–250 V AC, 1/4 HP, 125 V AC	50.000	6.000	10×10^6	280	7*
10 (3) A, 250 V~	10.1 A, 125–250 V AC, 1/4 HP, 125 V AC	10.000	6.000	10×10^6	280	L
3 A, 250 V~	3 A, 125–250 V AC	50.000	6.000	15×10^6	90	M
6 (2) A, 250 V~	5 A, 125–250 V AC	25.000	6.000	15×10^6	150	O
Special models designed for very low switching loads on request						*only T85

Contact configuration (3)

Contact configuration	
Ambient temperature 40T85	Code
S.P.S.T. - N.O.	E
S.P.S.T. - N.C.	F
S.P.D.T.	G
Ambient temperature 40T120	Code
S.P.S.T. - N.O.	A
S.P.S.T. - N.C.	B
S.P.D.T.	C

Terminals (4)

Type of terminal	Code
Q.C. terminal 2.8 x 0.5 mm, straight	B1
Solder terminal, short	A1
PCB terminal 1.3 x 0.5, straight	C1
PCB terminal 0.6 x 0.5, straight	D1
PCB terminal 0.6 x 0.5, right-hand side*	D2
PCB terminal 0.6 x 0.5, left-hand side*	D3
PCB terminal 0.6 x 0.5, right-hand side**	D4
PCB terminal 0.6 x 0.5, left-hand side**	D5
*with location pins ** without location pins	

Auxiliary actuator options (5)

Model	Mounting point	Length	Code
Without lever, spherical head	–	–	AA
lever, radius shape	–	–	BA
Straight	RM rear	4,8	LB
		7	LC
	FM front	42	LD
		7	MB
		9,4	MC
		43,5	MD
Roller	RM rear	2,5	RB
		4,7	RC
		39,7	RD
	FM front	4,7	TB
		7,1	TC
		41,2	TD
Simulated roller	RM rear	2,5	SB
		4,7	SC
		39,7	SD
	FM front	4,7	UB
		7,1	UC
		41,2	UD
Plastic straight	RM rear	7	WB
		14	WC
	FM front	9,4	GB
		16,2	GC
Plastic roller	RM rear	5,2	ZB
	FM front	7,3	OB
Plastic simulated roller	RM rear	5,6	VB
	FM front	7,9	HB

chanhvinh.com

Switching parameters


Option	Type	Max. operating force (cN)	Max. pretravel (mm)	Min. overtravel (mm)	Max. movement differential (mm)	Max. rest position (mm)	Operating point (mm)	Length actuator (mm) ± 0,8
Spherical-head actuator, w/o auxiliary actuator	DB5	70	1,0	0,6	0,1	9,3	8,4 ± 0,3	–
	DB1/O	150	1,0	0,6	0,1	9,3	8,4 ± 0,3	
	DB6	150	1,0	0,6	0,15	9,3	8,4 ± 0,3	
	DB2	250	1,0	0,6	0,1	9,3	8,4 ± 0,3	
	DB7	280	1,0	0,6	0,15	9,3	8,4 ± 0,3	
Actuator with radius, w/o auxiliary actuator	DB5	70	1,0	0,6	0,1	9,3	8,4 ± 0,3	–
	DB1/O	150	1,0	0,6	0,1	9,3	8,4 ± 0,3	
	DB6	250	1,0	0,6	0,15	9,3	8,4 ± 0,3	
	DB2	250	1,0	0,6	0,1	9,3	8,4 ± 0,3	
	DB7	280	1,0	0,6	0,15	9,3	8,4 ± 0,3	

Contact rating at direct voltage


	Switched current, resistive load		Induktive load (L/R = 3 ms)	
Switching voltage	DB 1	DB 2	DB 1	DB 2
12 V	6 A	10 A	6 A	10 A
24 V	3 A	5 A	2 A	4 A
60 V	1 A	1 A	0,5 A	0,5 A
110 V	0,5 A	0,5 A	0,2 A	0,2 A
220 V	0,25 A	0,25 A	0,1 A	0,1 A

Drilling patterns

drilling pattern for PCB terminal 1,3 x 0,5 mm



drilling pattern for PCB terminal 0,6 x 0,5 mm straight/lateral



drilling pattern for PCB terminal 0,6 x 0,5 mm lateral with location pins

