chanhvinh.com

NetKey

Network Components
Keystone Cabling System


NetKey Punchdown Patch Panels


Part Numbers: NK5EPPG24Y, NK5EPPG48Y, NK6PPG24Y, NK6PPG48Y, NK6XPPG24Y, NK6XPPG48Y


© Panduit Corp. 2017


INSTALLATION INSTRUCTIONS


NK410E




















For Technical Support: www.panduit.com/resources/install_maintain.asp

chanhvinh.com







RECOMMENDED CABLE ROUTING




Recommended cable routing for straight panel terminated ports.



Jack Module Removal



Jack Module Installation



COLOR-CODED WIRE POSITIONS

Pin outs	T568B	
5	WHITE/BLUE	T1
4	BLUE	R1
3	WHITE/GREEN	T3
6	GREEN	R3
1	WHITE/ORANGE	T2
2	ORANGE	R2
7	WHITE/BROWN	T4
8	BROWN	R4



Pin outs	T568A	
5	WHITE/BLUE	T1
4	BLUE	R1
1	WHITE/GREEN	T2
2	GREEN	R2
3	WHITE/ORANGE	T3
6	ORANGE	R3
7	WHITE/BROWN	T4
8	BROWN	R4

Notes:

1. NetKey patch panels can terminate most 22-26 AWG solid or stranded wire with a 0.050" (1.27mm) max. o.d., either PVC or plenum rated.
2. Never install wire into a slot previously used for a larger gauge wire.
3. Never install communications wiring during a lightning storm.
4. Never install communications wiring in wet locations unless the module is specifically designed for use in wet locations.
5. Never touch uninsulated communications wiring or terminals unless the communication line has been disconnected at the network interface.
6. Use caution when installing or modifying communication wiring.

For Instructions in Local Languages and Technical Support:
www.panduit.com/resources/install_maintain.asp

PANDUIT
www.panduit.com

E-mail:
techsupport@panduit.com

Phone:
866-405-6654